



INKS & COATINGS

ROYALE BLACK[®] NuTONE[®] 98

PRODUCT PROFILE

NuTone 98 is a medium structure specialty black pigment that gives good dispersion.

NuTone 98 can be used for mass tone in water based primer application. It is preferred as a tinting black with high stability to flooding and floating. With its treated surface, it disperses more easily than other regular furnace carbon blacks.

NuTone 98 carbon black offers very blue undertone and enables high loading.

The dispersion of NuTone 98 carbon black depends on the equipment used and the formulation.

TYPICAL VALUE

NSA m ² /g	STSA m ² /g	OAN CC/100g	Tint Strength % ITRB	Sieve Residue 325M, ppm	Heating Loss (As Shipped) %	Volatile %
34	34	95	65	20	0.6	1.0

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
Water-based Primer	5-10%
Industrial Coatings	5-10%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging - 20kg paper bags

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | **F:** +91 33 2248 0140/2243 6681 | **W:** www.pcblttd.com | **E:** pcbl.specialtyblack@rpsg.in

Revision No. - 03
Issue - Oct. 2024

