

EMULSION E-2353

Description

EMULSION E-2353 is a hard, all acrylic emulsion designed for use in factory-applied, waterborne, interior and exterior wood coatings. Its self-crosslinkable chemistry offers good exterior durability and is recommended for interior/exterior primers and topcoats. If EMULSION E-2353 is too hard, it can be blended with a soft polymer, such as RHOPLEX™ AC-261. It can also be reacted with melamine formaldehyde resins, the combination of which offers an extremely durable finish, ideally suited for long-term warranty applications.

Benefits

- Good Long Term Exterior Durability
- Good Block Resistance
- Good Water Resistance
- Good Heat Age and Mechanical Stability

Applications:

- Interior/Exterior Primers
- Interior/Exterior Topcoats
- Doorskins

Typical Properties

These properties are typical but do not constitute specifications.

Appearance	Opaque
Solids Content, %	45.5
pH	2.5
Viscosity (cps @ 25 °C)	<200
Tg (°C)	40
MFFT (°C)	30
Wet Density (lb/gal)	8.88

RHOPLEX is a trademark of Rohm and Haas Company, or of its subsidiaries or affiliates and is intended to designate goods marketed in North and South America; the same goods may be marketed in other countries, generally under other Company trademark designations.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.

Suggestions for uses of our products or the inclusion of descriptive material from patents and the citation of specific patents in this publication should not be understood as recommending the use of our products in violation of any patent or as permission or license to use any patents of the Rohm and Haas Company.