



COPRO® CP-500

Description	A non-ionic, carboxylated styrene-butadiene copolymer latex that contains an antioxidant and is freeze-thaw stable.	
Application	Used as a polymer modifier in all common hydraulic cements for construction applications such as grouts, mortars and concrete's.	
Features	<p>The proper use of Copro® CP-500 results in grouts, mortars and concrete's that display:</p> <ul style="list-style-type: none"> ◆ Improved adhesion ◆ Increased flexural strength ◆ Excellent hydrolysis resistance ◆ Improved freeze-thaw properties <p>Copro® CP-500 does not contain a defoamer to allow more flexibility to the user regarding choice of defoamer.</p>	
Properties	Nonvolatile Content, %	46.0 – 48.0
	pH	10.5 – 11.5
	Viscosity, cps (Brookfield, LVF, 60rpm/25C°/77°F)	30 - 200
	Wt/gal	8.4 – 8.5
	Tg, °C	-8
Storage	Protect from frost and direct sunlight. Ideal storage temperature is between 5°C and 35°C.	
Packaging Forms	Available in 55 gallon non-returnable drums.	
Important Safety Information	Before using this or any other chemical product, be sure to read and understand the information on the Safety Data Sheet and Product Labels. Remain aware of potential hazards and follow all precautionary measures, handling instructions, and disposal considerations outlined in the SDS and label.	

Rev 12/15

For help in a Chemical Emergency, call CHEMTREC at 1-800-424-9300

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the **H.B. Fuller General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.



H.B. Fuller

H.B. Fuller North America
inquiry@hbfuller.com
Contact us for details