



INKS & COATINGS

ROYALE BLACK[®] NuTONE[®] 36

PRODUCT PROFILE

NuTone 36 is a medium structure specialty black pigment that gives good dispersion.

NuTone 36 is used for general industrial and tinting for solvent and water based coating applications. This is a general purpose grade and can be use for ink, paint, and resin coloring. With its treated surface, it disperses more easily than other Regular Furnace carbon blacks.

NuTone 36 specialty carbon black offers blue undertone. It can also be used in UV curing inks.

The dispersion of NuTone 36 pigment black depends on the equipment used and the formulation.

TYPICAL VALUE

NSA m ² /g	STSA m ² /g	OAN CC/100g	Tint Strength % ITRB	Sieve Residue 325M, PPM	Heat Loss (As Shipped) %	Volatile %
104	102	95	125	20	0.8	2.0

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
Paints & Coatings	2-8%
Offset Inks	10-20%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging - 20kg paper bags

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | **F:** +91 33 2248 0140/2243 6681 | **W:** www.pcbltd.com | **E:** pcbl.specialtyblack@rpsg.in

Revision No. - 02
Issue - Oct. 2024

