

HYBASE C313

Print Date: 03/12/2019 Version: 1.6 Revision Date: 09/04/2018 SECTION 1. PRODUCT AND COMPANY IDENTIFICATION Product name: **HYBASE C313** Product Use Description: Additive Synonyms: calcium sulfonate detergent additive LANXESS Solutions US Inc. Company: 2 Armstrong Road Shelton, Ct 06484 United States of America (USA) Telephone: (US) +1 866-430-2775 **Emergency telephone** CHEMTREC: (24 hours) 800-424-9300 number: : US: 800-292-5898 (Technical inquiries) For additional emergency telephone numbers see section 16 of the Safety Data Sheet. Prepared by Product Safety Department (US) +1 866-430-2775 MSDSRequest@lanxess.com Recommended use of the chemical and restrictions on use Recommended use : Additive Restrictions on use Restricted to professional users. :

SECTION 2. HAZARDS IDENTIFICATION

Form	viscous liquid
Colour	brown
Odour	oily

GHS Classification

Eye irritation

: Category 2A

GHS label elements



HYBASE C313

sion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
Signal word	: Warning	
Hazard pictograms		
Hazard statements	: H319 Causes serious eye irrita	ition.
Other hazards	None	
Precautionary statements	 Prevention: P264 Wash skin thoroughly aft P280 Wear eye protection/ face Response: P305 + P351 + P338 IF IN EYE for several minutes. Remove co easy to do. Continue rinsing. P337 + P313 If eye irritation per attention. 	e protection. ES: Rinse cautiously with water ontact lenses, if present and
Carcinogenicity:		
IARC	No component of this product pres equal to 0.1% is identified as proba human carcinogen by IARC.	
OSHA	No component of this product pres equal to 0.1% is on OSHA's list of	ent at levels greater than or regulated carcinogens.
NTP	No component of this product pres equal to 0.1% is identified as a kno by NTP.	sent at levels greater than or

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	>= 30 - < 50 %
calcium carbonate	471-34-1	>= 20 - < 30 %
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	>= 10 - < 20 %
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	>= 10 - < 20 %
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 5 - < 10 %
calcium dihydroxide	1305-62-0	>= 1 - < 2.5 %



HYBASE C313

Version: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019	
SECTION 4. FIRST AID MEASU	RES		
If inhaled	: Remove to fresh air. Give oxygen or artificial respiration If symptoms persist, call a physic		
In case of skin contact	 Wash off with warm water and so Cool skin rapidly with cold water material. If skin irritation persists, call a ph Wash contaminated clothing before 	after contact with molten	
In case of eye contact	 Rinse thoroughly with plenty of w Keep eye wide open while rinsing If eye irritation persists, consult a 	g.	
If swallowed	Aspiration may cause pulmonary If symptoms persist, call a physic immediately.	 If swallowed, DO NOT induce vomiting. Aspiration may cause pulmonary oedema and pneumonitis. If symptoms persist, call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person. 	
Most important symptoms and effects, both acute and delayed	: irritant effects		
Notes to physician	: For specialist advice physicians s Information Service.	should contact the Poisons	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: (on small fires) Carbon dioxide (CO2) Dry chemical Dry sand Extinguishing media - large fires Foam Water mist	
Unsuitable extinguishing media	: Water spray jet	
Specific hazards during firefighting	 Do not use a solid water stream as it may scatter and spread fire. Burning produces irritant fumes. Exposure to decomposition products may be a hazard to health. 	t

LANXESS Energizing Chemistry

SAFETY DATA SHEET

HYBASE C313

ersion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
Specific extinguishing methods	: Cool containers/tanks with wat Prevent fire extinguishing wate water or the ground water syst	er from contaminating surface
Special protective equipment for firefighters	: Self-contained breathing appa operated in positive pressure r Body covering protective cloth	mode.
ECTION 6. ACCIDENTAL RELE	ASE MEASURES	
Personal precautions, protective equipment and emergency procedures	 Evacuate personnel to safe an Ensure adequate ventilation. Wear suitable protective clothi protection. Material can create slippery control 	ng, gloves and eye/face

: Do not allow contact with soil, surface or ground water. Do not flush into surface water or sanitary sewer system.

: Ventilate the area. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust). Pick up and transfer to properly labelled containers. Large spills should be collected mechanically (remove by

pumping) for disposal.

SECTION 7. HANDLING AND STORAGE

Environmental precautions

Methods and materials for

containment and cleaning up

Advice on safe handling	:	Handle in accordance with good industrial hygiene and safety practice. Use only in well-ventilated areas. Remove all sources of ignition. Ensure all equipment is electrically grounded before beginning transfer operations.
Conditions for safe storage	:	Keep only in the original container in a cool, well ventilated place away from oxidizing agents. Keep away from fire, sparks and heated surfaces. Protect from contamination.
Materials to avoid	:	Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



HYBASE C313

Version: 1.6

Revision Date: 09/04/2018

Print Date: 03/12/2019

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Distillates (petroleum), solvent- refined heavy paraffinic	64741-88-4	TWA	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
		PEL (particulate)	5 mg/m3	CAL PEL
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
calcium dihydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
		TWA	5 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL

Engineering measures	: Use with adequate ventilation.	
Personal protective equipme	ent	
Respiratory protection	 not required under normal use In the case of vapour formation use a rapproved filter. Respirator with combination filter for variable. 	•
Hand protection Remarks	: PVC or other plastic material gloves N handling hot material, use heat resista	
Eye protection	: Safety goggles	
Skin and body protection	: Long sleeved clothing	
SAP 6.0 SDS 2012-2 NA GHS	5 / 13	SDS Number: 40000003931



HYBASE C313

Version: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
	Remove and wash contaminated	d clothing before re-use.
Hygiene measures	 Handle in accordance with good practice. Avoid contact with skin, eyes and Avoid breathing vapours, mist or Wash hands before breaks and Keep away from food and drink. When working with hot material, Remove and wash contaminated Keep working clothes separately 	d clothing. gas. at the end of workday. avoid contact with skin. d clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous liquid	
Color	: brown	
Odor	: oily	
Odour Threshold	: No data available	
рН	: No data available	
Melting point/range	: No data available	
Boiling point/boiling range	: No data available	
Evaporation rate	: No data available	
Flash point	: 220 °C Method: Cleveland open cup ASTM D 92	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: 0.008 hPa (20 °C)	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: >1 g/cm3 (25 °C)	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: partly soluble Solvent: Organic solvents	
Partition coefficient: n-	: No data available	
SAP 6.0 SDS 2012-2 NA GHS	6 / 13	SDS Number: 40000003931



HYBASE C313

ersion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
octanol/water		
Auto-ignition temperature	: No data available	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: > 30 mm2/s (40 °C)	
Molecular weight	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Will not occur. Stable under normal conditions.
Conditions to avoid	: Exposure to moisture Contamination
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	 Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Sulphur oxides Oxides of calcium

SECTION 11. TOXICOLOGICAL INFORMATION

Product:		
Acute oral toxicity	 LD50 Oral (Rat): > 20 g/kg Remarks: Information given is based similar substances. 	d on data obtained from
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/ Method: Calculation method	kg
Components:		
5.0 SDS 2012-2 NA GHS	7 / 13	SDS Number: 4000000



HYBASE C313

rsion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
calcium carbonate: Acute oral toxicity	: LD50 (Rat): 6,450 mg/kg	
Sulfonic acids, petroleur Acute oral toxicity	n, calcium salts: : LD50 (Rat, male and female): > Method: OECD Test Guideline 4 GLP: yes	
Acute dermal toxicity	: LD50 (Rabbit, male and female) Method: OECD Test Guideline 4 GLP: yes	
calcium dihydroxide: Acute oral toxicity	: LD50 (Rat): 7,340 mg/kg	
Skin corrosion/irritation		
Product: Remarks: Not classified de	ue to lack of data.	
<u>Components:</u> calcium carbonate: Species: Rabbit Result: No skin irritation		
calcium dihydroxide: Result: Irritating to skin.		
Serious eye damage/eye	irritation	
<u>Components:</u> calcium carbonate: Species: Rabbit Result: No eye irritation		
calcium dihydroxide: Species: Rabbit Result: Risk of serious dar Method: Draize Test	nage to eyes.	
Respiratory or skin sens	itisation	
<u>Product:</u> Result: Does not cause sk	in sensitisation.	
Components:	10-16-alkyl derivs., calcium salts:	

Result: Probability or evidence of low to moderate skin sensitisation rate in humans

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

SAP 6.0 SDS 2012-2 NA GHS	8 / 13	SDS Number: 40000003931



HYBASE C313

sion: 1.6	Revision Date: 09/04/2018	Print Date: 03/12/2019
Result: Probability or evide	nce of low to moderate skin sensitisatior	n rate in humans
Sulfonic acids, petroleun Result: Probability or evide	n, calcium salts: nce of low to moderate skin sensitisatior	n rate in humans
calcium dihydroxide: Assessment: Did not cause	e sensitisation on laboratory animals.	
Carcinogenicity		
IARC	No component of this product prese equal to 0.1% is identified as proba human carcinogen by IARC.	
OSHA	No component of this product prese equal to 0.1% is on OSHA's list of r	
NTP	No component of this product prese equal to 0.1% is identified as a kno by NTP.	
Reproductive toxicity		
Components: calcium carbonate: Effects on fertility	: Species: Rat Application Route: Oral	
Reproductive toxicity - Assessment	: No toxicity to reproduction No effects on or via lactation	
STOT - single exposure		
<u>Components:</u> calcium dihydroxide: Assessment: May cause re	espiratory irritation.	
Aspiration toxicity		
Product: No aspiration toxicity class	ification	
Further information		
<u>Product:</u> Remarks: No data is availa	ble on the product itself.	



HYBASE C313

Version: 1.6

Revision Date: 09/04/2018

Print Date: 03/12/2019

SECTION 12. ECOLOGICAL INFORMATION Ecotoxicity <u>Product:</u>

Toxicity to fish

Remarks: No data available

Ecotoxicology Assessment

Components:

Sulfonic acids, petroleum, calcium salts:

:

Toxicity to fish	:	LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae	:	EbC50 (Green algae (Scenedesmus subspicatus)): > 100 mg/l Exposure time: 72 h Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 201 GLP: yes
		ErC50 (Green algae (Scenedesmus subspicatus)): > 100 mg/l Exposure time: Test Type: static test Analytical monitoring: no Method: OECD Test Guideline 201 GLP: yes
calcium dihydroxide:		
Toxicity to fish	:	LC50 (Gambusia affinis (Mosquito fish)): 160 mg/l Exposure time: 96 h Test Type: static test
Ecotoxicology Assessment		
Acute aquatic toxicity	:	Harmful to aquatic life.

SAFETY DATA SHEET

HYBASE C313

ersion: 1.6	Revisi	on Date: 09/04/2018	Print Date: 03/12/2019
Persistence and degradat	oility		
Product:			
Biodegradability	: Re	sult: No data available	
Impact on Sewage Treatment	: Ma	y be separated mechanically in	waste water plants.
Components:			
Sulfonic acids, petroleum	, calcium	salts:	
Biodegradability	Inc Re Bic Ex	robic oculum: activated sludge sult: Not readily biodegradable. odegradation: 8.6 % posure time: 28 d .P: yes	
Bioaccumulative potentia			
Product:			
Bioaccumulation	: Re	marks: No data available	
Mobility in soil			
Product:			
Mobility	: Re	marks: No data available	
Other adverse effects			
Product:			
Results of PBT and vPvB assessment		is mixture contains no substanc rsistent, bioaccumulating and to	
Additional ecological information	: No	information on ecology is avail	able.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Dispose of waste product or used containers according to local regulations. Waste must be classified and labelled prior to recycling or disposal. Do not dispose of waste into sewer.



HYBASE C313

Version: 1.6

Revision Date: 09/04/2018

Print Date: 03/12/2019

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

National Regulations

49 CFR Not regulated as a dangerous good

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)	
naphthalene	91-20-3	100	*	
*: Calculated RQ exceeds re	asonably attainable u	pper limit.		
SARA304 Reportable Quar	ntity			
This material does not conta	in any components w	ith a section 304 EHS	RQ.	
SARA 311/312 Hazards	: Serious eye dam	age or eye irritation		
SARA 302		this material are subject SARA Title III, Section		
SARA 313	known CAS num	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.		
US State Regulations				



HYBASE C313

Version: 1.6

Revision Date: 09/04/2018

Print Date: 03/12/2019

California Prop. 65

WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

The components of this product are reported in the following inventories:

KECIOn the inventory, or in compliance with the inventoryPICCSOn the inventory, or in compliance with the inventoryIECSCOn the inventory, or in compliance with the inventoryTCSIOn the inventory, or in compliance with the inventoryUS.TSCAOn TSCA Inventory	PICCS IECSC TCSI	On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory
--	------------------------	---

SECTION 16. OTHER INFORMATION

Further information

Other Emergency Phone Number

Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
<u>Mexico:</u>		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.