

TECHNICAL DATA SHEET

VANCRYL® 950

Acrylic Emulsion

INTRODUCTION

VANCRYL 950 emulsion is a very low Tg acrylic polymer designed for film printing applications in the graphic arts industry. Inks made from this polymer exhibit excellent gloss, adhesion to polyolefins, ice water crinkle resistance, and fine printing characteristics. VANCRYL 950 also has the unusual combined properties of excellent resolubility and fast drying. These properties are needed when converting flexible packaging printing from solvent-based to water-based formulations.

VANCRYL 950 emulsion is compatible with VANCRYL 68 pigment dispersions as well as other commonly used pigment dispersions. It also exhibits excellent compatibility with additives such as surfactants, adhesion promoters, alcohols, and waxes.

This polymer can be used as the backbone of printing inks and overprint coatings where various COF or slide angle requirements are needed, from a range of 0.25 to 0.45.

KEY PERFORMANCE PROPERTIES

- · Fast drying with excellent early water resistance and resolubility
- Excellent wetting of and adhesion to polyolefin films
- Very good gloss for packaging applications
- · Excellent ice water crinkle resistance
- Excellent transfer and printability

TYPICAL PROPERTIES	VALUES
VOC, %	<0.6
рН	8.3
Viscosity, (#4 spindle, 30 rpm), cP	3,000
Solids, %	50
Density, lbs/gal	8.6
Molecular Weight (Mn)	>200,000
Tg, °C	-50

• Worldwide Contact Info: www.allnex.com •

Disclaimer: Allnex Group companies ("Allnex") decline any liability with respect to the use made by anyone of the information contained herein. The information contained herein represents Allnex's best knowledge thereon without constituting any express or implied guarantee or warranty of any kind (including, but not limited to, regarding the accuracy, the completeness or relevance of the data set out herein). Nothing contained herein shall be construed as conferring any license or right under any patent or other intellectual property rights of Allnex or of any third party. The information relating to the products is given for information purposes only. No guarantee or warranty is provided that the product and/or information is adapted for any specific use, performance or result and that product and/or information do not infringe any Allnex and/or third party intellectual property rights. The user should perform its own tests to determine the suitability for a particular purpose. The final choice of use of a product and/or information as well as the investigation of any possible violation of intellectual property rights of Allnex and/or third parties remains the sole responsibility of the user.

TRADEMARK NOTICE: The * indicates a Registered Trademark in the United States and the ™ or * indicates a Trademark in the United States. The mark may also be registered, the subject of an application for registration or a trademark in other countries.