

SAFETY DATA SHEET

6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

SECTION 1. IDENTIFICATION

Product name : 6478 F
Product code : 00000000002471128

Manufacturer or supplier's details

Company : LANXESS Corporation
Product Safety & Regulatory Affairs
111 RIDC Park West Drive
15275-1112 Pittsburgh, United States of America

Responsible Department : +1800LANXESS

Emergency telephone number : Chemtrec (800) 424-9300
International (703) 527-3887
Lanxess Emergency Phone (800) 410-3063

Recommended use of the chemical and restrictions on use

Recommended use : inorganic pigment

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system)

GHS label elements

Hazard pictograms : 

Signal word : Danger

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Hazard statements : Causes skin irritation.
Causes serious eye damage.
May cause cancer.
Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage:
Store locked up.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Crystalline Quartz Silica	14808-60-7	>= 10 - < 20
Manganese Oxide	1313-13-9	>= 10 - < 20
manganese (Powder)	7439-96-5	>= 5 - < 10
aluminium oxide	1344-28-1	>= 1 - < 5
calcium oxide (Solution)	1305-78-8	>= 1 - < 5
magnesium oxide	1309-48-4	>= 1 - < 5

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

diphosphorus pentaoxide	1314-56-3	>= 1 - < 5
-------------------------	-----------	------------

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- If inhaled : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Get medical attention.
If unconscious, place in recovery position and get medical attention immediately.
Maintain open airway.
Loosen tight clothing such as a collar, tie, belt or waistband.
If not breathing, if breathing is irregular or respiratory arrest occurs, provide artificial respiration, or oxygen by a trained professional, using a pocket type respirator.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Continue to rinse for at least 10 minutes.
Get medical attention.
Wash clothing before reuse.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
Get medical attention if symptoms appear.
- If swallowed : Rinse mouth with water.
Do not induce vomiting unless directed to do by medical personnel.
Get medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed

- Effects : Causes skin irritation.
Causes serious eye damage.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure if inhaled.
May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing : None known.

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

media

Hazardous combustion products : Metal oxides
Oxides of phosphorus

Further information : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training.
Put on appropriate personal protection equipment.
Do not touch or walk through spilled material.
Evacuate personnel to safe areas.
Keep unnecessary and unprotected personnel from entering.
Provide adequate ventilation.
Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Move containers from spill area.
Vacuum or sweep up material and place in a designated, labeled waste container.
Dispose of wastes in an approved waste disposal facility.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid inhalation, ingestion and contact with skin and eyes.
Use only with adequate ventilation.
Remove contaminated clothing and protective equipment before entering eating areas.
Workers should wash hands and face before eating, drinking and smoking.
Put on appropriate personal protection equipment.
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Conditions for safe storage : Store in accordance with local regulations.
Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink.

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Keep container closed when not in use.
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Do not store in unlabeled containers.
Use appropriate container to avoid environmental contamination.
Empty containers retain residue and can be dangerous.
Do not reuse container.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Crystalline Quartz Silica	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
Manganese Oxide	1313-13-9	C	5 mg/m ³ (Manganese)	OSHA Z-1
		TWA (Inhalable particulate matter)	0.1 mg/m ³ (Manganese)	ACGIH
		TWA (Respirable particulate matter)	0.02 mg/m ³ (Manganese)	ACGIH
		manganese (Powder)	7439-96-5	C (Fumes)
		TWA (Inhalable particulate matter)	0.1 mg/m ³ (Manganese)	ACGIH
		TWA (Respirable particulate matter)	0.02 mg/m ³ (Manganese)	ACGIH
aluminium oxide	1344-28-1	TWA (total dust)	15 mg/m ³	OSHA Z-1

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH
calcium oxide (Solution)	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	5 mg/m3	OSHA Z-1
magnesium oxide	1309-48-4	TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (fume, total particulate)	15 mg/m3	OSHA Z-1

Engineering measures : If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal protective equipment

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Recommended:
NIOSH approved, air-purifying particulate respirator with N-95 filters.

Hand protection

Remarks : Permeation resistant gloves.

Eye protection : Tightly fitting safety goggles

Skin and body protection : Permeation resistant clothing and foot protection.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Appropriate techniques should be used to remove potentially contaminated clothing.
Wash contaminated clothing before reusing.
Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : brown

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Odour : odourless

Odour Threshold : No data available

pH : 4 - 8
Concentration: 5 %

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Self-ignition : Auto-ignition temperature
Not applicable

Burning number : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : Not applicable

Relative density : No data available

Density : No data available

Bulk density : 300 - 1,000 kg/m³

Solubility(ies)
Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : Not applicable

Viscosity, kinematic : No data available

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Explosive properties : No data available
Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : The product is chemically stable.
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : No specific data.
Incompatible materials : No specific data.
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

The most important known symptoms and effects are described in Section 2 and/or Section 4.

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Manganese Oxide:

Acute oral toxicity : LD50 (Rat): 3,478 mg/kg

manganese (Powder):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

aluminium oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

calcium oxide (Solution):

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 425
GLP: yes

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Acute dermal toxicity : LD50 (Rabbit, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

magnesium oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

aluminium oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

calcium oxide (Solution):

Result : Irritating to skin.

diphosphorus pentaoxide:

Assessment : Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

aluminium oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

calcium oxide (Solution):

Result : Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Components:

aluminium oxide:

Test Type : Draize Test
Exposure routes : Skin contact
Species : Guinea pig
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

aluminium oxide:

Genotoxicity in vitro : Test system: Bacteria
Method: OECD Test Guideline 471
Result: negative

diphosphorus pentaoxide:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes
Remarks: Test results on an analogous product

Test Type: Ames test
Test system: Escherichia coli
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes
Remarks: Test results on an analogous product

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
Remarks: Test results on an analogous product

Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster fibroblasts
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Carcinogenicity

May cause cancer.

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Components:

Crystalline Quartz Silica:

Result : Excessive exposure to airborne crystalline silica can cause fibrotic lung damage, with scarring of the lungs with cough and shortness of breath. This is called "Silicosis". This is generally a slowly developing fibrotic disease as symptoms are usually delayed for 10 years or more. Symptoms are dyspnea, chest pain, breathlessness, and cough. The chronic lung scarring developed from the silica dust causes a progressive massive fibrosis. This may lead to increased susceptibility to tuberculosis.

IARC	Group 1: Carcinogenic to humans Crystalline Quartz Silica (Silica dust, crystalline)	14808-60-7
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
OSHA	OSHA specifically regulated carcinogen Crystalline Quartz Silica (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen Crystalline Quartz Silica (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

Not classified based on available information.

Components:

calcium oxide (Solution):

Effects on foetal development : Species: Rat
Application Route: Oral
Duration of Single Treatment: 10 d
Developmental Toxicity: NOAEL: >= 680 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic potential
GLP: no

Species: Mouse
Application Route: Oral
Duration of Single Treatment: 10 d
General Toxicity Maternal: NOAEL: >= 440 mg/kg body weight
Developmental Toxicity: NOAEL: >= 440 mg/kg body weight
Method: OECD Test Guideline 414
GLP: no

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

STOT - single exposure

Not classified based on available information.

Components:

aluminium oxide:

Assessment : May cause respiratory irritation.

calcium oxide (Solution):

Assessment : May cause respiratory irritation.

magnesium oxide:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Crystalline Quartz Silica:

Exposure routes : Inhalation
Target Organs : Lungs
Assessment : Causes damage to organs through prolonged or repeated exposure.

Manganese Oxide:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

manganese (Powder):

Target Organs : Central nervous system
Assessment : May cause damage to organs through prolonged or repeated exposure.

aluminium oxide:

Exposure routes : Inhalation
Target Organs : Lungs
Assessment : May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Repeated dose toxicity

Components:

Manganese Oxide:

Species : Rat
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 10 d
Dose : 68 mg/m³
Remarks : Subacute toxicity

Species : Mammal - species unspecified
NOAEL : 1 mg/m³
Application Route : Inhalation
Exposure time : 9 Months
Dose : 1 mg/m³
Remarks : Chronic toxicity

magnesium oxide:

Species : Rat
NOAEL : < 1,120 mg/m³
Application Route : Inhalation
Exposure time : 29 d
Remarks : Chronic toxicity

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Manganese Oxide:

Toxicity to fish : LC0 (Oncorhynchus mykiss (rainbow trout)): > 0.05 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes
Remarks: Fresh water

Toxicity to daphnia and other aquatic invertebrates : EC0 (Daphnia magna (Water flea)): > 0.0735 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes
Remarks: Fresh water

Toxicity to algae/aquatic plants : EC0 (algae): > 0.07 mg/l
Exposure time: 72 h

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Method: OECD Test Guideline 201
GLP: yes
Remarks: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (Water flea)): 0.00735 mg/l
Exposure time: 8 d
Method: OECD Test Guideline 211
GLP: yes
Remarks: Fresh water

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
GLP: yes
Remarks: Fresh water

NOEC (activated sludge): 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
GLP: yes
Remarks: Fresh water

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility

manganese (Powder):

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 1,000 mg/l
Exposure time: 48 h

aluminium oxide:

Toxicity to fish : LC50 (Salmo trutta (brown trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

calcium oxide (Solution):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 50.6 mg/l
Exposure time: 96 h

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Method: OECD Test Guideline 203
GLP: yes
Remarks: Fresh water

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 49.1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC10 (Pseudokirchneriella subcapitata (microalgae)): 79.22 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

EC50 (Pseudokirchneriella subcapitata (microalgae)): 184.57 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC10 (activated sludge): 300.4 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
GLP: yes

diphosphorus pentaoxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 203
GLP: yes
Remarks: Fresh water

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 202
GLP: yes
Remarks: Fresh water

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 66.5 mg/l
End point: Growth rate
Exposure time: 72 h
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes
Remarks: Fresh water

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

NOEC (Desmodesmus subspicatus (green algae)): 25 mg/l
End point: Growth rate
Exposure time: 72 h
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes
Remarks: Fresh water

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
End point: Respiration inhibition
Exposure time: 3 h
Analytical monitoring: no
Method: OECD Test Guideline 209
GLP: yes
Remarks: Fresh water

Persistence and degradability

Components:

manganese (Powder):

Biodegradability : Result: The methods for determining the biological degradability are not applicable to inorganic substances.

aluminium oxide:

Biodegradability : Result: The methods for determining the biological degradability are not applicable to inorganic substances.

magnesium oxide:

Biodegradability : Result: The methods for determining the biological degradability are not applicable to inorganic substances.

diphosphorus pentaoxide:

Biodegradability : Result: The methods for determining the biological degradability are not applicable to inorganic substances.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

RCRA - Resource Conservation and Recovery Authorization Act : If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

Waste from residues : The generation of waste should be avoided or minimized wherever possible.
Dispose of wastes in an approved waste disposal facility. This material and its container must be disposed of in a safe way.
The product should not be allowed to enter drains, water courses or the soil.
Waste disposal should be in accordance with existing federal, state, provincial and/or local environmental controls.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(ARSENIC, LEAD)

Class : 9
Packing group : III
Labels : 9



ERG Code : 171
RQ : 2,785.52 lb
Marine pollutant : no

When in individual containers of less than the Product RQ, this material ships as non-regulated.

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Hazard and Handling Notes. : Keep separated from foodstuffs

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
arsenic	7440-38-2	1	2785
lead	7439-92-1	10	30959

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Manganese Oxide	1313-13-9	>= 10 - < 20 %
manganese (Powder)	7439-96-5	>= 5 - < 10 %
aluminium oxide	1344-28-1	>= 1 - < 5 %

US State Regulations

Massachusetts Right To Know

Crystalline Quartz Silica	14808-60-7	10 - 20
manganese (Powder)	7439-96-5	5 - 10
aluminium oxide	1344-28-1	1 - 5
calcium oxide (Solution)	1305-78-8	1 - 3
magnesium oxide	1309-48-4	1 - 5
diphosphorus pentaoxide	1314-56-3	1 - 3
arsenic	7440-38-2	< 0.1
chromium	7440-47-3	< 0.1
Cadmium	7440-43-9	< 0.1

Pennsylvania Right To Know

Umber	12713-03-0	> 1
-------	------------	-----

SAFETY DATA SHEET



6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

Crystalline Quartz Silica	14808-60-7	10 - 20
Manganese Oxide	1313-13-9	10 - 20
water	7732-18-5	> 1
manganese (Powder)	7439-96-5	5 - 10
aluminium oxide	1344-28-1	1 - 5
calcium oxide (Solution)	1305-78-8	1 - 3
magnesium oxide	1309-48-4	1 - 5
diphosphorus pentaoxide	1314-56-3	1 - 3

California Prop. 65

WARNING: This product can expose you to chemicals including Crystalline Quartz Silica, arsenic, lead, chromium, Cadmium, which is/are known to the State of California to cause cancer, and lead, chromium, Cadmium, mercury (Inorganic), which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

TSCA inventory

TSCA : This material is included in the TSCA Inventory as a naturally occurring chemical substance as described in 40 CFR 710.4 (b).

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION


Further information

SAFETY DATA SHEET

6478 F

Version 1.1 Revision Date: 10/10/2020 SDS Number: 215000001112 Date of last issue: 10/03/2020
Country / Language: US / EN

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EC_x - Concentration associated with x% response; EHS - Extremely Hazardous Substance; EL_x - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErC_x - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC₅₀ - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC₅₀ - Lethal Concentration to 50 % of a test population; LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety

SAFETY DATA SHEET



6478 F

Version	Revision Date:	SDS Number:	Date of last issue: 10/03/2020
1.1	10/10/2020	215000001112	Country / Language: US / EN

and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/10/2020

The data contained in this Safety Data Sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered to be a guidance for processing and does not contain any warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is the responsibility of the recipient of the product to ensure that any proprietary rights and existing laws and legislation are observed.