

ALKEST® SP 80 K

DESCRIPTION

ALKEST® SP 80 K is a sorbitan ester of oleic acid

PHYSICAL PROPERTIES¹

| | |
|---------------------------|-------------------------|
| Appearance (25°C) | Clear Liquid |
| Active Content, wt% | 100% |
| Hydroxyl Number | 202 mgKOH/g |
| HLB | 4.3 |
| Flash Point (Open cup) | > 175 °C |
| pH (10 wt% aqueous, 25°C) | 7.0 |
| Viscosity (25°C) | 1100 mPa.s |
| Density (25°C) | 1.000 g/cm ³ |
| Relative Vapor Pressure | < 0.0013 kPa |
| Saponification Value | 153 mgKOH/g |
| Water Content | < 1.0 % |

CHARACTERISTICS AND BENEFITS

- Versatile surfactant for a wide variety of applications
- Oil Soluble
- Bio-based surfactant
- Compatible with cationic, anionic and other nonionic surfactants

STORAGE AND HANDLING

Store in a covered, well-ventilated area, away from sunlight and away from sources of heat or open flame. Ensure that the storage locale has adequate control of temperature, pressure, and humidity. Keep the containers hermetically sealed when not in use. For more information, consult the Safety Data Sheet (SDS).

SHELF LIFE

24 Months from manufacturing date

STANDARD PACKAGING

Drums (473 lbs, 215 kg)

Bulk

Samples

ADDITIONAL INFORMATION

| | |
|---------------------------|-----------------|
| Sourcing | Oleo |
| Percent Renewable Content | 100% |
| INCI Name | Sorbitan Oleate |
| NF Compliant | No |
| FCC Compliant | No |
| RSPO (Mass Balance) | Available |
| Non-GMO | Available |
| Kosher/Halal Compliant | Yes |

REGULATORY

| | |
|-------------------------------|----------------|
| CAS Registry No. ² | 1338-43-8 |
| USA (TSCA) | Listed |
| Canada (DSL) | Listed |
| Australia (AICS) | Listed |
| China (IECSC) | Listed |
| Korea (ECL) | Listed |
| New Zealand (NZIoC) | Listed |
| Philippines (PICCS) | Listed |
| US DOT | Not classified |

¹The physical properties described in the table are only for informational purposes and may be changed without notice. Please contact Oxiteno for updated data. ²Chemical Abstracts Service.

DISCLAIMER

This information is given in good faith, based on Oxiteno's current knowledge on the subject, and is purely indicative. Any information, including suggestions for using the products, should not preclude experimental testing and verification, which are essential to ensure the suitability of the products to each specific application. All users shall also abide by local laws and obtain all necessary permits. When handling the product, consult the safety data sheet. In case of questions or additional needs, please contact Oxiteno through our customer service channels.

COMMERCIAL OFFICES

| Brazil | Colombia | Argentina | Mexico | United States |
|---------------------|------------------------------|-------------------------------|----------------------------|-------------------------|
| +55 11 3177 6102 | +57 11 555 0070 | +54 11 4115 5600 | +52 55 5322 0560 | +1 346 718 6200 |
| oxiteno@oxiteno.com | oxiteno.colombia@oxiteno.com | oxiteno.argentina@oxiteno.com | oxiteno.mexico@oxiteno.com | oxiteno.usa@oxiteno.com |