

## SAFETY DATA SHEET

---

### 1. IDENTIFICATION

**Product Name:** CYMEL® UI-21-E Resin  
**Synonyms:** None  
**Product Description:** Isobutylated urea-formaldehyde resin in ethanol  
**Molecular Formula:** Polymer  
**Molecular Weight:** Polymer  
**Intended/Recommended Use:** Raw material for surface coatings

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

**For Product and all Non-Emergency Information call** your local Allnex contact point or contact us at <http://www.allnex.com/contact>

**EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:**

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC)

See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with the ® or ™ are registered, unregistered or pending trademarks of Allnex IP S.à.r.l. or its directly or indirectly affiliated Allnex Group companies.

---

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable Liquids Hazard Category 3  
Carcinogenicity Hazard Category 1B  
Reproductive Toxicant Hazard Category 1A  
Serious Eye Damage / Eye Irritation Hazard Category 1  
Skin Sensitizer Hazard Category 1A  
Aquatic Environment Chronic Hazard Category 4

#### LABEL ELEMENTS



#### Signal Word

DANGER

#### Hazard Statements

Flammable liquid and vapor  
May cause cancer  
May damage fertility or the unborn child  
Causes serious eye damage

May cause an allergic skin reaction  
 May cause long lasting harmful effects to aquatic life

### Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Keep container tightly closed.  
 Ground/Bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Obtain special instructions before use.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Avoid release to the environment.  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 Immediately call a POISON CENTER or doctor/physician.  
 Specific treatment (see supplemental first aid instructions on this label).  
 Wash contaminated clothing before reuse.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local and national regulations.

### Hazards Not Otherwise Classified (HNOC), Other Hazards

Not applicable

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification	Carcinogen
Urea P/W formaldehyde, isobutylated 68002-18-6	76 - 80	Aquatic Chronic 4 (H413)	-
Ethanol 64-17-5	13 - 15	Flam. Liq. 2 (H225) Skin Irrit. 3 (H316) Eye Irrit. 2A (H319)	IARC 1 NTP ACGIH A3
Isobutanol 78-83-1	2 - 4	Flam. Liq. 3 (H226) STOT SE 3 (H335) STOT SE 3 (H336) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-
Formaldehyde 50-00-0	<= 0.8	Carc. 1B (H350) Muta. 2 (H341) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 2 (H401)	IARC 1 NTP ACGIH A2

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

---

## 4. FIRST AID MEASURES

### First-aid Measures

**Inhalation:**

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

**Skin Contact:**

Wash immediately with plenty of water and soap.

**Eye Contact:**

Rinse immediately with plenty of water for at least 15 minutes.

**Ingestion:**

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

### Most Important Symptoms and Effects, Acute and Delayed

None known.

### Immediate Medical Attention and Special Treatment

**Notes To Physician:**

No specific measures have been identified.

---

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:**

Use water spray, alcohol foam, carbon dioxide or dry chemical to extinguish fires. Water stream may be ineffective.

**Unsuitable Extinguishing Media:**

full water jet.

**Protective Equipment:**

Firefighters, and others exposed, wear self-contained breathing apparatus.

**Special Hazards:**

Keep containers cool by spraying with water if exposed to fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:**

Where exposure level is known, wear approved respirator suitable for level of exposure. Where exposure level is not known, wear approved, positive pressure, self-contained respirator. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

**Methods For Cleaning Up:**

Remove sources of ignition. Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

**Environmental Precautions:**

Avoid release to the environment.

**References to other sections:**

See Sections 7, 8 and 13 for additional information.

---

## 7. HANDLING AND STORAGE

### HANDLING

**Precautions:** Keep away from heat, sparks and open flame. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment.

**Special Handling Statements:** Provide good ventilation of working area (local exhaust ventilation if necessary). During processing and handling of the product, comply with the indicative occupational exposure limit values. Do not store or transport together with foodstuffs. Containers must be bonded and grounded when pouring or transferring material.

### STORAGE

Areas containing this material should have fire safe practices and electrical equipment in accordance with applicable regulations and/or guidelines. Standards are primarily based on the material's flashpoint, but may also take into account properties such as miscibility with water or toxicity. All local and national regulations should be followed. In the Americas, National Fire Protection Association (NFPA) 30: Flammable and Combustible Liquids Code, is a widely used standard. NFPA 30 establishes storage conditions for the following classes of materials: Class I Flammable Liquids, Flashpoint <37.8 °C. Class II Combustible Liquids, 37.8 °C < Flashpoint <60 °C. Class IIIa Combustible Liquids, 60 °C < Flashpoint < 93 °C. Class IIIb Combustible Liquids, Flashpoint > 93 °C.

**Storage Temperature:** Store at -20 - 30 °C -4 - 86 °F

**Reason:** Quality.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering Measures:

Utilize a closed system process where feasible. Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

### Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

#### Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

### Eye Protection:

Prevent eye and skin contact. Provide eye wash fountain and safety shower in close proximity to points of potential exposure. Wear eye/face protection such as chemical splash proof goggles or face shield.

### Skin Protection:

Prevent contamination of skin or clothing when removing protective equipment. Barrier creams may be used in conjunction with the gloves to provide additional skin protection. Wear impermeable gloves and suitable protective clothing.

### Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance

(dimension, color, flexibility etc.) is noticed.

Gloves for repeated or prolonged exposure - non exhaustive list:

Nitrile rubber (NBR), thickness: > 0.38 mm, break through time: up to 480 min

Gloves for short term exposure/splash protection - non exhaustive list:

Natural rubber (NRL), thickness: 0.75 mm, break through time: up to 30 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:

Natural rubber (NRL), thickness: 0.12 mm

Nitrile rubber (NBR), thickness: 0.12 mm

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

**Additional Advice:**

Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

**Exposure Limit(s)**

**64-17-5 Ethanol**

OSHA (PEL): 1000 ppm (TWA)  
1900 mg/m<sup>3</sup> (TWA)  
ACGIH (TLV): 1000 ppm (STEL)  
Other Value: Not established

**78-83-1 Isobutanol**

OSHA (PEL): 100 ppm (TWA)  
300 mg/m<sup>3</sup> (TWA)  
ACGIH (TLV): 50 ppm (TWA)  
Other Value: Not established

**50-00-0 Formaldehyde**

OSHA (PEL): 0.75 ppm (TWA)  
2 ppm (STEL)  
2 ppm STEL 15 min  
0.5 ppm Action Level  
0.75 ppm TWA  
ACGIH (TLV): 0.3 ppm (Ceiling)  
Other Value: Not established

**Biological Exposure Limit(s)**

No values have been established.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Color:** colorless  
**Appearance:** viscous liquid  
**Odor:** slight formaldehyde and ethanol

<b>Boiling Point:</b>	Not applicable
<b>Melting Point:</b>	Not applicable
<b>Vapor Pressure:</b>	Not available
<b>Specific Gravity/Density:</b>	1.01 g/cm <sup>3</sup> @ 25 °C
<b>Vapor Density:</b>	> 1
<b>Percent Volatile (% by wt.):</b>	~ 24
<b>pH:</b>	Not applicable
<b>Saturation In Air (% By Vol.):</b>	Not available
<b>Evaporation Rate:</b>	Less than 1
<b>Solubility In Water:</b>	Insoluble
<b>Volatile Organic Content:</b>	Not available
<b>Flash Point:</b>	25 °C 77 °F Setaflash Closed Cup
<b>Flammable Limits (% By Vol):</b>	Not available
<b>Autoignition Temperature:</b>	Not available
<b>Decomposition Temperature:</b>	Not available
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>Odor Threshold:</b>	Not available
<b>Viscosity (Kinematic):</b>	Not applicable
<b>Viscosity (Dynamic):</b>	Not available
<b>Explosive Properties:</b>	Not available
<b>Oxidizing Properties:</b>	No

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	No information available
<b>Stability:</b>	Stable.
<b>Conditions To Avoid:</b>	None known.
<b>Polymerization:</b>	Will not occur
<b>Conditions To Avoid:</b>	None known.
<b>Materials To Avoid:</b>	No specific incompatibility
<b>Hazardous Decomposition Products:</b>	Ammonia (NH <sub>3</sub> ) Carbon dioxide Carbon monoxide (CO) Formaldehyde oxides of nitrogen

## 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Oral, Skin, Eyes, Respiratory System.

**Acute toxicity - oral:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - dermal:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - inhalation:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin corrosion / irritation:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Serious eye damage / eye irritation:** Causes serious eye damage

**Respiratory sensitization:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin sensitization:** May cause an allergic skin reaction

**Carcinogenicity:** May cause cancer

**Germ cell mutagenicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Reproductive toxicity:** May damage fertility or the unborn child

**Specific target organ toxicity (STOT) - single exposure:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - repeated exposure:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Aspiration hazard:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

## PRODUCT TOXICITY INFORMATION

### ACUTE TOXICITY DATA

oral	rat	Acute LD50	> 2000 mg/kg
dermal	rabbit	Acute LD50	> 2000 mg/kg
inhalation	rat	Acute LC50 4 hr	> 5 mg/l (Dust/Mist)

### LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	dermal	Not irritating
Acute Irritation	eye	Causes serious damage

### ALLERGIC SENSITIZATION

Sensitization	dermal	Sensitizing
Sensitization	inhalation	No data

### GENOTOXICITY

#### Assays for Gene Mutations

Ames Salmonella Assay	No data
-----------------------	---------

### OTHER INFORMATION

The product toxicity information above has been estimated.

## 11. TOXICOLOGICAL INFORMATION


### HAZARDOUS INGREDIENT TOXICITY DATA

Ethanol has acute oral (rat) and dermal (rabbit) LD50 values of 10470 mg/kg and > 20,000 mg/kg, respectively. The 4-hour inhalation LC50 for ethanol in rats is 117-125 mg/l. Inhalation overexposure may cause respiratory tract irritation. Ethanol is a potent teratogen associated with abnormal fetal formation, growth retardation, neurological damage, and behavioral alterations in children with fetal alcohol syndrome. Chronic ingestion of ethanol may cause damage to the liver, heart and gastrointestinal tract. In a dominant lethal assay, male mice treated with ethanol over a three day period showed significant decrease in average litter size along with increased incidence of dead implants. Ethanol is reported to have shown positive results in in vivo and in vitro screening tests for mutagenicity. Direct contact with ethanol may cause moderate eye irritation and mild skin irritation. Ethanol may cause central nervous system depression that causes stupor, coma and eventually death if ingested in excessive quantities. The literature shows that due to synergistic and potentiating effects, the toxicity of ethanol may be enhanced by exposure to

halogenated hydrocarbons and Manganese.

Isobutanol has acute oral (rat) and dermal (rabbit) LD50 values of 2.46 g/kg and 2.46 - 3.4 g/kg, respectively. The LC50 (rat) following a 4-hour inhalation exposure is >8000 ppm (24.24 mg/L). Acute overexposure to isobutanol vapor can cause irritation to the eyes (severe), skin (moderate), and mucous membranes, as well as, central nervous system depression. Literature reports that acute oral exposure to isobutanol has produced CNS effects in animals. Direct contact with isobutanol may cause severe eye and mild to moderate skin irritation.

Formaldehyde has oral (rat) and dermal (rabbit) LD50 values of 640 mg/kg and 270 mg/kg, respectively. 50% of the mice had reduced respiration rate following a 10 minutes inhalation exposure at a concentration of 4.9 ppm. Irritation of the nose and throat has been observed in people exposed to formaldehyde vapor levels in excess of 1 ppm. Normal breathing may be seriously impaired and serious lung damage can occur. Formaldehyde has been reported to cause pulmonary hypersensitivity in some individuals who were exposed to concentrations known to cause irritation; however, no pulmonary sensitization has been demonstrated in laboratory animal studies. Formaldehyde solutions can cause severe eye and skin irritation. Repeated skin exposure to solutions of 2% or more formaldehyde has caused allergic skin reactions. Formaldehyde was found to be weakly genotoxic in a number of in vitro genotoxicity tests and positive in certain in vivo genotoxicity studies. Formaldehyde did not cause birth defects in rats inhaling concentrations up to 10 ppm. However, a study using higher levels did show a slight but statistically significant reduction in male fetal body weight. Lifetime inhalation of formaldehyde vapor at concentrations above 5 ppm for 6 hours per day, caused nasal tumors in laboratory animals. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to the occurrence of nasopharyngeal cancer, a rare type of cancer. IARC also found limited evidence of cancer of the nasal cavity and paranasal sinuses and insufficient evidence for an association between formaldehyde and leukemia. Inhalation caused liver and kidney damage in laboratory animal tests.

 **WARNING:** Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---

## 12. ECOLOGICAL INFORMATION

### TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

**Overall Environmental Toxicity:** May cause long lasting harmful effects to aquatic life.

Due to extreme low solubility in water, and therefore the non-availability to species, this product is regarded as not hazardous to aquatic organisms. The product is also not readily biodegradable.

### DEGRADATION

**Test:** Biodegradability

**Duration:** 28 day

< 70 %

### RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

### HAZARDOUS INGREDIENT TOXICITY DATA



Component / CAS No.	Toxicity to Fish
Urea P/W formaldehyde, isobutylated (68002-18-6)	Not available
Ethanol (64-17-5)	LC50 > 100 mg/L - Pimephales promelas (96h) LC50 13400 - 15100 mg/L - Pimephales promelas (96h) LC50 12.0 - 16.0 mL/L - Oncorhynchus mykiss (96h)
Isobutanol (78-83-1)	LC50 1120 - 1520 mg/L - Oncorhynchus mykiss (96h) LC50 1370 - 1670 mg/L - Pimephales promelas (96h) LC50 1480 - 1730 mg/L - Lepomis macrochirus (96h)
Formaldehyde (50-00-0)	LC50 = 6.7 mg/L - Morone saxatilis (96h)

Component / CAS No.	Toxicity to Water Flea
Urea P/W formaldehyde, isobutylated (68002-18-6)	Not available
Ethanol (64-17-5)	EC50 = 2 mg/L - Daphnia magna (48h) LC50 9268 - 14221 mg/L - Daphnia magna (48h) EC50 = 10800 mg/L - Daphnia magna (24h)
Isobutanol (78-83-1)	EC50 = 1300 mg/L - Daphnia magna (48h)
Formaldehyde (50-00-0)	EC50 = 5.8 mg/L - Daphnia pulex (48h)

Component / CAS No.	Toxicity to Algae
Urea P/W formaldehyde, isobutylated (68002-18-6)	Not available
Ethanol (64-17-5)	Not available
Isobutanol (78-83-1)	EC50 = 230 mg/L - Desmodesmus subspicatus (48h)
Formaldehyde (50-00-0)	EC50 = 4.89 mg/L - Desmodesmus subspicatus (72hrs)

Component / CAS No.	Partition coefficient
Urea P/W formaldehyde, isobutylated (68002-18-6)	Not available
Ethanol (64-17-5)	-0.32
Isobutanol (78-83-1)	0.79
Formaldehyde (50-00-0)	0.35

### 13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials

classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

### US DOT

Dangerous Goods? X  
 PROPER SHIPPING NAME: RESIN SOLUTION  
 Hazard Class: 3  
 Packing Group: III  
 UN/ID Number: UN1866  
 Transport Label Required: Flammable Liquid

<u>Component / CAS No.</u>	<u>Hazardous Substances/Reportable Quantity of Product (lbs)</u>
Formaldehyde	12500
Xylene	33333

Comments: Hazardous Substances/Reportable Quantities - DOT requirements specific to Hazardous Substances only apply if the quantity in one package equals or exceeds the product reportable quantity.

### TRANSPORT CANADA

Dangerous Goods? X  
 PROPER SHIPPING NAME: RESIN SOLUTION  
 Hazard Class: 3  
 Packing Group: III  
 UN Number: UN1866  
 Transport Label Required: Flammable Liquid

### ICAO / IATA

Dangerous Goods? X  
 UN PROPER SHIPPING NAME: RESIN SOLUTION  
 Transport Hazard Class: 3  
 Packing Group: III  
 UN Number: UN1866  
 Transport Label Required: Flammable Liquid

### IMO

Dangerous Goods? X  
 UN PROPER SHIPPING NAME: RESIN SOLUTION  
 Transport Hazard Class: 3  
 UN Number: UN1866  
 Packing Group: III  
 Transport Label Required: Flammable Liquid

### SPECIAL PRECAUTIONS FOR USER

Protect against external heat sources higher than +30°C/86°F.

## 15. REGULATORY INFORMATION

### Inventory Information

**United States (USA):** All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

**Canada:** All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

**European Economic Area (including EU):** When purchased from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

**Australia:** All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS.

**New Zealand:** This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

**China:** All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

**Japan:** All components of this product are included on the Japanese (ENCS and ISHL) inventories or are not required to be listed on the Japanese inventories.

**Korea:** All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory.

**Philippines:** All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

**Taiwan:** All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

### OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

Component / CAS No.	%	TPQ (lbs)	RQ(lbs)	S313	TSCA 12B
Isobutanol 78-83-1	2 - 4	None	5000	No	No
Formaldehyde 50-00-0	<= 0.8	500	100	Yes	No
Xylene 1330-20-7	0.2 - 0.3	None	100	Yes	No

### PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

#### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

#### Health Hazards

Carcinogenicity  
Reproductive toxicity  
Respiratory or Skin Sensitization  
Serious eye damage or eye irritation

---

## 16. OTHER INFORMATION

### NFPA Hazard Rating (National Fire Protection Association)

Health: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

Fire: 3 - Liquids and solids that can be ignited under almost all ambient temperature conditions.

Instability: 0 - Materials that in themselves are normally stable, even under fire exposure conditions.

**Reasons For Issue:** Revised Section 11

**Date Prepared:** 08/25/2018

**Date of last significant revision:** 10/19/2017

### Component - Hazard Statements

Urea P/W formaldehyde, isobutylated

H413 - May cause long lasting harmful effects to aquatic life.

Ethanol

H225 - Highly flammable liquid and vapor.

H316 - Causes mild skin irritation.

H319 - Causes serious eye irritation.

Isobutanol

H226 - Flammable liquid and vapor.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

H336 - May cause drowsiness or dizziness.

Formaldehyde

H301 - Toxic if swallowed.

H311 - Toxic in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H331 - Toxic if inhaled.

H341 - Suspected of causing genetic defects.

H350 - May cause cancer.

H401 - Toxic to aquatic life.

### Emergency phone numbers for other regions

#### Asia Pacific

Australia: +61 1800 022 037 (Allnex Australia)

China (PRC): +86(0)25 8547 7110 (Jiangsu registration center) / +86(0)532 8388 9090 (NRCC)

India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)

Indonesia: 007 803 011 0293 (Carechem 24)

Japan: +81 345 789 341 (Carechem 24)

Korea: +82 2 3479 8401 (Carechem 24)

Malaysia: +60 3 6207 4347 (Carechem 24)

New Zealand: +64 0800 803 002 (Allnex New Zealand)

Philippines: +63 2 231 2149 (Carechem 24)

Taiwan: +886 2 8793 3212 (Carechem 24)

Vietnam: +84 8 4458 2388 (Carechem 24)

All Others: +65 3158 1074 (Carechem 24)

**Europe**

+44 (0) 1235 239 670 (Carechem 24)

**Middle East, Africa**

+44 (0) 1235 239 671 (Carechem 24)

**Latin America**

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)

Chile: +56 2 2582 9336 (Carechem 24)

Mexico and all others: +52-555-004-8763 (Carechem 24)

---

Prepared By: Product Stewardship & Regulatory Affairs Department, <http://www.allnex.com/contact>

---

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.

---