



Product information

COLORTHERM® Red 110 M

Description

Туре	Red pigment
Delivery form	powder
Chemical class Colour Index	Synthetic iron oxide α - Fe ₂ O ₃ Pigment red 101 (77491)
CAS-No.	1309-37-1
REACH registration no.	01-2119457614-35-0000

Specification

Colour values and tinting strength			
Standard	COLORTI	HERM Red 110 M	
Year	2007		
Binder: Plasticised PVC	Reduction with titaniu KB-2 (1 : (um dioxide Tronox® R-	Test method Nr. 009 vom 2001-01-02 ⁴¹
	min	max	
Δ L*	-0.5	0.5	
∆ a*	-0.7	0.7	
∆ b*	-0.7	0.7	
Δ C _{ab} *	-0.7	0.7	
Δ H _{ab} *	-0.7	0.7	
ΔE _{ab} *		1.0	
Relative tinting strength [%]	95	105	

Specification

Dispersibility		max	Test method
Binder Alkydal F 681 75 % in white spirit			
Grindometer values [µm] (dissolver mill base)		20/35/50	No. 004 of 1995-05-15 ⁴¹
Technical Data	min	max	
water-soluble content [%]		0.5	as per DIN EN ISO 787-3:1995
Sieve residue (0.045 mm sieve) [%]		0.002	as per DIN 53195:1990
pH value	5.0	8.0	as per DIN EN ISO 787-9:1995





COLORTHERM® Red 110 M

Informative technical data (guide values)

					Test method
a - Fe ₂ O ₃ Content [%] ⁵³	>		99.1		information about the determination of iron oxide41
Loss on ignition at 1000 °C, 0.5 h [%]	<		0.7		similar to DIN 55 913-2:1972
Moisture content (after production) [%]	<		0.5		as per DIN EN ISO 787-2:1995
Particle shape			spheri	cal	Electron micrographs
Predominant particle size [µm]	~		0.09		Electron micrographs
Oil absorption [g/100 g]	~		25		as per DIN EN ISO 787-5:1995
Tamped density [g/ml]		0.7	-	1.1	as per DIN EN ISO 787-11:1995
Density [g/ml]	~		5.0		as per DIN EN ISO 787-10:1995



LANXESS Energizing Chemistry

COLORTHERM® Red 110 M

Packaging

The product is available in sacks or bulk bags. For further information please ask your local contact or send an enquiry by e-mail to mailto: ipg.product-information@lanxess.com

Transport and storage

Protect against weathering. Store in a dry place and avoid extreme fluctuations in temperature.

Special conditions for opened packaging: Close bags after use to prevent the absorption of moisture and contamination.

If stored under the correct conditions (no climatic influence, kept dry and no extreme fluctuations in temperature) our products have an excellent shelf life. However, due primarily to the limited durability of the packaging, we recommend that the product is used within 5 years of the date of manufacture and our product warranty is limited to this period. During the first five years after the date of manufacture we are able to ensure compliance with our specification, provided the material has been stored correctly and the packaging materials remain undamaged.

Safety

The product is not classified as dangerous under the relevant EC Directives and corresponding national regulations valid in the individual EU member states. It is not dangerous according to transport regulations.

In countries outside the EU, compliance with the respective national legislation concerning the classification, packaging, labelling and transport of dangerous substances must be ensured. The safety data sheet should be observed. This contains information on handling, product safety and ecology.





COLORTHERM® Red 110 M

Information concerning European food contact regulations (not specified)

This product complies with the purity requirements of the following legal regulations respectively is listed on the mentioned positive lists.

General remark

As the food contact regulation of each country may differ, it is the responsibility of the manufacturer of the finished articles to ensure compliance with the respective country's regulation (migration resp. extraction limits, e.g.)

e.g.)	
European Union (Council of Europe)	Resolution AP (89) 1
Germany	Recommendation IX of the Federal Institute for Risk Assessment (BfR) dated 1994.06.01.
Belgium	Koninklijk Besluit dated 11.5.1992; Warenwetgeving (1), aanvulling nr. 18 - September 1992
France	Circulaire 176 dated 2.12.1959, published in the Journal Officiel of 30.12.1959 incl. amendments.
Netherlands	Warenwet/Regeling Verpakkingen - en gebruiksartikelenbesluit; Uitvoeringsvoorschriften CIII-55, entered into force on 21.8.1991. As well as defining the content of soluble heavy metals in pigments, this regulation specifies maximum permissible migration values for the pigmented articles.
United Kingdom	Plastics for food contact applications, a code of practice for safety in use: BPF in connection with BIBRA, revised edition 1986. Like BfR Recommendation IX, this code does not have the force of law. However, processors view it as binding.
Italy	Decreto Ministeriale dated 21.3.1973, published in Gazetta Uffiziale No. 104 of 20.4.1973; last amendment in Decreto Ministeriale No. 338 of 22.7.98.
Spain	Resolucion dated 4.1L1982 (BOE 282 of 24.11.1982) in accordance with Article 5 of Royal Decree 211/1992 of March 5, 1992. All colorants are permitted which conform with the migration values defined in Appendix III of the Resolucion. Pigments used in foodcontact applications must be notified to the Health Ministry. All Bayferrox pigments which satisfy BgVV Recommendation IX can be used in Spain.

Information concerning Non-European food contact regulations (not specified)

This product complies with the purity requirements of the following legal regulations respectively is listed on the mentioned positive lists

General remark

As the food contact regulation of each country may differ, it is the responsibility of the manufacturer of the finished articles to ensure compliance with the respective country's regulation (migration resp. extraction limits, e.g.)

Australia	Australian Standard 2070.6 (1984)	Australian Standard 2070.6 (1984)		
USA	According to § 178.3297 (Colorants for Polymers)			

4/5





COLORTHERM® Red 110 M

Status of registration (not specified)

The components of this product are listed on the following inventories:						
Europe:	USA:	Canada:	Australia:	New Zealand:		
EINECS	TSCA	DSL	AICS	NZIoC		
Philipines:	Japan:	Korea:	China:	Taiwan:		
PICCS	METI	ESL	IECSC	NECSI		

⁴¹obtainable from LANXESS Deutschland GmbH, Business Unit Inorganic Pigments, Fax +49-2151-88-9599-4139, mailto: ipg.product-information@lanxess.com

⁵³Minor elements may arise from the raw materials used. However, these are firmly bound to the crystal lattice as ions.