SAFETY DATA SHEET

OREVAC® T 9304

1. PRODUCT AND COMPANY IDENTIFICATION

Company

SK Global Chemical Americas (SKGCA) 501 Office Center Drive, Suite 188 Fort Washington, Pennsylvania 19034

Functional Polyolefins

Customer Service Telephone Number: (267) 896-3500

(Monday thru Friday, 8:00am to 5:00pm EST)

Emergency Information

Transportation: CHEMTREC: 1-800-424-9300

(24 hrs. 7 days a week)

Medical: Rocky Mountain Poison Center: 866-767-5089

(24 hrs. 7 days a week)

Product Information

Product Name: OREVAC T 9304

Synonyms: UBa4
Molecular formula: Proprietary
Chemical family: Terpolymer

Product use: Coextrusion tie-layer, Pipe coating

2. HAZARDS IDENTIFICATION

Emergency Overview

Color:WhitePhysical State:SolidForm:PelletsOdor:Ester-like

<u>Classification of the substance or mixture:</u>

Not a hazardous substance or mixture.

GHS-Labeling

Supplemental Hazard Statements:

Processing may release vapors and/or fumes, which cause eye, skin and respiratory tract irritation.

Supplemental Information:

Potential Health Effects:

The product, in the form supplied, is not anticipated to produce significant adverse human health effects upon acute exposure. Contains high molecular weight polymer(s). Effects due to processing releases or residual monomer: Irritating to eyes, respiratory system and skin.

Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure).

SAFETY DATA SHEET

OREVAC® T 9304

Other:

Handle in accordance with good industrial hygiene and safety practice. (pellets/granules) This product may release fume and/or vapor of variable composition depending on processing time and temperature. Hazardous decomposition products may include confirmed or suspected carcinogens.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt%	GHS Classification
Acetic acid ethenyl ester, polymer with ethene	24937-78-8	<= 99 %	Not classified

^{**} For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AND MEASURES

4.1. Description of necessary first-aid measures:

Inhalation:

If inhaled, remove victim to fresh air.

Skin:

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms/effects, acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of immediate medical attention and special treatment needed, if necessary:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

5. FIREFIGHTING MEASURES

Extinguishing media (suitable):

Water spray, Carbon dioxide (CO2), Foam, Dry powder.

Protective equipment:



OREVAC® T 9304

Fire fighters and others who may be exposed to products of combustion should wear full firefighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

When burned, the following hazardous products of combustion can occur: Carbon oxides
Hazardous organic compounds

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:

Prevent further leakage or spillage if you can do so without risk. Ventilate the area. Sweep up and shovel into suitable properly labeled containers for prompt disposal. Possible fall hazard – floor may become slippery from leakage/spillage of product. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8...

7. HANDLING AND STORAGE

Handling

General information on handling:

Avoid breathing dust.

Avoid breathing processing fumes or vapors.

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

Storage

General information on storage conditions:

Keep in a dry, cool place. Keep away from direct sunlight. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Store away from moisture and heat to maintain the technical properties of the product.

Storage stability - Remarks:

Stable under normal conditions.

Storage incompatibility - General:

None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

Particles Not Otherwise Specified / Nuisance Dust (Proprietary)



OREVAC® T 9304

US. ACGIH Threshold Limit Values

Form: Inhalable particles.

Time weighted average 10 mg/m3

Form: Respirable particles.

Time weighted average 3 mg/m3

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Form: Respirable fraction.

PEL: 5mg/m3

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Form: Total dust PEL: 15 mg/m3

US OSHA Table Z-3 (29 CFR 1910.1000)

Form: Respirable fraction.

Time weighted average 15millions of particles per cubic foot of air

US OSHA Table Z-3 (29 CFR 1910.1000)

Form: Total dust

Time weighted average 50millions of particles per cubic foot of air

US OSHA Table Z-3 (29 CFR 1910.1000)

Form: Respirable fraction.

Time weighted average 5 mg/m3

US OSHA Table Z-3 (29 CFR 1910.1000)

Form: Total dust Time weighted average 15mg/m3

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Respiratory protection:

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing.

Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a



OREVAC® T 9304

potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

Eye protection:

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

9. PHYSICAL AND CHEMICAL PROPERTIES				
Color:	White			
Physical state:	Solid			
Form:	Pellets			
Odor:	Ester-like			
Odor threshold:	No data available.			
Flash point:	662 °F (350 °C) (Setaflash closed cup)			
Lower flammable limit (LFL):	No data available.			
Upper flammable limit (UFL):	No data available.			
pH:	Not applicable.			
Density:	930 - 950 kg/m3 (68 °F (20 °C))			
Specific gravity (Relative density):				
Boiling Point/Boiling Range:	No data available.			
Melting Point/Range:	158 - 230 °F (70 - 110 °C)			
Freezing point:	No data available.			
Evaporation rate:	No data available.			
Solubility in water:	68 °F (20 °C) insoluble			
Solubility in other solvents: [qualitative and quantative]	77 °F (25 °C) Carbon tetrachloride			
Viscosity, dynamic:	No data available.			
Oil/water partition coefficient:	No data available.			

SAFETY DATA SHEET

OREVAC® T 9304

Thermal decomposition: approximately > 500 °F (> 260 °C)

Flammability: See GHS Classification in Section 2 if applicable

10. STABILITY AND REACTIVITY

Stability:

The product is stable under normal handling and storage conditions.

Hazardous reactions:

Hazardous polymerization does not occur.

Materials to avoid:

None known.

Conditions / hazards to avoid:

Avoid direct sunlight. Store away from moisture and heat to maintain the technical properties of the product. See Hazardous Decomposition Products below.

Hazardous decomposition products:

Thermal decomposition giving toxic, flammable, and / or corrosive products: Carbon oxides
Hazardous organic compounds

11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Data for Acetic acid ethenyl ester, polymer with ethene (24937-78-8)

Acute toxicity

Oral:

May be harmful if swallowed. (rat) LD50 > 2,500 mg/kg.

Other information

The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance.

12. ECOLOGICAL INFORMATION

Chemical Fate and Pathway

No data are available.

Ecotoxicology

No data are available.

13. DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET

OREVAC® T 9304

Waste disposal:

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of in accordance with federal, state, and local regulations. Pigmented, filled and/or solvent laden product may require special disposal practices in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

14. TRANSPORT INFORMATION

US Department of Transportation (DOT): Not Regulated.

International Maritime Dangerous Goods Code (IMDG): Not Regulated.

15. REGULATORY INFORMATION

Chemical	Inventory	/ Status

US. Toxic Substances Control Act	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. EBCS – Existing and New Chemical Substances Inventory	ENCS (JP)	Conforms to
Japan. ISHL – Inventory of Chemical Substances	ISHL (JP)	Conforms to
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances (AICS)	AICS	Conforms to

United States - Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

Chemical name	CAS-No.	SARA Reportable Quantities	SARA Threshold Planning
Acetic acid ethenyl ester	108-05-4	5000 lbs.	Quantity 1000 lbs.



OREVAC® T 9304

SARA Title - Section 311/312 Hazard Categories:

No SARA Hazards.

SARA Title III - Section 313 Toxic Chemicals:

The following components are subject to reporting levels established by SARA Title III, Section 313:

Chemical name CAS-No. De minimis concentration Reportable threshold:

Acetic acid ethenyl ester 108-05-4 10000 lbs. (Otherwise used (nonmanufacturing/processing)) 25000 lbs.

(Manufacturing and processing)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity

(RQ):

Reportable quantity Chemical name CAS-No.

Acetic acid ethenyl ester 108-05-4 5000 lbs.

<u>United States – State Regulations</u>

New Jersey Right to Know

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right to Know

Chemical Name

CAS-No. Acetic acid ethenyl ester, polymer with ethene

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

16. OTHER INFORMATION

Latest Revision(s):

Reference number: 200006504 Date of Revision: 09/18/2017 Date Printed: 09/18/2017

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, SKGCA expressly disclaims any and all liability as to any results obtained or arising from any use of the product reliance on such information; NO WARRANT OF FIRNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED IS MADE CONCERNING THE GOODS DESCIRBED OR THE INFORMATION PROVIDED HERIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent, it should not be construed as an inducement to infringe any patent, and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Product code: AT119 Version 2.3 Issued on: 09/18/2017 Page: 8 / 8