



# Baerostab M 25 SA

**Baerlocher USA**  
3676 Davis Road N.W.  
Dover, OH 44622  
Tel. (330) 364-6000

## PRODUCT INFORMATION

### Type

Butyltin mercaptide

### Typical Properties

Appearance: Liquid  
Color (Gardner) 2 Max.  
Refractive index at 25°C  $1.5070 \pm 0.0050$

### Application

Baerostab M 25 SA is a liquid butyltin mercaptide suitable for the stabilization of all PVC types (suspension, emulsion, mass and copolymers) in technical applications.

Baerostab M 25 SA imparts good heat stability and transparency even in the most demanding processing techniques such as rigid injection molding and extrusion.

Main advantage of Baerostab M 25 SA is its low odor during processing as well as in the finished article.

Baerostab M 25 SA has no self lubricating properties, the addition of suitable lubricants is mandatory.

### Recommended Dosage

1.0 to 2.0 phr, depending on the application.

### Food Packaging Approval

Baerostab M 25 SA may not be used for the manufacturing of food packaging materials.

### Handling

A material safety data sheet for the handling of this product is available on request.

### Storage

Dry storage at room temperature is recommended.  
Once opened, packaging should be firmly closed.

The data herein is deemed accurate by the supplier, however, is provided for informational purposes only and creates no warranties, express or implied. As the consumer controls application of the product, this information does not constitute a warranty of merchantability, fitness for a particular use or recommendations to practice any patented invention without a license.