



Revision Number: 002.2

Issue date: 10/21/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE S-FN M 254N
FUNCTIONAL PREVENTATIVE COATING ACHESON known as MOLYDAG 254N

IDH number: 1224299

Product type: Lubricant

Restriction of Use: None identified

Region: United States

Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

Contact information:
 Telephone: (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR.
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

IDH number: 1224299

Product name: BONDERITE S-FN M 254N FUNCTIONAL PREVENTATIVE COATING ACHESON known as MOLYDAG 254N

Disposal: Keep cool. Store locked up.
Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

14 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Toluene	108-88-3	10 - 30
Phosphoric acid, polymer with 4,4'-Isopropylidenediphenol and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	64346-82-3	10 - 30
Antimony trioxide	1309-64-4	10 - 30
Methoxypropyl acetate 2-	108-65-6	10 - 30
Methyl ethyl ketone	78-93-3	10 - 30
Lead oxide phosphonate	12141-20-7	5 - 10
Formaldehyde, polymer with 3-chloro-1-propene and phenol	28470-78-2	1 - 5
Rheological additive	Proprietary	1 - 5

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.

Eye contact: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.

Ingestion: Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions. Vapors may travel considerable distance to source of ignition and flash back.

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways. Remove all sources of ignition.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists of this product. Use only with adequate ventilation. Use non-sparking tools when opening or closing containers. Make sure containers are properly grounded before use or transfer of material. Do not take internally. For industrial use only.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling 500 ppm MAX. CONC 10 minutes	None	None
Phosphoric acid, polymer with 4,4'-Isopropylidendiphenol and 2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	None	None	None	None
Antimony trioxide	0.5 mg/m ³ TWA (as Sb) Included in the regulation but with no data values. See regulation for further details Exposure by all routes should be carefully controlled to levels as low as possible.	0.5 mg/m ³ PEL (as Sb)	None	None
Methoxypropyl acetate 2-	None	None	50 ppm TWA	None
Methyl ethyl ketone	200 ppm TWA 300 ppm STEL	200 ppm (590 mg/m ³) PEL	None	None
Lead oxide phosphonate	0.05 mg/m ³ TWA (as Pb)	0.05 mg/m ³ TWA 0.03 mg/m ³ OSHA_ACT	None	None
Formaldehyde, polymer with 3-chloro-1-propene and phenol	None	None	None	None
Rheological additive	None	None	None	None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear chemical goggles; face shield (if splashing is possible).

Skin protection:

Wear impervious gloves for prolonged contact. Suitable glove materials may include: Neoprene gloves. Nitrile gloves. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Black
Odor:	Aromatic
Odor threshold:	2.140 ppm
pH:	Not applicable
Vapor pressure:	91 mm hg
Boiling point/range:	> 79 °C (> 174.2 °F)
Melting point/ range:	-89 °C (-128.2 °F) calculated
Specific gravity:	1.34
Vapor density:	3.2
Flash point:	-4.4 °C (24.08 °F) Closed cup
Flammable/Explosive limits - lower:	1.2 %

IDH number: 1224299

Product name: BONDERITE S-FN M 254N FUNCTIONAL PREVENTATIVE COATING ACHESON
known as MOLYDAG 254N

Flammable/Explosive limits - upper:	11.5 %
Autoignition temperature:	> 272 °C (> 521.6 °F)
Evaporation rate:	Not determined
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	616 g/l
Viscosity:	200 - 1,000 cp
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	Strong acids, alkalies and oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Avoid excessive heat and ignition sources.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
-------------------------------------	------------------------

Potential Health Effects/Symptoms

Inhalation: This product is irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Skin contact: This product is irritating to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. A component in this product may be absorbed through the skin in harmful amounts. Prolonged contact with this product may cause allergic skin sensitization reactions.

Eye contact: This product may be severely irritating to the eyes.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Moderately toxic by ingestion. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Toluene	Oral LD50 (RAT) = 2.6 g/kg Oral LD50 (RAT) = 5,000 mg/kg Dermal LD50 (RABBIT) = 12,124 mg/kg Inhalation LC50 (RAT, 1 h) = 26700 ppm Inhalation LC50 (RAT, 2 h) = 12200 ppm Inhalation LC50 (RAT, 4 h) = 8000 ppm	Behavioral, Cardiac, Central nervous system, Developmental, Ear, Irritant
Phosphoric acid, polymer with 4,4'-Isopropylidendiphenol and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	None	No Records
Antimony trioxide	Oral LD50 (RAT) = > 34,600 mg/kg Oral LD50 (RAT) = > 20 g/kg	Cardiac, Developmental, Eyes, Gastrointestinal, Irritant, Kidney, Liver, Lung, Mutagen, Nervous System, Reproductive, Sensory, Some evidence of carcinogenicity
Methoxypropyl acetate 2-	None	Irritant, Central nervous system
Methyl ethyl ketone	Oral LD50 (RAT) = 2,300 - 3,500 mg/kg Oral LD50 (RAT) = 4,500 - 6,800 mg/kg Dermal LD50 (RABBIT) = > 8,000 mg/kg Inhalation LC50 (RAT, 4 h) = 11700 ppm	Irritant, Central nervous system
Lead oxide phosphonate	None	No Records
Formaldehyde, polymer with 3-chloro-1-propene and phenol	None	No Records
Rheological additive	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Toluene	No	No	No
Phosphoric acid, polymer with 4,4'-Isopropylidendiphenol and 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	No	No	No
Antimony trioxide	No	Group 2B	No
Methoxypropyl acetate 2-	No	No	No
Methyl ethyl ketone	No	No	No
Lead oxide phosphonate	Reasonably Anticipated to be a Human Carcinogen.	Group 2A	No
Formaldehyde, polymer with 3-chloro-1-propene and phenol	No	No	No
Rheological additive	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Toxic to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number:	Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. If discarded, this product is considered a RCRA ignitable waste, D001. This product may contain traces of: D008: Lead This product contains a component or components identified as hazardous under 40 CFR 261.24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Paint
Hazard class or division:	3
Identification number:	UN 1263
Packing group:	II

International Air Transportation (ICAO/IATA)

Proper shipping name:	Paint
Hazard class or division:	3
Identification number:	UN 1263
Packing group:	II

Water Transportation (IMO/IMDG)

Proper shipping name:	PAINT (Lead phosphite dibasic)
Hazard class or division:	3
Identification number:	UN 1263
Packing group:	II
Marine pollutant:	Lead phosphite dibasic
Additional information:	IMDG-Code: Segregation group 9- Lead and its compounds

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Toluene (CAS# 108-88-3). Antimony trioxide (CAS# 1309-64-4). Methyl ethyl ketone (CAS# 78-93-3). Lead oxide phosphonate (CAS# 12141-20-7).
CERCLA Reportable quantity:	Toluene (CAS# 108-88-3) 1,000 lbs. (454 kg) Antimony trioxide (CAS# 1309-64-4) 1,000 lbs. (454 kg) Methyl ethyl ketone (CAS# 78-93-3) 5,000 lbs. (2,270 kg) Arsenic (CAS# 7440-38-2) 1 lbs. (0.454 kg) Lead oxide phosphonate (CAS# 12141-20-7) 10 lbs. (4.54 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

Issue date: 10/21/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.