

SURFYNOL® MD 20

DESCRIPTION

SURFYNOL® MD 20 is a very compatible molecular defoamer based on Gemini surfactant technology. Free of silicone and silica. Offers additional dynamic wetting properties.

KEY BENEFITS

- universal use in waterborne formulations
- effectiveness against macro- and micro-foam in combination with high compatibility
- highly recommended in combination with classical silicone-based defoamers or substrate wetting additives

APPLICATION RECOMMENDATION

Brush application/roller application



Airless spraying



Compressed air spraying



Flexo/gravure printing



Dip coating, flow coating, curtain coating



Flooring



SUITABILITY

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
addition to the grinding stage	addition to the let-down stage
●	●
● not suitable ● partly suitable ● suitable	

TYPICAL APPLICATIONS

- Wood coatings
- General industrial coatings
- Printing Inks
- Car OEM coatings

TECHNICAL DATA

active matter content	100 %
appearance	clear colored liquid
chemical description	organic based Gemini molecular defoamer
solvent	-

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●
● not soluble ● partly soluble ● soluble	

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

PROCESSING INSTRUCTIONS

Can be introduced in the grind and let-down stage.

HANDLING & STORAGE

SURFYNOL® MD-20 surfactant should be stored under dry and clean conditions between -10 °C and 50 °C. Product is freeze-thaw stable; if it phase separates or freezes at colder temperatures, warm container to 40 °C and mix thoroughly before use. Please refer to Material Safety Data Sheet.

MSDS & REGULATORY INFORMATION



This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Resource Efficiency GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com