

TECHNICAL DATA SHEET

CRAYVALLAC® PA3 WDA 20

Pre-activated amide rheology modifier supplied in mineral spirit

Polyamide

TYPICAL CHARACTERISTICS

Nature	Polyamide
Appearance	Off-white paste
Solid Content (%)	20
Active Content (%)	20
Specific gravity	0.88
Solvent	D60 and Alcohol
Total Bio content (%)	17

DESCRIPTION

CRAYVALLAC® PA3 WDA 20 is a pre-activated amide wax supplied in a mixture of mineral spirit (D60) and alcohols. Under paste form for post-addition to solvent-based low polarity coating systems, it provides a shear-thinning rheology with thixotropic viscosity recovery to coating formulations. In coating systems, its crystalline fibres form an interacting network which gives rise to the shear-thinning rheology of the final coating. It provides a very high viscosity under the low shear rates associated with sedimentation, and a low viscosity at the much higher application shear rates. The net result is excellent control of sedimentation combined with ease of application. Immediately following application, the coating's viscosity undergoes a time dependent recovery as the network re-establishes itself. This time dependence is known as thixotropy and enables the final coating to attain very good levelling.

RECOMMENDED ADDITION LEVEL

0.5-5.0% under low to medium shear dispersion

STANDARD PACKAGING

Other packaging may be available upon request

- 15 Kg Pail

HANDLING & STORAGE

It should be stored in the original containers in a dry place at temperatures between 5°C (41°F) and 30°C (86°F). Avoid exposure to direct sunlight or frost. In these conditions, this product should be used within 24 months from production.

MARKETS

Coatings & Inks

- Architectural Coating
- Industrial Coating

KEY BENEFITS

FORMULATION

- Ready to use
- Easy handling
- Post addition



STORAGE

- Antisettling
- In-can appearance
- Syneresis resistance
- Viscosity stability



APPLICATION

- Edge-coverage
- Sag resistance
- Sprayability



FILM PROPERTIES

- Gloss
- Levelling
- Transparency



SAFER SOLUTIONS

- APEO Free*
- Heavy Metal Free*

* Not intentionally added but not specifically measured (not part of product specification)

- Total Bio content (%)

17

THICKENING MECHANISM

Non Associative



VISCOSITY CONTRIBUTION

Low Shear contribution
Mid Shear contribution



CRAYVALLAC® PA3 WDA 20

PROCESSING INSTRUCTIONS

In order to obtain maximum efficiency from CRAYVALLAC® PA3 WDA 20, it is necessary to disperse this product without destroying the crystalline fibres. It is therefore preferable to incorporate CRAYVALLAC® PA3 WDA 20 under low to medium shear conditions over as short a time period as possible. There are two main methods by which CRAYVALLAC® PA3 WDA 20 can be incorporated: **Post addition: Using a high-speed disperser, CRAYVALLAC® PA3 WDA 20 is added during the final stages of production, when the coating has been partially thinned to a viscosity of 600- 800mPas (ICI cone and plate at 10000s-1) and the peripheral speed reduced to approximately 4m.s-1. Too high a speed will result in reduced performance, whereas, too low a speed will result in extended incorporation times. In general, the time required for incorporation should be kept to a minimum in order to minimize overshear. Master batch preparation: To be prepared by dispersing CRAYVALLAC® PA3 WDA 20 in a resin and/or solvent using low to medium shear rates. This dispersion can then be added to the finished coating.**

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA