



Print this page Polymer Solutions

Edition Date January 01, 2014 Edition Number 3

Licocare® RBW 330 powder Vita

Modified natural wax

Product Description

Licocare RBW 330 powder Vita is a partially saponified wax based on renewable resource.

See here for more details about Licocare® RBW [for Plastics](#) and [for Coatings and Inks](#).

Benefits

- Excellent lubricating effect in Engineering Plastics
- Combined nucleating and lubricating effect in partly crystalline polymers like polyamides, providing high mechanical properties and increased output in injection molding
- High thermal stability
- Low volatility
- Very effective at low concentrations

Specifications

Delivery Specifications and (*) General Properties

Characteristics	Unit	Target value	Test method
Appearance		yellowish powder	QM-AA-634
Drop point	[°C]	90 - 120	ISO 2176
Acid value	[mg KOH/g]	10 - 20	ISO 2114
Saponification value	[mg KOH/g]	65 - 95	ISO 3681
Calcium content	[%]	1.6 - 2.4	DGF M-IV 4
*Density (23°C)	[g/cm ³]	~ 1.00	ISO 1183
*Viscosity	[mPa·s]	~ 1000	DIN 53019 at 120°C

Applications

Highly efficient combined nucleating and lubrication agent for engineering resins, predominately for all kinds of polyamides.

Packaging and Handling

Delivery form

Powder
The product is also available in other physical form.

Packaging

Polyethylene bag 20 kg
Pallet 1000 kg (50 bags)

Storage

For best shelf life store this product in a dry area at normal ambient temperatures.
Minimum shelf life is two years from the date of shipping when properly stored.

EcoTain®

Products that offer outstanding sustainability advantages are awarded Clariant's EcoTain® label. EcoTain® products significantly exceed sustainability market standards, have best-in-class performance and contribute overall to sustainability efforts of the company and our customers. Find out more about: [EcoTain®](#).

Safety

Hazards

The product does not require a hazard warning label according CLP regulation (Regulation (EC) No. 1272/2008, as amended).
For further information please refer to the Material Safety Data Sheet.

Contact Us;

Please contact us for safety and regulatory details or the Material Safety Data Sheet (MSDS).

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application.

* Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

* For sales to customers located within the United States and Canada the following applies in addition: No express or implied warranty is made of the merchantability, suitability, fitness for a particular purpose or otherwise of any product or service.

© Trademark of Clariant registered in many countries.

© 2019 Clariant International Ltd

www.clariant.com