



SAFETY DATA SHEET

ROHM & HAAS CHEMICALS LLC

Product name: PARALOID™ B-99 50% Resin

Issue Date: 08/05/2021

Print Date: 08/07/2021

ROHM & HAAS CHEMICALS LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: PARALOID™ B-99 50% Resin

Recommended use of the chemical and restrictions on use

Identified uses: Coatings product

COMPANY IDENTIFICATION

ROHM & HAAS CHEMICALS LLC
Agent for Rohm and Haas Chemicals LLC
400 ARCOLA ROAD
COLLEGEVILLE PA 19426-2914
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids - Category 2

Skin irritation - Category 2

Eye irritation - Category 2A

Reproductive toxicity - Category 2

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Nervous system, Auditory system) through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mist or vapours.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye protection and/or face protection.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents and/or container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Acrylic polymer solvent based

This product is a mixture.

Component	CASRN	Concentration
Xylene	1330-20-7	>= 26.0 - < 28.0 %
Toluene	108-88-3	>= 14.0 - < 16.0 %
Ethylbenzene	100-41-4	>= 5.0 - < 7.0 %
tert-Butyl 2-ethylperoxyhexanoate	3006-82-4	>= 0.5 - < 0.9 %

4. FIRST AID MEASURES

Description of first aid measures**General advice:**

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If burn is present, treat as any thermal burn, after decontamination. Alcohol consumed before or after exposure may increase adverse effects. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Dry sand. Dry chemical.

Unsuitable extinguishing media: High volume water jet. Do not use direct water stream..

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Nitrogen oxides (NOx).

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.. Flammable mixtures may exist within the vapor space of containers at room temperature.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Ventilate the area. Use personal protective equipment. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and

handling equipment. Vapor explosion hazard. Keep out of sewers. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ground and bond container and receiving equipment.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Xylene	OSHA Z-1	TWA	435 mg/m ³ 100 ppm
	ACGIH	TWA	100 ppm
	Further information: A4: Not classifiable as a human carcinogen		
	ACGIH	STEL	150 ppm
	Further information: A4: Not classifiable as a human carcinogen		
Toluene	ACGIH	TWA	20 ppm
	Further information: A4: Not classifiable as a human carcinogen; Ototoxicant		

	OSHA Z-2	TWA	200 ppm
	OSHA Z-2	CEIL	300 ppm
	OSHA Z-2	Peak	500 ppm
Ethylbenzene	ACGIH	TWA	20 ppm
	Further information: A3: Confirmed animal carcinogen with unknown relevance to humans		
	OSHA Z-1	TWA	435 mg/m3 100 ppm
tert-Butyl 2-ethylperoxyhexanoate	Dow IHG	C	2 ppm

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	colourless clear
Odor	Sour, burnt odor
Odor Threshold	No data available
pH	Not applicable, substance/mixture is non-polar/aprotic
Melting point/range	-95.00 °C (-139.00 °F) Toluene
Freezing point	No data available
Boiling point (760 mmHg)	111.00 °C (231.80 °F) Toluene
Flash point	18.30 °C (64.94 °F) <i>PENSKY MARTENS CLOSED CUP</i>
Evaporation Rate (Butyl Acetate = 1)	1.90 Toluene
Flammability (solid, gas)	Not Applicable
Lower explosion limit	1.00 % vol Xylene
Upper explosion limit	7.00 % vol Xylene
Vapor Pressure	13.000000 mmHg at 20.00 °C (68.00 °F) estimated
Relative Vapor Density (air = 1)	3.6000 Xylene

Relative Density (water = 1)	1.0100
Water solubility	practically insoluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	466.00 - 530.00 °C (870.80 - 986.00 °F) Xylene
Decomposition temperature	No data available
Dynamic Viscosity	2,100.000 - 4,200.000 mPa.s
Kinematic Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Liquid Density	1.01 g/cm ³
Molecular weight	No data available
Percent volatility	49.00 - 51.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Highly flammable liquid and vapour.

Conditions to avoid: Avoid static discharge. Heat, flames and sparks.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products:

Decomposition products can include and are not limited to: Acrylic monomers. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Based on product testing:

LD50, Rat, male, > 5,000 mg/kg

Information for components:

Xylene

LD50, Rat, 4,300 mg/kg

Toluene

LD50, Rat, 5,580 mg/kg

Ethylbenzene

LD50, Rat, 3,500 mg/kg

tert-Butyl 2-ethylperoxyhexanoate

LD50, Rat, male and female, > 10,000 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Based on product testing:

LD50, Rabbit, > 3,000 mg/kg

Information for components:

Xylene

LD50, Rabbit, > 2,000 mg/kg

Toluene

LD50, Rabbit, 12,267 mg/kg

Ethylbenzene

LD50, Rabbit, 15,500 mg/kg

tert-Butyl 2-ethylperoxyhexanoate

LD50, Rat, female, 14,142 mg/kg

LD50, Rat, male, 20,000 mg/kg

Acute inhalation toxicity

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Alcohol consumption and exertion may increase the adverse effects of toluene.

As product: The LC50 has not been determined.

Information for components:

Xylene

Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. LC50, Rat, 4 Hour, vapour, 27.5 mg/l

Toluene

LC50, Rat, male, 4 Hour, vapour, 25.7 mg/l

LC50, Rat, female, 4 Hour, vapour, 30 mg/l

Ethylbenzene

LC50, Rat, 4 Hour, vapour, 17.2 mg/l

tert-Butyl 2-ethylperoxyhexanoate

Prolonged excessive exposure may cause serious adverse effects, even death.
Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

LC50, Rat, male and female, 4 Hour, dust/mist, 168.8 mg/l

Skin corrosion/irritation

Based on information for component(s):

Brief contact may cause moderate skin irritation with local redness.

Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Vapor may cause skin irritation.

May cause drying and flaking of the skin.

Information for components:

Xylene

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

Vapor may cause skin irritation.

May cause drying and flaking of the skin.

Toluene

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Ethylbenzene

Brief contact may cause moderate skin irritation with local redness.

Prolonged contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

May cause drying and flaking of the skin.

tert-Butyl 2-ethylperoxyhexanoate

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Based on product testing:

May cause moderate eye irritation which may be slow to heal.

May cause slight corneal injury.

Information for components:

Xylene

May cause moderate eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Toluene

May cause slight eye irritation.

May cause slight temporary corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

Ethylbenzene

May cause moderate eye irritation.

Vapor may cause lacrimation (tears).

tert-Butyl 2-ethylperoxyhexanoate

Essentially nonirritating to eyes.

Sensitization

Based on information for component(s):

Skin contact may cause an allergic skin reaction.

Has caused allergic skin reactions in humans.

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

Information for components:

Xylene

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

Toluene

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Ethylbenzene

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:

No relevant data found.

tert-Butyl 2-ethylperoxyhexanoate

Skin contact may cause an allergic skin reaction.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

Information for components:

Xylene

May cause respiratory irritation.
Route of Exposure: Inhalation
Target Organs: Respiratory system

Toluene

May cause drowsiness or dizziness.
Route of Exposure: Inhalation
Target Organs: Central nervous system

Ethylbenzene

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

tert-Butyl 2-ethylperoxyhexanoate

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Xylene

May be fatal if swallowed and enters airways.

Toluene

May be fatal if swallowed and enters airways.

Ethylbenzene

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia. May be fatal if swallowed and enters airways.

tert-Butyl 2-ethylperoxyhexanoate

Based on physical properties, not likely to be an aspiration hazard.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals:
Central nervous system.

Kidney
Liver
lung
Blood.

May cause hearing loss based on animal data.

Excessive exposure may cause neurologic signs and symptoms.

Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.

Intentional misuse by deliberately inhaling toluene may cause nervous system damage, hearing loss, liver and kidney effects and death.

Although one early inhalation study on ethylbenzene reported an adverse effect on the testes, recent, more comprehensive studies have not shown this effect.

Information for components:

Xylene

In animals, effects have been reported on the following organs:

Liver
kidney
Blood

Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans.

Toluene

In animals, effects have been reported on the following organs:

Central nervous system.

Excessive exposure may cause neurologic signs and symptoms.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.

Intentional misuse by deliberately inhaling toluene may cause nervous system damage, hearing loss, liver and kidney effects and death.

Ethylbenzene

In animals, effects have been reported on the following organs:

May cause hearing loss based on animal data.

Kidney.
Liver.
Lung.

Although one early inhalation study on ethylbenzene reported an adverse effect on the testes, recent, more comprehensive studies have not shown this effect.

tert-Butyl 2-ethylperoxyhexanoate

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Based on information for component(s): Ethylbenzene has been shown to cause cancer in laboratory animals. There is no evidence that these findings are relevant to humans. Workers exposed during 1933-1945 to very high vapor concentrations of ethyl acrylate and methyl methacrylate, and to volatile by-products of the ethyl acrylate/methyl methacrylate polymerization process, showed an increase in deaths due to colorectal cancer. Such increases were not observed in workers exposed after that time. Although suggestive, these findings do not establish a causal relationship between high level exposure to these acrylates and colorectal cancer.

Information for components:

Xylene

Xylene was not found to be carcinogenic in a National Toxicology Program bioassay in rats and mice.

Toluene

Did not cause cancer in laboratory animals.

Ethylbenzene

Ethylbenzene has been shown to cause cancer in laboratory animals. There is no evidence that these findings are relevant to humans.

tert-Butyl 2-ethylperoxyhexanoate

No relevant data found.

Carcinogenicity

Component

Ethylbenzene

List

IARC

ACGIH

Classification

Group 2B: Possibly carcinogenic to humans

A3: Confirmed animal carcinogen with unknown relevance to humans.

Teratogenicity

Based on information for component(s): Has been toxic to the fetus in lab animals at doses nontoxic to the mother. Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects. In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

Information for components:

Xylene

Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects. Available data are inadequate for evaluation of maternal toxicity.

Toluene

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

Ethylbenzene

Has caused birth defects in laboratory animals only at doses toxic to the mother. Has been toxic to the fetus in lab animals at doses nontoxic to the mother.

tert-Butyl 2-ethylperoxyhexanoate

No relevant information found.

Reproductive toxicity

Based on information for component(s): In animal studies, has been shown to interfere with fertility.

Information for components:

Xylene

In animal studies, did not interfere with reproduction.

Toluene

In animal studies, did not interfere with reproduction.

Ethylbenzene

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

tert-Butyl 2-ethylperoxyhexanoate

In animal studies, has been shown to interfere with fertility.

Mutagenicity

Based on information for component(s): In vitro genetic toxicity studies were negative in some cases and positive in other cases.

Information for components:**Xylene**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Toluene

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

Ethylbenzene

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

tert-Butyl 2-ethylperoxyhexanoate

In vitro genetic toxicity studies were negative in some cases and positive in other cases.
Animal genetic toxicity studies were negative.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**Xylene****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2.6 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

IC50, Daphnia magna (Water flea), 24 Hour, 1 - 4.7 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (algae), Static, 73 Hour, Growth rate, 4.36 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Pseudokirchneriella subcapitata (green algae), 73 Hour, Growth rate, 0.44 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), flow-through, 56 d, mortality, > 1.3 mg/l

Toluene**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

Acute toxicity to aquatic invertebrates

LC50, water flea Ceriodaphnia dubia, semi-static test, 48 Hour, 3.78 mg/l

Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

Toxicity to bacteria

IC50, Bacteria, 16 Hour, 29 mg/l

Chronic toxicity to fish

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), 7 d, number of offspring, 0.74 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 150 - 280 mg/kg

Ethylbenzene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 4.2 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 1.8 - 2.4 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth inhibition (cell density reduction), 3.6 - 4.6 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 12 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, 0.96 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 2 d, survival, 0.047 mg/cm²

tert-Butyl 2-ethylperoxyhexanoate

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, Poecilia reticulata (guppy), semi-static test, 96 Hour, 8.66 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 7.5 mg/l

Acute toxicity to algae/aquatic plants

ErC50, green alga Pseudokirchneriella subcapitata (formerly known as Selenastrum capricornutum), Static, 72 Hour, Growth rate, 0.4394 mg/l

Persistence and degradability**Xylene**

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Pass

Biodegradation: > 60 %

Exposure time: 10 d

Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 3.17 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	37.000 %
10 d	58.000 %
20 d	72.000 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 19.7 Hour

Method: Estimated.

Toluene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 3.13 mg/mg Calculated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 2 d

Method: Estimated.

Ethylbenzene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %

Exposure time: 6 d

Method: OECD Test Guideline 301E or Equivalent

Theoretical Oxygen Demand: 3.17 mg/mg Estimated.

Chemical Oxygen Demand: 2.62 mg/mg Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	31.5 %
10 d	38.5 %
20 d	45.4 %

Photodegradation

Sensitization: OH radicals

Atmospheric half-life: 55 Hour

Method: Estimated.

tert-Butyl 2-ethylperoxyhexanoate

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 55 %

Exposure time: 28 d

Theoretical Oxygen Demand: 2.44 mg/mg

Stability in Water (1/2-life)

Hydrolysis, half-life, 19.8 Hour

Photodegradation

Atmospheric half-life: 18.7 Hour

Method: Estimated.

Bioaccumulative potential

Xylene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 3.12 Measured

Bioconcentration factor (BCF): 25.9 Rainbow trout (Salmo gairdneri) Measured

Toluene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.73 Measured

Bioconcentration factor (BCF): 13.2 - 90 Fish Measured

Ethylbenzene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 3.15 Measured

Bioconcentration factor (BCF): 15 Fish Measured

tert-Butyl 2-ethylperoxyhexanoate

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 4.79 Measured

Mobility in soil

Xylene

Partition coefficient (Koc): 443 Estimated.

Toluene

Partition coefficient (Koc): 37 - 178 Estimated.

Ethylbenzene

Partition coefficient (Koc): 518 Estimated.

tert-Butyl 2-ethylperoxyhexanoate

Partition coefficient (Koc): 390 - 2200 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. FOR UNUSED AND UNCONTAMINATED PRODUCT, always send to a licensed disposer per applicable regulations. Consult the local waste disposal expert for the appropriate waste disposal method. Recover or recycle, if possible. Otherwise, send it to a licensed disposer.

Contaminated packaging: Empty containers retain product residues. Follow label warnings even after container is emptied. Improper disposal or reuse of this container may be dangerous and illegal. Refer to applicable federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Resin solution
UN number	UN 1866
Class	3
Packing group	II
Reportable Quantity	Toluene, Xylene

Classification for SEA transport (IMO-IMDG):

Proper shipping name	RESIN SOLUTION
UN number	UN 1866
Class	3
Packing group	II
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the	Consult IMO regulations before transporting ocean bulk

IBC or IGC Code**Classification for AIR transport (IATA/ICAO):**

Proper shipping name	Resin solution
UN number	UN 1866
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Flammable (gases, aerosols, liquids, or solids)
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN
Xylene	1330-20-7
Toluene	108-88-3
Ethylbenzene	100-41-4

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Acrylic polymer	Trade secret
Xylene	1330-20-7
Toluene	108-88-3
Ethylbenzene	100-41-4

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**HMIS**

Health	Flammability	Physical Hazard
3*	3	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 10004914 / 1001 / Issue Date: 08/05/2021 / Version: 8.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
C	Ceiling limit
CEIL	Acceptable ceiling concentration
Dow IHG	Dow Industrial Hygiene Guideline
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire

Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

ROHM & HAAS CHEMICALS LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US