



UBZ 7972 HF

PRODUCT INFORMATION

Description

Liquid Ba/Zn Stabilizer

Typical Properties

Appearance:	Clear amber liquid
Specific gravity at 20°C:	1.02
Refractive Index at 20 °C:	1.4781

Application

BAEROSTAB UBZ 7972HF is a high efficiency liquid Ba/Zn stabilizer designed for flexible and semi-rigid clear, extrusion and injection molding compounds, calendared film and sheet offering good heat stability and clarity.

BAEROSTAB UBZ 7972HF is especially recommended for applications where high clarity is required.

The addition of 2 to 5 phr of epoxy soya plasticizer (ESO) can be made to improve the heat stability. The addition of 0.1 to 0.2 phr Stearic Acid is recommended as additional lubrication for extrusion and injection molding applications. For optimum clarity no more than 0.10 phr Stearic Acid should be used.

Recommended Use Level: 2.0 phr

Food Packaging Approval

UBZ 7972 HF may not be used for the manufacturing of food packaging materials.

Handling

A material safety data sheet for the handling of this product is available on request.

Storage

Dry storage at room temperature is recommended.
Once opened, packaging should be firmly closed.

The data herein is deemed accurate by the supplier, however, is provided for informational purposes only and creates no warranties, express or implied. As the consumer controls application of the product, this information does not constitute a warranty of merchantability, fitness for a particular use or recommendations to practice any patented invention without a license.