

# BLUESIL SP 3307

<b>Description</b>	<b>BLUESIL SP 3307</b> is a polyether modified polysiloxane.													
<b>Examples of applications</b>	<b>BLUESIL SP 3307</b> is a super wetting agent which can find applications in many fields like for instance: <ul style="list-style-type: none"> <li>• Agrochemicals</li> <li>• Fiber treatment</li> <li>• Surface modification and formulation additive</li> <li>• Leather treatment</li> </ul>													
<b>Key benefits</b>	<ul style="list-style-type: none"> <li>• Very good wetting properties</li> <li>• Improves the adherence of coatings</li> <li>• High surface activity</li> <li>• Affinity with various surfaces</li> <li>• Extra fluid viscosity</li> <li>• high spreading rate</li> </ul>													
<b>Typical properties</b>	<table border="1"> <tr> <td><b>Appearance</b></td> <td>liquid</td> </tr> <tr> <td><b>Colour</b></td> <td>slightly yellow</td> </tr> <tr> <td><b>Density at 25°C, approx</b></td> <td>1.02</td> </tr> <tr> <td><b>Surface tension at 25°C, mN.m-1, 100% approx</b></td> <td>23</td> </tr> <tr> <td><b>Viscosity mPa.s at 25°C</b></td> <td>25</td> </tr> <tr> <td><b>Flash point (close cup),°C</b></td> <td>&gt;100</td> </tr> </table> <p>Soluble into water and all polar solvents. Please note: The typical properties are not intended for use in preparing specifications. Please contact our local Sales Department for assistance in writing specifications.</p>		<b>Appearance</b>	liquid	<b>Colour</b>	slightly yellow	<b>Density at 25°C, approx</b>	1.02	<b>Surface tension at 25°C, mN.m-1, 100% approx</b>	23	<b>Viscosity mPa.s at 25°C</b>	25	<b>Flash point (close cup),°C</b>	>100
<b>Appearance</b>	liquid													
<b>Colour</b>	slightly yellow													
<b>Density at 25°C, approx</b>	1.02													
<b>Surface tension at 25°C, mN.m-1, 100% approx</b>	23													
<b>Viscosity mPa.s at 25°C</b>	25													
<b>Flash point (close cup),°C</b>	>100													
<b>Instruction of use</b>	Please consult your local ELKEM SILICONES sales office.													
<b>Regulation</b>	Please consult your local ELKEM SILICONES sales office.													
<b>Limitations</b>	Please consult your local ELKEM SILICONES sales office.													
<b>Packaging</b>	<ul style="list-style-type: none"> <li>• BLUESIL SP 3307 is available in                             <ul style="list-style-type: none"> <li>○ Tote bin of 1000 KG (2205 LB)</li> </ul> </li> </ul>													
<b>Storage and shelf life</b>	When stored in its original packaging: BLUESIL SP 3307 may be stored at temperatures between -5°C / 23°F and 40°C / 104°F for up to 18 months from its date of manufacturing. Comply with the storage instructions and expiration date marked on the packaging. Beyond this date, Elkem Silicones no longer guarantees that the product meets the sales specifications.													
<b>Safety</b>	Please consult the Safety Data Sheet of: BLUESIL SP 3307													

Visit our website [www.elkem.com/silicones/](http://www.elkem.com/silicones/)

#### Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELKEM SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Determination of the suitability of product for the uses and applications contemplated by users and others shall be the sole responsibility of users. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELKEM SILICONES is at their disposal to supply any additional information.

# BLUESIL SP 3307