

Revision Number: 002.0 Issue date: 09/11/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE S-AD 1246 SOLID IDH number:

LUBRICANT ADDITIVE ACHESON

known as SLA1246

Product type: Lubricant Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

United States Region:

Contact information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1224689

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW WARNING: CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.

	HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION		2
FYF IRRITATION		2A

PICTOGRAM(S)



Precautionary Statements

Prevention: Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for Response:

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take

off contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	30 - 60

IDH number: 1224689 Product name: BONDERITE S-AD 1246 SOLID LUBRICANT ADDITIVE ACHESON known as SLA1246

Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	10 - 30
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	1 - 5
Distillates (petroleum), solvent-refined light paraffinic, contains < 3% DMSO	64741-89-5	1 - 5

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). If

symptoms develop and persist, get medical attention.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice. If symptoms develop and persist, get medical attention.

Ingestion: Immediate medical treatment necessary. DO NOT induce vomiting unless

directed to do so by medical personnel.

Symptoms: See Section 11.

IDH number: 1224689

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not empty into drains /

surface water / ground water.

Clean-up methods: Ensure adequate ventilation. Wear protective clothing, gloves and safety

glasses. Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local

governmental regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. Remove all sources of ignition. Do not take internally. For industrial use only. Launder work clothes frequently. Ground and bond all

equipment as required (when transferring products).

Storage: For safe storage, store at or below < 90 °F (< 32.2 °C)

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty

containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), solvent-refined heavy paraffinic	5 mg/m3 TWA Inhalable fraction. 5 mg/m3 TWA mist 10 mg/m3 STEL mist	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist. 5 mg/m3 TWA mist	None	None
Distillates (petroleum), hydrotreated light paraffinic	None	5 mg/m3 PEL Mist.	None	None
Distillates (petroleum), solvent-dewaxed heavy paraffinic	None	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Distillates (petroleum), solvent-refined light paraffinic, contains < 3% DMSO	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist.	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Gray

Odor: Slight hydrocarbon
Odor threshold: Not available.
pH: Not applicable

Vapor pressure: < 0.1 mm hg (20 °C (68°F)) None

Boiling point/range: > 260 °C (> 500°F) None

Melting point/ range:Not determinedSpecific gravity:0.97 - 1.01Vapor density:Not determined

Flash point: 190 °C (374°F) Pensky Martens closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Not available.
Not determined
Not applicable
Insoluble

IDH number: 1224689 Product name: BONDERITE S-AD 1246 SOLID LUBRICANT ADDITIVE ACHESON known as SLA1246

Partition coefficient (n-octanol/water): Not determined

VOC content: 0 g/l 500 cp Viscosity: **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: None under normal processing.

Hazardous decomposition Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

products:

molecular weight hydrocarbons.

Incompatible materials: This product may react with strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: This product is irritating to the respiratory system. Excessive inhalation of this material causes

headache, dizziness, nausea and incoordination.

Skin contact: This product may cause irritation to the skin. Prolonged and/or repeated skin contact with this

product may cause irritation/dermatitis. A component in this product may be absorbed through

the skin, especially if skin is damaged.

Eve contact: This product may cause irritation to the eyes.

Ingestion: Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), solvent-refined heavy paraffinic	None	Irritant
Distillates (petroleum), hydrotreated light paraffinic	None	Irritant, Some evidence of carcinogenicity
Distillates (petroleum), solvent-dewaxed heavy paraffinic	None	Irritant
Distillates (petroleum), solvent-refined light paraffinic, contains < 3% DMSO	None	Irritant, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), solvent-refined heavy paraffinic	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No
Distillates (petroleum), solvent-refined light paraffinic, contains < 3% DMSO	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: No data available.

IDH number: 1224689 Product name: BONDERITE S-AD 1246 SOLID LUBRICANT ADDITIVE ACHESON known as SLA1246

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Wastes must be tested using methods described in 40 CFR Part 261 to

determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None

Identification number:

Packing group:

None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

Issue date: 09/11/2014

IDH number: 1224689 Product name: BONDERITE S-AD 1246 SOLID LUBRICANT ADDITIVE ACHESON known as SLA1246

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.