

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 16-Sep-2020 Revision Number 4

1. Identification

Product identifier

Product Name Aluminum Paste

Other means of identification

Product Code(s) TZ-585A; TZ-588A; TZ-788A; TZ-200A; TZ-7150A; TZ-7155A; TZ-716A; TZ-716A; TZ-715A; TZ-

816A; TZ-826A; TZ-65466A; MG1200

Synonyms Aluminum Paste

Recommended use of the chemical and restrictions on use

Recommended use Pigments and coatings manufacturing

Restrictions on useNo information available.

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address

Toyal America, Inc.

Toyal Zhaoqing Co., Ltd.

Toyal Zhaoqing Co., Ltd.

Linjiang Industry Park, Zhaoqing

Lockport, IL 60441 USA

High Technology Industry Development Zone, Zhaoqing

Facility Phone: 815-740-3000 Guangdong, China Post No. 526238

86-758-3602080

Emergency telephone number

Emergency telephone CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

1-800-424-9300 (NORTH AMERICA)

2. Hazard(s) identification

Classification

Specific target organ toxicity (single exposure)

Category 3

Label elements

Warning

Hazard statements

May cause respiratory irritation.

SDS ID: TA-010 Page 1 / 9

May cause drowsiness or dizziness.



Precautionary Statements - Prevention

Avoid breathing dust, fume, gas, mist, vapors and spray. Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

: .

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

Other information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Synonyms

Aluminum Paste

| Chemical name | CAS No | Weight-% | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|--|------------|----------|---|---|
| Aluminum powder (stabilized) | 7429-90-5 | 60-80 | - | - |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | 10-30 | - | - |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | 5-20 | - | - |
| 1,2,4 Trimethylbenzene | 95-63-6 | < 3 | - | - |
| Oleic acid | 112-80-1 | <=2 | - | - |

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if

SDS ID: TA-010 Page 2 / 9

Skin contact Wash skin with soap and water. Get medical attention if symptoms occur.

symptoms occur.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable Extinguishing Media Carbon dioxide (CO2). Dry sand.

Unsuitable extinguishing media Water. Halogenated extinguishing agents.

Specific hazards arising from the

chemical

In the event of fire and/or explosion do not breathe fumes. Do not allow evaporation to dryness. Avoid generation of dust. Fine dust dispersed in air may ignite. In case of contact

with acid or alkaline (as well as water), aluminum powder will react and emission of

hydrogen will occur.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Evacuate

personnel to safe areas.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Take up with sand or other noncombustible absorbent material and place into containers for

later disposal.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Ensure adequate

ventilation. Avoid breathing vapors or mists. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. Do not eat, drink or smoke when

using this product.

SDS ID: TA-010 Page 3 / 9

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container dry.

Store away from incompatible materials. See section 10 for more information. Keep away

from food, drink and animal feeding stuffs.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

| Chemical name | ACGIH TLV | | OSHA | PEL | | NIOS | H |
|------------------------------|-------------------------------|--------|-------------------------|----------------------------|-----------------|----------------------|----------------------|
| Aluminum powder (stabilized) | TWA: 1 mg/m ³ resp | irable | TWA: 15 mg/r | | | 10 mg/m ³ | total dust |
| 7429-90-5 | particulate matte | er | TWA: 5 mg/m | ³ respirable | TWA: 5 | mg/m ³ ı | espirable dust |
| | | | frac | ion | | | |
| | | | (vacated) TWA: | 15 mg/m ³ total | | | |
| | | | du | st | | | |
| | | | (vacated) TV | | | | |
| | | | respirable | fraction | | | |
| 1,2,4 Trimethylbenzene | - | | - | | | TWA: 25 | ppm |
| 95-63-6 | | | | | | TWA: 125 | mg/m ³ |
| Chemical name | Alberta | Britis | sh Columbia | Ontario | | Q | uebec |
| Aluminum powder (stabilized) | TWA: 10 mg/m ³ | TWA | : 1.0 mg/m ³ | TWA: 1 mg | /m ³ | TWA: | 10 mg/m ³ |
| 7429-90-5 | _ | | | | | | - |

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls Avoid release to the environment.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Contaminated work

clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using

this product. Avoid breathing vapors or mists.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Silver paste
Physical state Solid

SDS ID: TA-010 Page 4 / 9

Color Silver Odor Aromatic

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

None known No data available Ha Melting point / freezing point No data available None known Boiling point / boiling range No data available None known Flash point No data available None known **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available None known Vapor density No data available None known Relative density 1.8 None known Water solubility No data available None known Solubility(ies) No data available None known **Partition coefficient** No data available None known No data available **Autoignition temperature** None known No data available

Decomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other information

Explosive properties
Oxidizing properties
No information available.
No information available.
No information available.
No information available

10. Stability and reactivity

Reactivity None under normal use conditions.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions In case of contact with acid or alkaline (as well as water), aluminum powder will react and

emission of hydrogen will occur. May catch fire on contact with mineral acids, azo, diazo and hydrazine compounds, halogenated organic substances, and powerful oxidizing

agents. May generate flammable gases on contact with mineral acids.

Conditions to avoid Incompatible materials. Do not allow evaporation to dryness. Dust formation.

Incompatible materials Incompatible with oxidizing agents. Water. Acids. Alcohols. Halogens. Alkalis. Nitrates.

Halogenated hydrocarbons.

Hazardous decomposition products Hydrogen.

11. Toxicological information

Information on likely routes of exposure

Product Information

SDS ID: TA-010 Page 5 / 9

Inhalation Specific test data for the substance or mixture is not available. May cause drowsiness or

dizziness. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Contact with eyes may

cause irritation.

Skin contact Specific test data for the substance or mixture is not available. May be harmful in contact

with skin.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|--------------------|-------------------------|------------------------------------|
| Naphtha (petroleum), hydrotreated heavy | > 6000 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | > 8500 mg/m ³ (Rat) 4 h |
| Solvent naphtha (petroleum), light arom. | = 8400 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 3400 ppm (Rat) 4 h |
| 1,2,4 Trimethylbenzene | = 3280 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 18 g/m ³ (Rat) 4 h |
| Oleic acid | = 25 g/kg (Rat) | - | - |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposureNo information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

| Chemical name | Algae/aquatic plants | Fish | Toxicity to | Crustacea |
|---------------|----------------------|------|-------------|-----------|
| | | | | _ |

SDS ID: TA-010 Page 6 / 9

| | | | microorganisms | |
|---|---|--|----------------|---|
| Naphtha (petroleum), hydrotreated heavy 64742-48-9 | - | LC50: =2200mg/L (96h, Pimephales promelas) | - | - |
| Solvent naphtha (petroleum), light arom. 64742-95-6 | - | LC50: =9.22mg/L (96h, Oncorhynchus mykiss) | - | EC50: =6.14mg/L (48h, Daphnia magna) |
| 1,2,4 Trimethylbenzene 95-63-6 | - | LC50: 7.19 - 8.28mg/L (96h, Pimephales promelas) | - | EC50: =6.14mg/L (48h, Daphnia magna) |
| Oleic acid 112-80-1 | - | LC50: =205mg/L (96h, Pimephales promelas) | - | - |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical name | Partition coefficient |
|------------------------|-----------------------|
| 1,2,4 Trimethylbenzene | 3.63 |
| 95-63-6 | |

Mobility in soil No information available.

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Dispose of in accordance with local regulations, Dispose of waste in accordance with

environmental legislation.

Contaminated packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical name | | California Hazardous Waste Status |
|------------------------------|-----------|-----------------------------------|
| Aluminum powder (stabilized) | | Ignitable powder |
| | 7429-90-5 | |

14. Transport information

DOT Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

SDS ID: TA-010 Page 7 / 9

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.

| Chemical name | CAS No | US TSCA Inventory listing | US TSCA inactive/active |
|------------------------|---------|---------------------------|-------------------------|
| | | | designation |
| 1,2,4 Trimethylbenzene | 95-63-6 | Present | Active |

DSL/NDSL

Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical name | SARA 313 - Threshold Values % | |
|--|-------------------------------|--|
| Aluminum powder (stabilized) - 7429-90-5 | 1.0 | |
| 1.2.4 Trimethylbenzene - 95-63-6 | 1.0 | |

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts | Pennsylvania |
|------------------------------|------------|---------------|--------------|
| Aluminum powder (stabilized) | X | X | X |
| 7429-90-5 | | | |
| 1,2,4 Trimethylbenzene | X | X | X |
| 95-63-6 | | | |
| Oleic acid | - | - | X |

SDS ID: TA-010 Page 8 / 9

| 112-80-1 | | |
|----------|--|--|

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and chemical

properties -

<u>HMIS</u> Health hazards 1 Flammability 0 Physical hazards 0 Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Key literature references and sources for data used to compile the SDS

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Issuing Date 05-May-2015

Summary of Changes: Rev 1, 5 May 2015 New SDS Format

Rev 2, 18 Sept 2015 Corrected name of 64742-48-9 in Section 3 & 11 Rev 3, 7 Oct 2016 Changes to Sections 2,3,4,8,9,11,12,14 & 15 Rev 4, 16 Sept 2020 Revise for non-hazardous, no longer UN1325

Revision Note Change to classification.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet