

# SAFETY DATA SHEET

This SDS complies with OSHA HazCom Standard 29 CFR 1910.1200 (GHS), Canadian Workplace Hazardous Material Information System (WHMIS), Mexico NOM-018-STPS-2015

## SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

**1.1 Product Identifier:**

Product Form: Substance  
 Chemical Name: Barium Sulfate

Product Name(s): POLYWATE 325, CIMBAR 325, CIMBAR PC, CIMBAR XF, CIMBAR UF, CIMBAR EX, CIMBAR BF, BARIMITE 200, #22 BARYTES, #44 BARYTES, BARIMITE 10, BARIMITE XF, BARIMITE UF, BARISCAN ULTRA, BARISCAN ELITE, MITI-WITE B1, MITI-WITE B3, MITI-WITE B10.

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Identified uses: Pigment, filler for paint and plastics.  
 Uses Advised Against: Any use other than those identified.

**1.3 Details of the supplier of the Safety Data Sheet:**

Manufacturer: CIMBAR Performance Minerals  
 49-0 Jackson Lake Rd., Chatsworth GA 30705 (Corporate Office)  
 Emergency Phone: (800)-852-6868, ext. 1108

## SECTION 2- HAZARDS IDENTIFICATION

**2.1 Classification of the Substance or Mixture:**

OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity: Category 2 (H351)  
 Specific target organ toxicity (STOT)- repeated exposure, category 2 Lungs


Physical Hazards: Not classified.

Health Hazards: Carcinogenicity category 2 (Lungs).

Environmental Hazard: Not classified.

**2.2 Label Elements:**

GHS-US Labeling:

Hazard Pictogram (Health Hazard)		
Signal Word	Warning	
Hazard Statements	H351	Suspected of causing cancer
Precautionary Statements	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P260	Do not breathe dust.
	P280	Wear protective gloves, protective clothing, eye protection, face protection.
	P308+P313	If exposed or concerned: Get medical attention/advice.

\*Respirable Silica: The amount of respirable silica (<10 microns) is less than 0.60%.

**2.3 Other Hazards: None known.**

## SECTION 3- COMPOSITION/INFORMATION ON THE COMPONENTS

### 3.1 Chemical Characterization (Substances):

Chemical	CAS Number	% Weight	Classification
Barium Sulfate	7727-43-7, 13462-86-7	80-100	None
Crystalline Silica, quartz	14808-60-7	1-5	Carc. 1A, *STOT- repeated exposure, category 2

\*Specific target organ exposure

### 3.2 Chemical Characterization (Mixtures): No mixtures.

## SECTION 4- FIRST AID MEASURES

### 4.1 Description of first aid measures:

General Advice: When in doubt or if symptoms are observed, get medical advice.

Inhalation: Move to fresh air. Give symptomatic treatment as necessary.

Skin contact: Wash with soap and water.

Eye contact: Wash with soap and neutral eyewash solution.

Ingestion: Do not induce vomiting. Give up to 200 ml water. In case of persistent symptoms, consult a doctor.

**4.2 More important symptoms/effects, acute and delayed:** Signs and symptoms may include coughing, gasping, choking and difficulty breathing.

**4.3 Indication of immediate medical attention and special treatment needed:** If exposed or concerned: Get medical advice/attention. Treatment should be symptomatic and supportive. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

## SECTION 5- FIRE FIGHTING MEASURES

### 5.1 Extinguishing Media

Suitable Extinguishing Media: Water spray (fog), foam, dry chemical, carbon dioxide (CO2).

Unsuitable Extinguishing Media: None known.

**5.2 Special hazards arising from the substance or mixture:** Do not breathe dust.

**5.3 Advice for Firefighters:** In case of fire and/or explosion do not breathe fumes.

## SECTION 6- ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:** Keep unauthorized personnel away. Use personal protection recommended in Section 8.

**6.2 Environmental precautions:** Avoid dust dispersion to the environment. Prevent leakages from entering drains and ditches that lead to natural waterways.

**6.3 Methods and material for containment and cleaning up:** Clean by sweeping or vacuum. Avoid dust generation and spreading of dust.

**6.4 Reference to other sectors:** Section 8. Exposure controls and personal protection. See Section 13 for additional waste treatment information.

## SECTION 7- HANDLING AND STORAGE

- 7.1 Precautions for safe handling: Avoid overexposure-** obtain special instructions before use. Ensure adequate ventilation. Do not breathe dust. Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice.
- 7.2 Conditions for safe storage, including any incompatibilities:** Store in tightly closed original container in a dry place. No incompatible products known.

## SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control Parameters:

#### Occupational Exposure Limits

Substance Identification	Type	Value
Barium Sulfate	OSHA PEL (USA)	10 mg/m <sup>3</sup>
	ACGIH TLV (USA)	10 mg/m <sup>3</sup>
	Canada	0.5 mg/m <sup>3</sup>
	Canada- BC TWA	0.5 mg/m <sup>3</sup>
Crystalline Silica (Quartz)	OSHA (TWA)	0.05 mg/m <sup>3</sup>
	OSHA (action level)	0.025 mg/m <sup>3</sup>
	ACGIH (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	NIOSH (TWA)	0.05 mg/m <sup>3</sup> (respirable fraction)
	Canada (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	Canada- BC (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	Canada- Manitoba- OEL (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	Canada- Newfoundland/Labrador-OEL (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	Canada- Nova Scotia-OEL (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	Canada- Prince Edward Island-OEL (TWA)	0.025 mg/m <sup>3</sup> (respirable fraction)
	Mexico (TWA)	0.1 mg/m <sup>3</sup> (respirable fraction)

### 8.2 Exposure Controls:

**Engineering Measures:** Engineering methods to prevent or control exposure are preferred. If they are not effective, then suitable personal protective should be used.

**Personal Protective Equipment:**

**Respiratory Protection:** The specific respirator selected must be based on the airborne concentration found in the workplace and must not exceed the working limits of the respirator.

**Hand Protection:** For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

**Eye/Face Protection:** Wear safety glasses with side shields (or goggles).

**Skin/Body Protection:** Wear suitable protective clothing.

**Hygiene Measures:** Follow general hygiene considerations recognized as common good workplace practices. Wash daily at the end of each shift, and prior to eating, drinking, smoking, etc.

**Environmental Exposure Controls:** Dispose of in accordance with local regulations.

## SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

Appearance:	
Physical State:	Solid
Color:	Beige to white.
Specific Gravity:	4.0-4.30.
Odor:	Odorless
Boiling/Melting Point: Point:	N/A
Evaporation Rate:	N/A
Vapor Pressure (mm Hg):	N/A Vapor Density (Air=1): N/A
Solubility in water:	Insoluble in Water
MOHS Hardness:	2.5-3.5
pH:	8-10 @ 10% slurry in water

### 9.2 Other Information:

Volatile Organic Compound (VOC): 0% (EC/1999/13)

## SECTION 10- STABILITY AND REACTIVITY

**10.1 Reactivity:** No reactivity known.

**10.2 Chemical stability:** Stable under normal temperatures and pressures.

**10.3 Possibility of hazardous reactions:** Hazardous Polymerization- Will not polymerize.

**10.4 Conditions to avoid:** None known.

**10.5 Incompatibility:** Strong acids.

**10.6 Hazardous decomposition products:** None known.

## SECTION 11- TOXICOLOGICAL INFORMATION

General Information: Users are advised to consider national occupational exposure limits or other equivalent values.

### Information on Likely Routes of Exposure:

Inhalation: Extended inhalation at levels above the workplace limit value can could cause irreversible damage to the lungs (silicosis).

Skin: Contact with dust could cause mechanical irritation or drying of the skin.

Eyes: Avoid contact with eyes. Dust contact with the eyes can lead to mechanical irritation.

Ingestion: Ingestion is not a likely route of exposure.

Aspiration: Not an expected route of exposure.

### Symptoms Related to the physical, chemical and toxicological characteristics:

Contact with dust may cause mechanical irritation or drying of the skin. Dust may cause mechanical irritation to eyes. May cause irritation to the respiratory tract.

### 11.1 Information on toxicological effects:

Barite:

Oral LD50: 15000 mg/kg (oral rat)

**Crystalline Silica:**

Oral LD50	500 mg/kg (oral rat)
ACGIH	Group 2A- Probably carcinogenic to humans
IARC	Group 1- Carcinogenic to humans

**Acute Toxicity:** Users are advised to consider national occupational exposure limits or other equivalent values.

**Chronic Toxicity:** Potential occupational carcinogen.

**Chronic Effects:** Extended inhalation at levels above the workplace limit value may cause irreversible damage to the lungs (silicosis).

**Respiratory Sensitization:** Could cause respiratory tract inhalation if inhaled.

**Serious Eye Damage/Irritation:** Dust may cause mechanical irritation to the eyes.

**Skin Irritation:** Prolonged or repeated contact may dry skin and cause irritation.

**Carcinogenicity:** Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1).

**SECTION 12- ECOLOGICAL INFORMATION**

**12.1 Ecotoxicity:** Not considered harmful to aquatic life.

Crystalline Silica, quartz (impurity)

WGK Classification (VwVwS) 849: nwg

**12.2 Persistence/Degradability:** Not readily biodegradable.

**12.3 Bioaccumulation potential:** None.

**12.4 Mobility in soil:** The product is insoluble in water and will sediment in water systems.

**12.5 Results of PBT and vPvB assessment:** According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances like Barium Sulfate.

**12.6 Other adverse effects:** None.

**SECTION 13- DISPOSAL**

**13.1 Waste treatment methods:** Dispose of waste and residues in accordance with all applicable local and national regulations.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**Waste Codes:** Waste codes should be assigned by the user based on the application for which the product was used.

Crystalline Silica, quartz (impurity): WGK Classification (VwVwS) 849: nwg

## SECTION 14- TRANSPORT INFORMATION

Mode of Transportation (Road, Water, Air, Rail)

**14.1 UN Number:** N/A.

**14.2 UN Proper shipping name:** N/A.

**14.3 Transport hazard class(es):**

ADR: not regulated

IMDG: not regulated

ICAO/IATA: not regulated

RID: not regulated

DOT: not regulated

**14.4 Packing Group:** N/A.

**14.5 Environmental hazards:** None.

**14.6 Special precautions for user:** None.

**14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.

## SECTION 15- REGULATORY INFORMATION

### Global Inventories

**Pure Substance/Mixture:** Substance

Chemical Name	CAS No.	EC No.	REACH Registration No.	AUS (AICS)	CAN (DSL)	China (IECSC)	Japan	S. Korea (KECL)	Mexico	New Zealand	Phil. (PICCS)	Taiwan	TSCA USA
Barium Sulfate	13462-86-7, 7727-43-7	236-664-5	Exempt	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Crystalline Silica	14808-60-7	238-878-4	Exempt	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

### US Federal Regulations:

EPA (Crystalline Silica, quarts, impurity)

CERCLA: Not listed

SARA 304: Listed

SARA 313: Listed

SARA 302 RQ, lbs: Not listed

SARA 304: Not listed

SARA 311/312 Hazardous Categorization: Hazardous chemical/ immediate health effects/delayed health effects

Crystalline Silica, quartz (impurity)


Acute Health Hazard: Yes

Chronic Health Hazard: Yes

CWA (Clean Water Act): Not listed.

### US State Right-to-Know Regulations

Chemical Name	CAS No.	Cal. Prop 65	Massachusetts	Minnesota	New Jersey	Pennsylvania
Barium Sulfate	13462-86-7, 7727-43-7			Y		
Crystalline Silica, quartz (impurity)	14808-60-7	Y	Y	Y	Y	Y

**California Proposition 65:**  **WARNING-** This product can expose you to chemicals including silica, crystalline, which is known in the state of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CANADA (WHMIS):** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Crystalline Silica, quartz (impurity): D2A- Very toxic materials 0.1%

## SECTION 16- OTHER INFORMATION\CONTACT

### Acronyms:

EPA = Environmental Protection Agency  
TSCA = Toxic Substance Control Act  
ACGIH = American Conference of Governmental Industrial Hygienists  
IARC = International Agency for Research on Cancer  
NIOSH = National Institute for Occupational Safety and Health  
NTP = National Toxicology Program  
OSHA = Occupational Safety and Health Administration  
DOT = Department of Transportation  
RCRA = Resource Conservation and Recovery Act

### Other Information:

Disclaimer: CIMBAR Performance Minerals (CPM) is not responsible for the use of information, product, method, or apparatus herein presented ("Information"), and you must make your own determination as to its suitability and completeness for your own use, for the protection of the environment, and for health and safety purposes. You assume the entire risk of relying on this information. In no event shall CPM be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information. By providing this information, CPM neither can nor intends to control the method or manner by which you use, handle, store, or transport CPM products. Nothing herein shall be construed as a recommendation or license to use any Information that conflicts with any patent, trademark or copyright. Safety Data Sheets providing safety precautions that should be observed in handling and storing CPM products are available upon request. You should obtain and review the available material safety information before handling any of these products.

CPM MAKES NO PRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE REGARDING THIS INFORMATION, AND NOTHING HEREIN WAIVES ANY CONDITIONS OF SALE.

This information could include technical inaccuracies or typographical errors. Changes are periodically added to the information herein; these changes will be incorporated in revisions of the information.

CPM may make improvements and/or changes in the product(s) described in this information at any given time.

The information contained herein is based on data available to CIMBAR Performance Minerals and is believed to be correct. However, CIMBAR Performance Minerals makes no warranty, expressed or implied, regarding the accuracy or completeness of this information or the results to be obtained from the use thereof.

CIMBAR Performance  
Minerals Quality Assurance  
Department Phone: 1-800-  
852-6868  
Fax: 770-607-3799  
[www.cimbar.com](http://www.cimbar.com)