

TECHNICAL DATA SHEET

CRAYVALLAC® WW-1001

Dispersion of polyethylene wax in water

Wax dispersion

TYPICAL CHARACTERISTICS

Nature	Polyolefin
Appearance	Low viscous white milky liquid
Solid Content (%)	Approx. 40%
Active Content (%)	40
Brookfield viscosity (mPa.s)	Approx. 100
Specific gravity	1

DESCRIPTION

CRAYVALLAC® WW-1001 is a 40% active dispersion of polyethylene wax in water. The low viscosity and high active content of this dispersion, together with freedom from dust, assist the efficiency of manufacturing processes. CRAYVALLAC® WW-1001 provides the formulator with the means of controlling the frictional characteristics of a coating as well as enhancing its surface protection properties.

RECOMMENDED ADDITION LEVEL

1.0 – 6.0% under low to medium shear dispersion

STANDARD PACKAGING

Other packaging may be available upon request

- 200 Kg Drum
- 20 Kg Pail

HANDLING & STORAGE

It should be stored in the original containers in a dry place at temperatures between 5°C (41°F) and 30°C (86°F). Avoid exposure to direct sunlight or frost. Exposure to temperatures less than 5°C may result in product agglomeration and settling.

In these conditions, this product should be used within 24 months from production.

PROCESSING INSTRUCTIONS

CRAYVALLAC® WW-1001 is readily dispersed into coating formulations using a variety of techniques. It also retards the settlement of pigments and assists in their re-dispersion. The use of pre-dispersed waxes, such as CRAYVALLAC® WW-1001, avoids the inconveniences commonly associated with micronised powders. Dispersions by nature are also easier and more efficient to incorporate, as they require less intensive processing.

MARKETS

Coatings & Inks

- Architectural Coating
- Graphic Arts
- Industrial Coating

KEY BENEFITS

FORMULATION

- Post addition
- Ready to use
- Easy handling



FILM PROPERTIES

- Matting effect
- Slip improvement
- Scratch resistance



SAFER SOLUTIONS

- APEO Free*
- Heavy Metal Free*
- Solvent Free*

* Not intentionally added but not specifically measured (not part of product specification)

CRAYVALLAC® WW-1001

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)