

# Dynasytan® MTMS

## Methyltrimethoxysilane

### Technical data

Properties and test methods	Value	Unit	Method
Density (20 °C)	approx. 0.96	g/cm <sup>3</sup>	DIN 51757
Viscosity (20 °C)	approx. 0.5	mPa·s	DIN 53015
Flash point	approx. 9	°C	DIN 51755
Initial boiling point	approx. 102	°C	DIN 51751

### Registrations

#### Dynasytan® MTMS

EINECS/ELINCS (EU):	Yes
AICS (Australia):	Yes
DSL/NDSL (Canada):	Yes
PICCS (Philippines):	Yes
TSCA (USA):	Yes
IECS (P.R. China):	Yes
ENCS (Japan):	Yes
ECL (South Korea):	Yes

**Dynasytan®** MTMS, an alkyltrialkoxysilane is an important component in sol-gel systems.

**Dynasytan®** MTMS is a colorless, low-viscosity liquid.

**Dynasytan®** MTMS is regarded as trifunctional since all three alkoxy groups are able to hydrolyze. Additionally **Dynasytan®** MTMS contains a methyl group that adds organic character to the products. Hydrolysis leads to silanol groups which, in a subsequent condensation reaction, form very stable siloxane bonds (-Si-O-Si-). Condensation occurs parallel to hydrolysis once a certain amount of silanol groups have been formed. The absolute and relative rates of hydrolysis and condensation depend on a number of factors. The most important factors include pH, concentration, solvent, temperature and the catalyst.

### Safety and handling

Before considering the use of Dynasytan® products please read its Material Safety Data sheet (MSDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Material Safety Data Sheet is available after registration on our website [www.dynasytan.com](http://www.dynasytan.com) or upon request from your local representative, customer service or from Evonik Industries AG, Product Safety Department, E-MAIL [sds-im@evonik.com](mailto:sds-im@evonik.com).

### Packaging and storage

**Dynasytan®** MTMS are available in 25 kg, 190 kg and 900 kg drums/ containers. **Dynasytan®** MTMS must be stored with exclusion of moisture. In a sealed container, the product has a shelf-life of 12 months with no loss of quality.

## Properties and application

In some sol-gel applications **Dynasylan**<sup>®</sup> MTMS is partially hydrolyzed to form a preproduct that can be further crosslinked using temperature. This prehydrolysis often is done in conjunction with other organofunctional silanes (e.g. **Dynasylan**<sup>®</sup> GLYMO), silicic acid esters or even an aqueous silica sol. This preproduct can be modified even further by addition of organic resins or inorganic nanoparticles such as AEROSIL<sup>®</sup>. It is also possible to construct an inorganic/organic network by adding silanes containing organofunctional groups (e.g. aminopropyl groups) and organic resins and polymerizing using standard organic methods. This principle makes it possible to obtain more resistant coatings having a higher UV-stability than traditional organic coatings. This can also lead to more flame resistant materials than using traditional resins.

## Reactivity

**Dynasylan**<sup>®</sup> MTMS reacts faster with water than **Dynasylan**<sup>®</sup> MTES.

This information and all technical and other advice are based on Evonik's present knowledge and experience. However, Evonik assumes no liability for such information or advice, including the extent to which such information or advice may relate to third party intellectual property rights. Evonik reserves the right to make any changes to information or advice at any time, without prior or subsequent notice. EVONIK DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, AND SHALL HAVE NO LIABILITY FOR, MERCHANTABILITY OF THE PRODUCT OR ITS FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE), OR OTHERWISE. EVONIK SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. It is the customer's sole responsibility to arrange for inspection and testing of all products by qualified experts. Reference to trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used.

#### **Europe/Middle-East/Africa/RoW**

##### **Evonik Industries AG**

Inorganic Materials  
Rodenbacher Chaussee 4  
63457 Hanau-Wolfgang  
Germany  
PHONE +49 6181 59 13636  
FAX +49 6181 59 13737  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Degussa (SEA) Pte. Ltd.**

Inorganic Materials  
3 Internatioanl Business Park  
#07-18, Nordic European Centre  
Singapore 609927  
PHONE +65 6809 6830  
FAX +65 6809 6630  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Taiwan Ltd.**

Inorganic Materials  
Artist Construction Bldg.  
9F, No. 133  
Min Sheng East Road, Sec 3  
Taipei, 105 Taiwan, R.O.C.  
Taiwan  
PHONE +886 227 17 1242  
FAX +886 227 17 2106  
dynasytan@evonik.com  
www.dynasytan.com

#### **North America**

##### **Evonik Degussa Corporation**

Inorganic Materials  
P.O. Box 677  
299 Jefferson Road  
Parsippany, NJ 07054-0677  
USA  
PHONE (TOLL FREE) +1 800 237 67 45  
PHONE +1 973 929 8513  
FAX +1 973 929 8503  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Degussa (Shanghai) Co. Ltd.**

Inorganic Materials  
55, Chungdong Road  
Shanghai 201108  
P.R. China  
PHONE +86 21 6119 1053  
FAX +86 21 6119 1075  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Japan Co. Ltd**

Inorganic Materials  
12th Floor Monolith Building  
2-3-1, Nishi-Shinjuku-ku  
Tokyo 163-0912  
Japan  
PHONE +81 353 23 7300  
FAX +81 353 23 7399  
dynasytan@evonik.com  
www.dynasytan.com

#### **Latin America**

##### **Evonik Brasil Ltda.**

Inorganic Materials  
Alameda Campinas, 579  
01404-000 São Paulo-SP  
Brazil  
PHONE +55 11 3146 4123  
FAX +55 11 3146 4109  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Korea Ltd.**

Inorganic Materials  
94, Galsan 1-dong  
Bupyeong-gu  
Incheon, 403-081  
Korea  
PHONE +82 32 510 2433  
FAX +82 32 505 2510  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik India Pvt. Ltd.**

Inorganic Materials  
Krislon House  
Saki Vihar Road, Anderi (E)  
Mumbai - 400 072  
India  
PHONE +91 226 7238 800  
FAX +91 226 7238 811  
dynasytan@evonik.com  
www.dynasytan.com