

CODE 5899

Product Information

CALCIUM STEARATE GP POWDER HYDENSE®

Description Low bulk density, very fine, white powder.

| Properties | Test | <u>Specification</u> | Typical Property |
|------------|------------------------|----------------------------|------------------|
| | Assay (%CaO) | 9.4 -10.8% | 9.6% |
| | Free Fatty Acid (%) | 1.0% max. | 0.1% |
| | Moisture (%) | 3.5% max. | 2.9% |
| | Sieve US Std. 325 Mesh | 99.5% min. through | 99.7% |
| | Bulk Density | Report lb./ft ³ | 13 |

Features Calcium Stearate GP Powder is produced from a high quality, tallow derived fatty

acid for polymer and all applications requiring a finely divided calcium stearate

powder with good handling and feeding characteristics.

Performance The basic nature of Calcium Stearate makes it an effective acid scavenger for

polyvinyl chloride extrusion, polyolefin film extrusion and molding applications.

The very fine and consistent particle size distribution provides excellent dispersion properties in blending, compounding and extrusion equipment.

High surface area and fine particle size provides excellent lubrication and surface quality in reinforced thermoset and other molding applications and an excellent

anti-tack and mold release agent in rubber applications.

The hydrophobic nature of calcium stearate combined with the fine particle size and high surface area imparts excellent water repellency to concrete, mortar and

other masonry and construction materials.

Quality Control A modern, state-of-the-art plant process with strict control ensures consistent

quality in chemical and mechanical properties.

Regulatory Meets FDA requirements under 21 CFR for indirect food contact applications.

NSF Standard 14 listed ingredient for use in potable pipe.

Packaging Standard 60 x 25 lb. Kraft paper multiwall bags on stretch wrapped pallets and

bulk packaging in supersacks is available.

Storage Storage in dry areas at normal ambient temperatures is recommended. Open

containers of unused product should be firmly closed for storage.

TDS-5899 180321

NOTICE: Although the information and recommendations contained in this document (hereinafter "Information") are presented in good faith and believed to be correct at the date of their publication, BAERLOCHER makes no representations or warranties as to the completeness or accuracy of Information.

Information is supplied upon the condition that the persons or entities receiving same will make their own determination as to its suitability for their purposes prior to their use. In no event, will BAERLOCHER be responsible or liable for any loss of profits, lost goodwill, direct, special, indirect, incidental, or consequential damages of any nature whatsoever, including without limitation lost revenue, resulting from the use of or reliance upon Information or the product to which Information refers.

Nothing contained in this disclaimer is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent or intellectual property right, and BAERLOCHER makes no representation or warranty, express or implied, that the use thereof will not infringe any patent or intellectual property rights.

No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to Information or the product to which Information refers.

Baerlocher U.S.A. 5890 Highland Ridge Drive Cincinnati, OH 45232 Tel: toll-free 1-866-482-1700 Fax: toll-free 1-866-482-6344 Internet: http://www.baerlocher.com