



INKS & COATINGS

ROYALE BLACK[®] EI 98

PRODUCT PROFILE

EI 98 is a low surface area and medium structure black pigment. This pigment is having low sieve residue and offers very good dispersibility.

EI 98 is used in paints and coating application which demands bluer undertone. It can also be used for mass tone in water-based primer and coating application.

EI 98 carbon black offers very blue undertone and enables high loading.

The dispersion of EI 98 carbon black depends on the equipment used and the formulation.

TYPICAL VALUE

NSA m ² /g	STSA m ² /g	OAN CC/100g	Tint Strength % ITRB	Sieve Residue 325M, ppm	Heating Loss (As Shipped) %	Volatile %
34	34	92	65	20	0.6	1.7

APPLICATION FIELD

TYPICAL APPLICATION	RECOMMENDED DOSAGE
Coatings	5-10%
Water-based Primer	5-10%

- Recommended dosage can vary depending upon end use and modification of other ingredients
- Packaging - 20kg paper bags

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India

Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India

P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcblttd.com | E: pcbl.specialtyblack@rpsg.in

Issue - Apr. 2024

