



Product Data Sheet - Waxes

Additives

Ceridust® 8090 TP

Edition Date August 10, 2016 Edition Number 4

Renewable polymer wax

Product Description

Ceridust 8090 TP is a revolutionary bio-based additive for wood coatings

Benefits

- Natural wood touch surface
- Increased coefficient of friction
- Outstanding scratch resistance performance
- Structured surfaces possible
- Bio-based and sustainable raw material
- Suitable for water based formulations

Specifications

General Properties

Characteristics	Unit	Target Value	Test Method
Appearance		white micronized powder	QM-AA-634
Particle Size > 45 µm	[%]	~ 2	ISO 4610
Particle Size > 71 µm	[%]	0	ISO 4610

Applications

Ceridust 8090 TP is recommended for water based coatings. The nature of this Ceridust creates a smooth and soft touch surface like untreated wood and there is no compromise between wood touch and protection by a coating.

By adding the Ceridust 8090 TP you can influence the coefficient of friction with outstanding scratch resistance performance, especially in water based formulations.

Structured surfaces are possible to achieve with Ceridust 8090 TP.

Packaging and Handling

Delivery form

Micronized powder

Packaging

Paper bag 20 kg

Pallet 560 kg (28 bags)

Storage

For best shelf life store this product in a dry area at normal ambient temperatures. Minimum shelf life is 2 years from the date of shipping when properly stored.

EcoTain



PEOPLE



SAFE AND EFFICIENT TO USE

- Non hazardous

ADDRESSING MEGATRENDS AND SOCIAL TRENDS



- Best for water based, solvent free coatings



PLANET



RAW MATERIALS AND SUSTAINABLE SOURCING

- 100% renewable raw material, not food competing



PERFORMANCE



INTEGRATED SUSTAINABLE BUSINESS

- Cooperation with supplier on sustainable raw materials



PERFORMANCE ADVANTAGES

- Increased coefficient of friction and outstanding scratch resistance

Safety and MSDS

Hazards

The product does not require a hazard warning label according CLP regulation (Regulation (EC) No. 1272/2008, as amended). For further information please refer to the Material Safety Data Sheet.

www.clariant.com



Clariant International Ltd



This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Clariant makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Clariant's products for its particular application.

* Nothing included in this information waives any of Clariant's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing. Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing Clariant products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products. For additional information, please contact Clariant.

* For sales to customers located within the United States and Canada the following applies in addition: No express or implied warranty is made of the merchantability, suitability, fitness for a particular purpose or otherwise of any product or service.

© Trademark of Clariant registered in many countries.

® 2013 Clariant International Ltd