



PRODUCT DATA SHEET

PURETOL™ 22

TEST DESCRIPTION	METHOD	SPECIFICATIONS		TYPICAL
Product Code				PTL22
Specific Gravity at 25 °C	ASTM D4052	0.845	0.885	0.862
Kinematic Viscosity, cSt at 40 °C	ASTM D445	39.0	46.0	43.1
Saybolt Universal Viscosity at 100 °F	ASTM D2161	Report		220
Colour, Saybolt	ASTM D156	30		+30
Appearance, Visual	LORM 004	Clear & Bright		Clear & Bright
Flashpoint, C O C, °C	ASTM D92	210		220
Pour Point, °C	ASTM D5950		-9	-15
* Exp. Date, from Date of Manufacture*	3 YEARS		Pass	Pass
Readily Carbonizable Substances Test	USP/NF Curr Rev		Pass	Pass
Limit of Sulfur Compounds	USP/NF Curr Rev		Pass	Pass
Solid Paraffin	USP/NF Curr Rev		Pass	Pass
Limit of Polycyclic Aromatic Hydrocarbon	USP/NF Curr Rev		Pass	Pass
Acidity	USP/NF Curr Rev		Pass	Pass
Infrared Absorption	USP/NF Curr Rev		Pass	Pass

Date Issued: 7/31/2018

Date Reviewed: 7/14/2022

PURETOL™ 22 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA) 21 CFR 172.878 White Mineral Oil and 21 CFR 178.3620(a) Mineral Oil
- National Formulary (NF) Light Mineral Oil Monograph
- Certified Kosher (Passover)
- Certified Halal
- Certified Vegan
- Expiry Date, from Date of Manufacture is 3 years

Petro-Canada Lubricants Inc.

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

Tel: 1-844-388-2665

lubricants.petro-canada.com