



AN HF SINCLAIR BRAND

PURETOL™ 15

TEST DESCRIPTION	METHOD	SPECIFICATIONS		TYPICAL
		MIN	MAX	
Product Code				PTL15
Density, kg/l at 20 °C	ASTM D4052	Report		0.859
Specific Gravity at 25 °C	ASTM D4052	0.850	0.870	0.858
Kinematic Viscosity, cSt at 40 °C	ASTM D445	27.7	30.7	29.2
Kinematic Viscosity, cSt at 100 °C	ASTM D445	Report		5.17
Kinematic Viscosity, cSt at 20 °C	ASTM D445	Report		76.29
Saybolt Universal Viscosity at 100 °F	ASTM D2161	Report		150
Appearance, Visual	LORM 004	Clear & Bright		Clear & Bright
Colour, Saybolt	ASTM D156	30		+30
Pour Point, °C	ASTM D5950	Report		-15
Flashpoint, C O C, °C	ASTM D92	Report		> 185
* Exp. Date, from Date of Manufacture*	3 YEARS	Pass		Pass
Readily Carbonizable Substances Test	USP/NF Curr. Rev	Pass		Pass
Limit of Sulfur Compounds	USP/NF Curr. Rev	Pass		Pass
Solid Paraffin	USP/NF Curr. Rev	Pass		Pass
Limit of Polycyclic Aromatic Hydrocarbon	USP/NF Curr. Rev	Pass		Pass
Acidity	USP/NF Curr. Rev	Pass		Pass
Infrared Absorption	USP/NF Curr. Rev	Pass		Pass

Date Issued: 7/31/2018

Date Reviewed: 7/13/2021

PURETOL™ 15 meets the requirements of the following specifications:

- U.S. Food and Drug Administration (FDA) 21 CFR 172.878 White Mineral Oil and 21 CFR 178.3620(a) Mineral Oil
- National Formulary (NF) Light Mineral Oil Monograph
- Certified Kosher (Passover)
- Certified Halal
- Certified Vegan
- Expiry Date, from Date of Manufacture is 3 years