

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: EBECRYL® 8402 radiation curing resins
Synonyms: None
Product Description: Radiation curing resin
Molecular Formula: Mixture
Molecular Weight: Mixture
Intended/Recommended Use: Radiation curable coating ingredient, Coatings & Inks

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

For Product and all Non-Emergency Information call your local Allnex contact point or contact us at <http://www.allnex.com/contact>

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC)

See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ®, TM or * as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive Toxicant Hazard Category 1B
Skin Corrosion / Irritation Hazard Category 2
Serious Eye Damage / Eye Irritation Hazard Category 2A

LABEL ELEMENTS



Signal Word
DANGER

Hazard Statements

May damage fertility or the unborn child
Causes skin irritation
Causes serious eye irritation

Precautionary Statements

Obtain special instructions before use.
Wear protective gloves/protective clothing/eye protection/face protection.

Wash face, hands and any exposed skin thoroughly after handling.

IF exposed or concerned: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

Specific treatment (see supplemental first aid instructions on this label).

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

Contact with skin may cause a cross-allergic reaction in persons already sensitized to acrylates.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

| Component / CAS No. | % | GHS Classification |
|---------------------------------|----------|--|
| Dibutyltin dilaurate 77-58-7 | < 0.2 | Muta. 2 (H341) Repr. 1B (H360FD) STOT RE 1 (H372) STOT Single 1 (H370) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) |
| Acrylated resin - | 99 - 100 | Skin Irrit. 2 (H315) Eye Irrit. 2A (H319) |

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

First-aid Measures

Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

Skin Contact:

Remove contaminated clothing and shoes without delay. Wash immediately with plenty of water. Do not reuse contaminated clothing without laundering. Get medical attention if pain or irritation persists after washing or if signs and symptoms of overexposure appear.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects, Acute and Delayed

None known.

Immediate Medical Attention and Special Treatment

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Notes To Physician:

No specific measures have been identified.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray or fog, carbon dioxide or dry chemical.

Unsuitable Extinguishing Media:

full water jet.

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

Methods For Cleaning Up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

Environmental Precautions:

None known.

References to other sections:

See Sections 7, 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

Precautions: Wash hands thoroughly after handling. Wear protective gloves and eye/face protection.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct

sunlight.

Storage Temperature: Store at 4 - 40 °C

Reason: Quality.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure.

Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

Eye Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield. Eyewash equipment and safety shower should be provided in areas of potential exposure.

Skin Protection:

Avoid skin contact. Wear impermeable gloves and suitable protective clothing.

Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

Gloves for repeated or prolonged exposure - non exhaustive list:

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: up to 480 min

Gloves for short term exposure/splash protection - non exhaustive list:

Nitrile rubber (NBR), thickness: 0.1 mm, break through time: up to 30 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:

Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

Exposure Limit(s)

77-58-7

Dibutyltin dilaurate

| | |
|--------------|---|
| OSHA (PEL): | 0.1 mg/m ³ (TWA) |
| ACGIH (TLV): | 0.2 mg/m ³ Sn (STEL) (skin) |
| | 0.1 mg/m ³ Sn (TWA) |
| Other Value: | Not established |

Biological Exposure Limit(s)

No values have been established.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|----------------------------------|
| Color: | clear colorless to light straw |
| Appearance: | Clear to slightly hazy liquid. |
| Odor: | acrylate |
| Boiling Point: | > 100 °C |
| Melting Point: | Not available |
| Vapor Pressure: | 0.013 hPa @ 20 °C |
| Specific Gravity/Density: | 1.13 g/cm ³ |
| Vapor Density: | Not available |
| Percent Volatile (% by wt.): | < 0.5 % |
| pH: | Not available |
| Saturation In Air (% By Vol.): | Not available |
| Evaporation Rate: | Not applicable |
| Solubility In Water: | Not soluble, coagulates. |
| Volatile Organic Content: | Not available |
| Flash Point: | 220 °C 428 °F Cleveland Open Cup |
| Flammable Limits (% By Vol): | Not applicable |
| Autoignition Temperature: | Not available |
| Decomposition Temperature: | Not available |
| Partition coefficient (n-octanol/water): | Not available |
| Odor Threshold: | Not available |
| Viscosity (Kinematic): | Not available |
| Viscosity (Dynamic): | Viscous liquid |
| Flammability: | Normal combustion |
| Oxidizing Properties: | No |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------|---|
| Reactivity: | No information available |
| Stability: | Stable. |
| Conditions To Avoid: | Avoid exposure to strong UV sources. Avoid friction with temperature increase as result. Avoid direct contact with heat sources. Avoid temperature higher than 40°C. Avoid direct exposure to sunlight. Loss of dissolved air. Loss of polymerization inhibitor. |
| Polymerization: | May occur |
| Conditions To Avoid: | Hazardous polymerization can occur when exposed to direct sunlight. Hazardous exothermic polymerization can occur when heated. Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers Material should not be |

heated above 100°C due to polymerization.

Materials To Avoid:

Avoid free radical producing initiators.
 Avoid contact with peroxides.
 Avoid contact with strong oxidizing agents.
 Copper, copper alloys, carbon steel, iron and rust.
 They give an exothermic reaction with the product.
 Unintentional contact with them should be avoided.
 Hazardous polymerization may occur.

Hazardous Decomposition Products:

oxides of carbon
 Nitrous oxides (NOx)
 hydrocarbons

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin, Eyes, Oral.

Acute toxicity - oral: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - dermal: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Acute toxicity - inhalation: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Skin corrosion / irritation: Causes skin irritation

Serious eye damage / eye irritation: Causes serious eye irritation

Respiratory sensitization: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Skin sensitization: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Carcinogenicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Germ cell mutagenicity: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

Reproductive toxicity: May damage fertility or the unborn child

Specific target organ toxicity (STOT) - single exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

Aspiration hazard: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

PRODUCT TOXICITY INFORMATION

ACUTE TOXICITY DATA

| | | | | |
|------------|--------|------------|--------|----------------------|
| oral | rat | Acute LD50 | > 2000 | mg/kg |
| dermal | rabbit | Acute LD50 | > 2000 | mg/kg |
| inhalation | rat | Acute LC50 | 4 hr | > 5 mg/l (Dust/Mist) |

LOCAL EFFECTS ON SKIN AND EYE

| | | | |
|------------------|--------|--------|------------|
| Acute Irritation | dermal | rabbit | Irritating |
| Acute Irritation | eye | rabbit | Irritating |

ALLERGIC SENSITIZATION

| | | |
|---------------|------------|---------|
| Sensitization | Skin | No data |
| Sensitization | inhalation | No data |

GENOTOXICITY**Assays for Gene Mutations**

| | |
|-----------------------|---------|
| Ames Salmonella Assay | No data |
|-----------------------|---------|

OTHER INFORMATION

The product toxicity information above has been estimated.

Contact with skin may cause a cross-allergic reaction in persons already sensitized to acrylates.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

HAZARDOUS INGREDIENT TOXICITY DATA

Based on literature and actual test data, dibutyltin dilaurate (DBTL) has acute oral LD50 values ranging from less than 2000 to >2000 mg/kg. The acute dermal LD50 (rat) is >2000 mg/kg. Dibutyltin dilaurate (DBTL) may cause severe skin irritation. This substance may cause skin sensitization (allergic skin reactions). Repeated oral administration of DBTL has caused liver damage and death in animals. Neurotoxicity has also been observed in animals after oral exposure. DBTL may impair fertility, may cause harm to the unborn child and is suspected of causing genetic defects. Tumour formation was not observed in a 2-year chronic study conducted with mice and rats with a structural analogue. Organotin compounds are suspected of causing immunosuppressant effects.

The toxicological properties of acrylated resin have not been fully investigated. Direct contact with this material may cause moderate eye and skin irritation.

12. ECOLOGICAL INFORMATION**TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS**

The ecological assessment for this material is based on an evaluation of its components.

This material is not classified as dangerous for the environment.

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

| Component / CAS No. | Toxicity to Fish |
|--------------------------------|--|
| Dibutyltin dilaurate (77-58-7) | LC50 = 2 mg/L - <i>Oryzias latipes</i> (48h) LC50 = 3.1 mg/L - <i>Brachydanio rerio</i> (zebrafish) |
| Acrylated resin (-) | Not available |

| Component / CAS No. | Toxicity to Water Flea |
|--------------------------------|--|
| Dibutyltin dilaurate (77-58-7) | EC50 = 0.463 mg/L - <i>Daphnia magna</i> |
| Acrylated resin (-) | Not available |

| Component / CAS No. | Toxicity to Algae |
|--------------------------------|--|
| Dibutyltin dilaurate (77-58-7) | EC50 = 1 mg/L - <i>Scenedesmus subspicatus</i> (algae) |
| Acrylated resin (-) | Not available |

| Component / CAS No. | Partition coefficient |
|--------------------------------|-----------------------|
| Dibutyltin dilaurate (77-58-7) | Log Kow = 4.44 |
| Acrylated resin (-) | Not available |

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? Not applicable/Not regulated

TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

IMO

Dangerous Goods? Not applicable/Not regulated

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are designated as "Active" on the TSCA Inventory or are not required to be listed.

Canada: All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

European Economic Area (including EU): When purchased and shipped from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

Australia: All components of this product are included in the Australian Inventory of Industrial Chemicals (AIIC) or are not required to be listed on AIIC.

New Zealand: This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS and ISHL) inventories or are not required to be listed on the Japanese inventories.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory. When purchased from Allnex Korea or Chemart distributor this product is compliant with the ARECs (the Act on the Registration and Evaluation, etc. of Chemical Substances). All its components are either excluded, exempt, pre-notified and/or registered. When purchased from another allnex entity, please contact PSRA-KREACH@allnex.com to check the possibility to be covered by our Only Representative.

Philippines: All components of this product are either listed on the Philippine (PICCS) inventory, have been assessed by Environmental Management Bureau (EMB) or are exempt from notification requirements.

Taiwan: All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

Switzerland: All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 24-26).

Turkey: When purchased directly from Allnex by a Turkish legal entity, this product is compliant with the PRE-registration requirements of KKDİK as all its components are either pre-registered, excluded and/or exempt.

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA**Physical Hazards**

Not applicable

Health Hazards

Reproductive toxicity

Skin Corrosion or Irritation

Serious eye damage or eye irritation

16. OTHER INFORMATION**NFPA Hazard Rating (National Fire Protection Association)**

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

Reasons for Issue: Revised Section 1**Date Prepared:** 03/23/2021**Date of last significant revision:** 03/22/2021**Component - Hazard Statements**

Dibutyltin dilaurate

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H341 - Suspected of causing genetic defects.

H360FD - May damage fertility. May damage the unborn child.

H370 - Causes damage to organs.

H372 - Causes damage to organs through prolonged or repeated exposure.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

Acrylated resin

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Emergency phone numbers for other regions**Asia Pacific**

Australia: +61 1800 022 037 (Allnex Australia)

China (PRC): +86(0)532 8388 9090 (NRCC)

India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)

Indonesia: 007 803 011 0293 (Carechem 24)

Japan: +81 345 789 341 (Carechem 24)

Korea: +82 2 3479 8401 (Carechem 24)

Malaysia: +60 3 6207 4347 (Carechem 24)

New Zealand: +64 0800 803 002 (Allnex New Zealand)

Philippines: +63 2 231 2149 (Carechem 24)

Taiwan: +886 2 8793 3212 (Carechem 24)

Vietnam: +84 8 4458 2388 (Carechem 24)

All Others: +65 3158 1074 (Carechem 24)

Europe

+44 (0) 1235 239 670 (Carechem 24)

Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)

Chile: +56 2 2582 9336 (Carechem 24)

Mexico and all others: +52-555-004-8763 (Carechem 24)

Prepared By: Product Stewardship & Regulatory Affairs Department, <http://www.allnex.com/contact>

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.
