

Product Data Sheet - Waxes

Business Unit Additives

Edition 11.11.2013

Licowax PE 130 powder

High density polyethylene wax

Product-No.: 105234 **CAS-No.**: [9002-88-4] **Version**: 6

Product Description

High density polyethylene wax

Delivery specifications and (*) general properties

Characteristics	Unit	Target value	Test method	
Appearance		white powder	QM-AA-634	
Acid value	[mg KOH/g]	0	ISO 2114	
Saponification value	[mg KOH/g]	0	ISO 3681	
Drop point	[°C]	127 - 132	ASTM D 3954	
*Viscosity	[mPa·s]	~ 350	DIN 53019 at 140°C	
*Density (23°C)	[g/cm ³]	~ 0,97	ISO 1183	

Delivery form

Powder

The product is also available in further physical form(s)

Packaging

Polyethylene bag 20 kg Pallet 1000 kg (50 bags)

Storage

For best shelf life store this product in a dry area at normal ambient temperatures.

Minimum shelf life is 2 years from the date of shipping when properly stored

Main applications

Licowax PE 130 is an external lubricant especially for rigid PVC applications. It provides excellent anti-sticking properties to the PVC melt resulting in a smooth and glossy surface of the end article. Liowax PE 130 is also an internal lubricant for polyolefins providing flow improvement of PE compounds and can be used as a dispersing aid for polyolefin masterbatch application.

Another application for Licowax PE 130 is that it adjusts viscosity, open and set time in hotmelt adhesives.

It can also be used as a wax compound in printing inks to provide rub and scratch resistance as well as a slip modification additive.

Status under food legislation

EU: All components listed in Annex I, Table 1 of Commission Regulation (EU) No 10/2011 on plastic materials and articles intended to come into contact with food (no SML).

FDA: 21 CFR §§ 175.105, 175.300, 177.1520 (c) 2.1, 2.2, 2.3 (further notifications available).

Declarations regarding the requirements and specifications of several regulations and standards are available including: Directive 2011/65/EU (RoHS), CONEG's "toxics in packaging", EN 71-3 ("safety of toys – migration of certain elements"), Directive 94/62/EC

("packaging and packaging waste"). For further information please contact your Clariant representative.

Hazards

The product does not require a hazard warning label according to the German federal regulations of hazardous substances (GefStoffV). For further information please refer to the material safety data sheet.

Ecological and toxicological properties

Acute oral toxicity LD50: >2000 mg/kg (rat) Insoluble in water
No harmful effects to fish and bacteria.

For all specifications, deliveries and services the following applies: $\underline{\mbox{Disclaimer}}$

Clariant Web Site: http://www.clariant.com
Clariant Additives Web Site: http://additives.clariant.com