

Revision Number: 005.0

PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type/use:

Restriction of Use:

Company address:

Henkel Corporation

Rocky Hill, Connecticut 06067

One Henkel Way

BONDERITE L-GP 505 CORROSION INHIBITOR known as P3-PREVOX 505 Lubricant

1.

None identified

IDH number:

594827

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

# EMERGENCY OVERVIEW DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE AN ALLERGIC SKIN REACTION. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE INHALATION	2



**Precautionary Statements** 

Prevention:	Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective
	gloves, clothing, eve and face protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation or rash
Storage:	occurs: Get medical attention. Wash contaminated clothing before reuse. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3.	<b>COMPOSITION</b>	<b>INFORMATION ON</b>	INGREDIENTS
----	--------------------	-----------------------	-------------

Hazardous Component(s)	CAS Number	Percentage*
Triethanolamine	102-71-6	10 - 30

IDH number: 594827

Product name: BONDERITE L-GP 505 CORROSION INHIBITOR known as P3-PREVOX 505 Page 1 of 6

Monoethanolamine	141-43-5	10 - 30
Sodium 4(or 5)-methyl-1H-benzotriazolide	64665-57-2	1 - 5
Sodium EDTA	64-02-8	1 - 5
Diethanolamine	111-42-2	0.1 - 1
Alcohols, C6-10, ethoxylated propoxylated, fumarated, sodium salts~	102900-02-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FI	RST AID MEASURES
Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
Skin contact: For skin contact flush with large amounts of water. If symptoms develop a persist, get medical attention.	
Eye contact:	Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.
Ingestion:	If material is ingested, immediately contact a physician or poison control center. DO NOT induce vomiting unless directed to do so by medical personnel.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively.
5. FIRE	FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus. Wear full protective clothing.
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate personal protective equipment.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.
7.	HANDLING AND STORAGE
Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Provide adequate ventilation. Wash thoroughly after handling. Do not take internally. Do not mix this product with fluids which contain NITRITES/NITRATES. NITROSAMINE may be formed.
Storage:	For safe storage, store between 5.0 °C (41°F) and 38.0 °C (100.4 °F) Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Triethanolamine	5 mg/m3 TWA	None	None	None
Monoethanolamine	6 ppm STEL 3 ppm TWA	3 ppm (6 mg/m3) PEL	None	None
Sodium 4(or 5)-methyl-1H-benzotriazolide	None	None	None	None
Sodium EDTA	None	None	None	None
Distancianis	1 mg/m3 TWA Inhalable fraction and	Nega	Nega	News
Diethanolamine	vapor. (SKIN) Inhalable fraction and vapor.	None	None	None
Alcohols, C6-10, ethoxylated propoxylated, fumarated, sodium salts~	None	None	None	None

Engineering controls:

**Respiratory protection:** 

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided. When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known; or any other circumstances where air purifying respirators may not provide adequate protection.

Eye/face protection:

Skin protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. The breakthrough time of the selected glove must be greater than the intended use period. Suitable glove materials may include: Neoprene gloves. Nitrile gloves.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor. Odor threshold: pH: . Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Liquid Amber Mild amine Not available. 10.7 Not determined > 100 °C (> 212°F)calculated Not determined 1.05 - 1.09 Not determined Aqueous solution Not applicable Not applicable Not determined Not applicable Not available. Complete Not determined Not available. 100 - 300 mPa.s Not available.

# **10. STABILITY AND REACTIVITY**

Stability:	Stable at normal conditions.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Upon decomposition, this product may yield oxides of nitrogen and ammonia, carbon dioxide, carbon monoxide and other low molecular weight hydrocarbons.
Incompatible materials:	Monoethanolamine: reacts violently with acetic acid, acetic anhydride, acrolein, acrylic acid, acrylonitrile, chlorosulfonic acid, epichlorohydrin, hydrochloric acid, hydrofluoric acid, sulfuric acid, mesityle oxide, nitric acid, oleum, b-propiolactone and vinyl acetate. Do not mix this product with nitrites or other nitrosating agents because a carcinogenic nitrosamine may be formed.
Reactivity:	This product may react with strong acids or oxidizing agents.
Conditions to avoid:	Freezing conditions. Store away from incompatible materials.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns.
Skin contact:	This product is severely irritating to the skin and may cause burns. May cause skin sensitization.
Eye contact:	This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion:	Ingestion causes burns of the upper digestive and respiratory tracts.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Triethanolamine	Oral LD50 (Rat) = 8.0 g/kg Dermal LD50 (Rabbit) = > 20,000 mg/kg	Irritant, Allergen	
Monoethanolamine	Oral LD50 (Rat) = 10.2 g/kg Oral LD50 (Mouse) = 700 mg/kg Dermal LD50 (Rabbit) = 1,025 mg/kg	Irritant, Kidney, Liver, Corrosive, Respiratory, Developmental	
Sodium 4(or 5)-methyl-1H-benzotriazolide	None	Irritant	
Sodium EDTA	Oral LD50 (Rat) = > 2,000 mg/kg	Irritant	
Diethanolamine	Oral LD50 (Rat) = 710 mg/kg Oral LD50 (Rat) = 1.82 g/kg	Allergen, Corrosive, Irritant, Liver, Respiratory	
Alcohols, C6-10, ethoxylated propoxylated, fumarated, sodium salts~	None	No Records	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Triethanolamine	No	No	No
Monoethanolamine	No	No	No
Sodium 4(or 5)-methyl-1H-benzotriazolide	No	No	No
Sodium EDTA	No	No	No
Diethanolamine	No	Group 2B	No
Alcohols, C6-10, ethoxylated propoxylated, fumarated, sodium salts~	No	No	No

# **12. ECOLOGICAL INFORMATION**

Ecological information:

Do not empty into drains / surface water / ground water.

#### Information provided is for unused product only. Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. This product contains a chelating agent. **TRANSPORT INFORMATION** 14. The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration. U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Ethanolamine solutions Hazard class or division: 8 Identification number: UN 2491 Packing group: ш International Air Transportation (ICAO/IATA) Proper shipping name: Ethanolamine solution Hazard class or division: 8 Identification number: UN 2491 Packing group: ш Water Transportation (IMO/IMDG) Proper shipping name: ETHANOLAMINE SOLUTION Hazard class or division: 8 Identification number: UN 2491 Packing group: ш 15. **REGULATORY INFORMATION United States Regulatory Information**

**13. DISPOSAL CONSIDERATIONS** 

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	One or more components are not listed on, and are not exempt from listing on either the

#### **16. OTHER INFORMATION**

Domestic Substances List or the Non-Domestic Substances List.

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date:

09/01/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.