

DESCRIPTION

SURFYNOL® AD 01 is multi-functional gemini surfactant combining dynamic wetting and molecular defoaming. SURFYNOL® AD 01 also acts as a coalescing aid.

KEY BENEFITS

- excellent dynamic wetting
- reduction of MFFT for low-VOC formulations
- fast knock-down defoaming and outstanding foam control

EFFECT**Substrate wetting****Anti-crater effect****Flow promotion****Defoaming****Reduction of static surface tension****Reduction of dynamic surface tension****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing****pigmented coatings****clear coatings**

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Printing Inks
- Wood coatings
- Car OEM coatings
- Architectural paints

TECHNICAL DATA

active matter content	100 %
appearance	clear colored liquid
chemical description	organic gemini surfactant
solvent	-

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

PROCESSING INSTRUCTIONS

- Can be introduced in the grind and let-down stage.
- Addition to the coating as supplied or as a predilution is possible.

HANDLING & STORAGE

Keep containers tightly closed in a dry, cool, and well-ventilated place. Mix thoroughly before use. Product is normally freeze-thaw stable but may separate as a result of standing or freezing. If the product has frozen or become thick due to storage in colder temperatures, warm to 40 °C and mix thoroughly before use.

MSDS & REGULATORY INFORMATION

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Resource Efficiency GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com