



EBECRYL® 740/40 TP radiation curing resins

Acrylic resin

GHS Labeling

Signal Word

WARNING

Hazard Statements

May cause respiratory irritation

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

Allnex Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

Precautionary Statements

Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local and national regulations.

CA Prop65 Label Compliance Method and Statement:

SAFE HARBOR LANGUAGE



WARNING: Reproductive Harm – www.P65Warnings.ca.gov

GHS Symbols (if required):



Trademarks indicated with ® , TM or * as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

Right-to-know data for CAS No. / Component

Before handling this material, read Safety Data Sheet # 0018384 for more detailed safety, health and environmental data.

The following components of this product are listed in accordance with right-to-know laws:

Component / CAS No.

Tripropylene glycol diacrylate	42978-66-5
--------------------------------	------------

NJTSRN: 371705164000-6288

Standard Packaging Statements:

Drums:

ATTENTION - Container headspace may contain hazardous gas or vapor. Open container with care, using adequate ventilation and avoiding ignition sources. Do not use air pressure or apply heat with open flame to remove contents of container. After emptied, container may retain solid, liquid, and/or vapor residues. Continue to observe all precautions, if any, on label. Do not cut, puncture, torch, or weld on or near emptied container. Do not use for other purposes.

Bags:

ATTENTION - After emptying, bag may retain solid, liquid, and/or vapor residues. Continue to observe all precautions, if any, on label. Do not cut, puncture, torch, or weld on or near emptied container. Do not use for other purposes.

Tank car/truck (bulk):

ATTENTION - Container headspace may contain hazardous gas or vapor. Open container with care, using adequate ventilation and avoiding ignition sources. DO NOT REMOVE TAG UNTIL TANK IS CLEANED.

Cylinders:

ATTENTION - Cylinder contains gas or liquid under pressure. Using equipment rated for cylinder pressure, open valves slowly with care, using adequate ventilation and avoiding ignition sources. When cylinder is empty and disconnected, ensure threaded plugs are properly inserted in valve openings as the cylinder will contain residues. Continue to observe all precautions on label. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Do not cut, puncture, torch, or weld on or near emptied cylinder. Do not use for other purposes.

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA; Telephone: 800-433-2873; Emergency Telephone (Carechem 24 - Allnex29003-NCEC): +1-215-207-0061 or +1-866-928-0789

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident

call:

Asia Pacific:

Australia: +61 1800 022 037 (Allnex Australia)
China (PRC): +86(0)532-8388-9090 (NRCC)
Japan: +81 345 789 341 (Carechem 24)
New Zealand: +64 0800 803 002 (Allnex New Zealand)
India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)
Korea: +82 2 3479 8401 (Carechem 24)
Malaysia: +60 3 6207 4347 (Carechem 24)
Philippines: +63 2 231 2149 (Carechem 24)
Vietnam: +84 8 4458 2388 (Carechem 24)
All Others: +65 3158 1074 (Carechem 24)

Europe/Africa/Middle East (Carechem 24):

Europe, Middle East, Africa, Israel: +44 (0) 1235 239 670
Middle East, Africa (Arabic speaking countries): +44 (0) 1235 239 671

Latin America:

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)
Chile: +56 2 2582 9336 (Carechem 24)
Mexico and all others: +52-555-004-8763 (Carechem 24)

Canada and USA (Carechem 24 - Allnex29003-NCEC): +1-866-928-0789 (toll free) or +1-215-207-0061

Flash Point: > 100 °C

NSF (National Sanitation Foundation)

NSF Statements/Maximum Usage:

Not applicable/Not approved

Dangerous Goods Transport Classification - only incorporate on product label if needed.

US DOT

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9

Packing Group: III

UN/ID Number: UN3082


Transport Label Required: Miscellaneous
Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): TRIPROPYLENE GLYCOL DIACRYLATE


Comments:

Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.





Non-Bordered Black Diamond Holder



Graphic for the Temperature & Frost Sensitive statement:

SPECIAL PRECAUTIONS FOR USER Protect against external heat sources above +40°C/104°F.

Precautionary Measures: Avoid contact with eyes, skin and clothing.
Avoid breathing vapor.
Use with adequate ventilation.
Keep container closed.
Wash thoroughly after handling.

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.