TEGO® Flow 380

DESCRIPTION

TEGO* Flow 380 is a silicone-free acrylic leveling agent and shows good compatibility and flow promotion with additional anti-popping properties. It is highly recommended for solventborne coatings, especially clear coatings.

KEY BENEFITS

- excellent leveling
- good compatibility
- recoatable

EFFECT		
Anti-crater effect		
Flow promotion		
Slip effect		
Anti-blocking		
Low foam		

vaterborne	solventborne
	•
-pack 100%	radiation-curing
	•
igmented coatings	clear coatings
)	•

TYPICAL APPLICATIONS

- Car OEM coatings
- Car repair coatings
- General industrial coatings

TECHNICAL DATA	
active matter content	100 %
appearance	clear, yellow liquid
chemical description	organic polymer, silicone-free

Water	Ethanol
0	•
TPGDA	Acetone
	•
Butylacetate	Mineral Spirits
	•

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.2 - 0.7 wt-%

PROCESSING INSTRUCTIONS

- Addition as supplied or as a predilution is possible.
- Easy to incorporate.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of $48\ months$ from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried on only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com

