

## **MODULAST™ PUR Modifier**

CAS No. 27138-31-4 TECHNICAL DATA SHEET

# **MODULAST**<sup>™</sup> **PUR Product Description**

MODULAST PUR is a **newly developed**, **high purity modifier** designed primarily for use in reactive polyurethane systems, featuring the **lowest residual hydroxyl levels available on the market**. MODULAST PUR aids the polyurethane formulator by coupling unexpected properties—softness and strength—while providing exceptional compatibility and very low color development and odor.

While MODULAST PUR helps impart softness to polyurethanes, it does so with less efficiency than traditional dibenzoates such as MODULAST CLS. Combined with its high compatibility, this means that MODULAST PUR can be utilized at higher loading levels to achieve equal softness, providing the opportunity to optimize the overall cost of a polyurethane formulation.

## **Specifications**

Acidity, as benzoic acid, maximum, %	0.1
	98.0
	50
	2
	0.07
Typical Properties	
Assay, as benzoate ester, %	>98
Acidity, as benzoic acid, %	0.03
Boiling point, 5 mmHg, °C	205
Boiling point, 760 mmHg (extrapolated), °C	343
Color, APHA	
Density, ASTM D1475, 25°C, lbs/gal	9.6
Flash point, ASTM D92, °C	215
Freeze point, °C	<-20
Glass point, by DSC, °C	51
Hydroxyl number, mg KOH/g	1.8
Moisture content, %	
Refractive index, 25°C	
Solubility, in water, %	0.3
Solubility, water in, %	0.1
Solubility parameter, Small's, Hildebrands	
Specific gravity (density, g/mL), 25/25°C	
Surface tension, ASTM D1331, 25°C, dynes/cm	
Vapor pressure, 25°C (extrapolated), mmHg	
Viscosity, Brookfield RVT, 20 RPMs at 25°C, cPs and mPa⋅s	
VOC, ASTM D2369, %	0.9



### MODULAST™ PUR Modifier TECHNICAL DATA SHEET

## **Regulatory Information**

### **FDA CFR Listings**

 21 CFR 175.105 – Adhesives (PART 175 – INDIRECT FOOD ADDITIVES: ADHESIVES AND COMPONENTS OF COATINGS, Subpart B – Substances for Use Only as Components of Adhesives).

Emerald Performance Materials does not warrant that these product(s) are suitable under applicable food additive / food contact regulations of any potential use. The responsibility for determining the overall compliance with applicable food additive / food contact laws and regulations is with the company manufacturing the final consumer product and/or the person placing the products described herein in contact with food. This information is provided in good faith and is believed accurate as of the date of this letter. No warranty is subsequently expressed or implied. Liability is expressly disclaimed.

#### **Global Inventories**

Kalama® VITROFLEX®, K-FLEX®, and MODULAST™ products are included on or exempted from many global inventories. Please reference the product safety data sheet (SDS) for current global inventory status and other regulatory information. Current SDS's can be found on our website at www.emeraldkalama.com or can be requested from product.compliance@emeraldmaterials.com.

### **Contact Us**

#### **Americas**

1499 SE Tech Center PI, Ste 300, Vancouver, WA 800.223.0035 / +1.360.954.7100/ Fax +1.360.954.7201 KFLEX@emeraldmaterials.com

#### **Asia Pacific**

Rm 1708-09 Shui On Centre 6-8 Harbour Rd., Wanchai, Hong Kong +852 25987807 / FAX +852 25981909 KFLEX.asia@emeraldmaterials.com

#### Europe, Middle East, Africa

Fascinatio Boulevard 200-232 3065 WB Rotterdam, The Netherlands +31.88.888.0500 KFLEX.emea@emeraldmaterials.com

Today's toughest, highest performing adhesives, coatings, sealants, and vinyl rely on Emerald's innovative portfolio of industrial specialties. A wide range of non-phthalate plasticizers, low-VOC coalescents, modifiers, synthesis intermediates, and more deliver critical performance characteristics, such as durability and flexibility. Emerald's industrial chemistries are strategically optimized to provide the best value to manufacturers, while also allowing them to meet regulatory requirements and consumer demand for products with excellent health and safety profiles.

#### Global Service through our Regional Distribution Partners www.emeraldkalama.com

The information contained herein is believed to be reliable; however, it is based upon laboratory work with small scale equipment and does not necessarily indicate end-product performance. Because of variations in methods, conditions and equipment used commercially in processing these materials, Emerald makes no representations, warranties or guarantees, express or implied, as to the suitability of the products for particular applications, including those disclosed, or the results to be obtained. Full-scale testing and end-product performance are the responsibility of the user. Emerald Performance Materials shall not be liable for and the customer assumes all risk and liability for use and handling of any materials beyond Emerald's direct control. Nothing contained herein is to be considered as permission, recommendation nor as inducement to practice any patented invention without permission of the patent owner.