

Product information

SPHERILEX® DP-0115

Silicon Dioxide

Characteristic physico-chemical data*

Properties and test methods	Unit	Value
Median particle size	μ m	13.5
Particle Size d95	μ m	25
Speficif Gravity	g/cc	2.2
Linseed Oil Absorption	ml/100g	40
BET Surface Area	m²/g	< 15
Sodium Slufate Content	%	< 1
рН	5 %	7.5
Refractive Index		1.46

*) The given data are typical values. Specifications on request.

Certifications and Classifications

SPHERILEX® DP-0115

CAS-No. 112926-00-8

Quality excellence achieved through GMPs and ISO:9001 certifications

SPHERILEX® DP-0115 synthetic amorphous Silicon Dioxide has a unique spherical particle shape that allows for outstanding burnish and abrasion resistance as very well as very low binder demand. SPHERILEX® DP-0115 Silicon Dioxide has the largest particle size within the SPHERILEX® Silicon Dioxide family, which benefits both abrasion resistance and matting efficiency. The uniquely narrow particle size distribution and absence of oversized particles allows larger particle size of SPHERILEX® DP-0115 Silicon Dioxide to be used even in systems with particle size limitations, while providing a smooth pleasing feel to the coating film.

Benefits

- Maximum burnish and abrasion resistance
- Outstanding scrub resistance
- Large particle size for enhanced matting
- Excellent clarity and color in deep tints
- Low binder demand and low visvosity at high loadings
- Low abrasive character for improved metal marking and low dirt pick-up

Safety and Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Evonik Operations, Product Safety Department, E-MAIL sds-im@evonik.com We recommend to read carefully the safety data sheet prior to the use of our product.

Packaging and storage

For details regarding our packaging options for this product, please contact your local sales representative. Our silica products are inert and extremely stable chemically. However, due to their high specific surface area, they can absorb moisture and volatile organic compounds from the surrounding atmosphere. Therefore, we recommend storing the products in sealed containers in a dry, cool place, and removed from volatile organic substances. Even if a product is stored under these conditions, after a longer period it can still pick up ambient moisture over time, which could lead to its exceeding the specified moisture content. For this reason, our recommended use-by date is 24 months after date of manufacture. Product more than 24 months old should be tested for moisture content before use in order to make certain that it is still suitable for the intended application.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Applied Technology Evonik Operations GmbH

Business Line Silica Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany PHONE +49 6181 59-3536 FAX +49 6181 59-4096 ask-si@evonik.com www.silica-specialist.com

Europe/ Middle-East/ Africa/ Latin America Evonik Operations GmbH

Business Line Silica Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany PHONE +49 6181 59-8118 FAX +49 6181 59-78118 ask-si@evonik.com www.silica-specialist.com

North America Evonik Corporation

Business Line Silica 299 Jefferson Road Parsippany, NJ 07054-0677 USA PHONE +1 800 233-8052 FAX +1 973 929-8502 ask-si@evonik.com www.silica-specialist.com

Asia-Pacific Evonik (SEA) Pte. Ltd.

Business Line Silica
3 International Business Park
#07-18, Nordic European Centre
Singapore 609927
PHONE +65 6 809 6877
FAX +65 6 809 6677
ask-si-asia@evonik.com
www.silica-specialist.com

