

EUROPRENE[®] SIS

SOL T 9242 Styrene - Isoprene Block Copolymer

Europrene[®] SOL T 9242 is a linear block copolymer obtained by anionic polymerisation. The polymer is based on styrene and isoprene, where bound styrene content is 24 % wt and diblock content is 68 %. A non-staining, TNPP free antioxidant system is added during the production process.

Properties	Test Method	Unit	Typical Value
Specific gravity	ASTM D 792	g/cc	0,92
Hardness ¹⁾	ASTM D 2240	Sh A	35
Melt Flow Index	ASTM D 1238	g/10 min	20,0 (190°C, 5 Kg)
Brookfield Viscosity	ASTM D 1084	Pa .s	NA (Toluene sol., 25% wt)

1) Measured on ASTM D 4703 compression molded specimens

Key Features

Europrene[®] SOL T 9242 is a block copolymer with linear molecular structure and very high diblock content, designed for hot melt pressure sensitive applications where excellent tack performance, combined with softness and low viscosity, are required.

Main Applications

Hot-melt pressure sensitive adhesives for labels

Physical Form

The product is supplied from Ravenna Plant (Italy) in pellet form

Packaging

Available in bags on pallet or big bags. For detailed information, please refer to your versalis representative

Storage Conditions

Store the preparation in a covered place in sealed packaging, away from sunlight and heat sources. Ensure the proper ventilation in all storage areas.

Shelf life : 18 months

Please consult the relevant safety data sheet for more detailed information.

The information and data presented herein are to the best of our knowledge true and accurate, but no warranty or guarantee, expressed or implied, is made nor is any liability accepted with respect to the use of such information and data.