## **DRY - #1 Castor Oil**

## **Technical Data Sheet**



## Product Identification

DRY-#1 Castor Oil is a Technical Grade Castor Oil having very low moisture content, 0.02% maximum. The low moisture content makes this product ideal for lubricant or polyurethane applications where low moisture is required.

	<u>Property</u>	<u>Value</u>
Physical Properties	Composition	Approximately, 90% Triglyceride of Ricinoleic Acid
-	Molecular Weight	928
	Form	Clear to slightly hazy liquid
	Acid Value	1
	Color, Gardner	1+
	Density, lbs./gal, 25°C	7.98
	Fire Point, COC, °F	605
	Flash Point, COC, °F	555
	Hydroxyl Value	164
	lodine Value	86
	Moisture Content, %	0.01
	Pour Point, °F	-10
	Refractive Index	1.4775
	Saponification Value	180
	Specific Gravity, 25°C/25°C	0.959
	Viscosity, 25°C, Stokes	7.3
• Polyurethane Systems		
	<ul> <li>Lubricants</li> </ul>	
	Chemical Intermediates	
	<ul> <li>Insoluble in water</li> </ul>	
	<ul> <li>Soluble in alcohols (hydrocarbons</li> </ul>	not), esters, ethers, ketones and aromatic
Partially soluble in aliphatic hydrocarbons		atic hydrocarbons

For toxicity or regulatory information please consult the Material Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA

USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com

Web: www.vertellus.com