

# CARPOL® PEG-400 Polyethylene Glycol

CARPOL® PEG-400 is a polyol that is functionally 100% active. It is a clear, odorless, viscous liquid. The two primary hydroxyl groups of the polyethylene glycol can undergo typical alcohol reactions to form monoesters, diesters, ethers, and acetals. CARPOL® PEG-400 is hydrophilic and is soluble in water, acetone, alcohols, glycols, and aromatic hydrocarbons.

## **Typical End Use Applications**

Alkyd Resins

Rubber

Textile and Leather

Printing

Paper

Paints and Coatings

Typical Analytical Pr	operties*
-----------------------	-----------

Hydroxyl Number (mg KOH / g) 281

pH (10 parts of IPA: 6 parts of H<sub>2</sub>O) 6.0

Moisture (%) [maximum] 0.1

Color (APHA) [maximum] 35

Appearance Free & Clear

Average Molecular Weight (Da) 380-420

Density @ 25 °C (lb / gal) 9.38

## **Storage Information**

CARPOL® PEG-400 will absorb water if the product container is not secured properly. This may affect reactivity, appearance, and performance. Therefore, it is advised that all receptacles containing this material be tightly fastened and stored in a dry place. Consult the Safety Data Sheet for additional information.

### **Health and Safety Information**

Health and safety information is available in the form of a Safety Data Sheet. This literature, describing proper precautions and personal protective gear, is available for review. To receive this information, please contact a Carpenter Co. representative.

### **Ordering and Shipping Options**

Carpenter Co. offers different shipping options. Please contact your sales representative for details.

For additional information please contact:
Carpenter Co.
Chemicals Division

Customer Service 800-260-5373 5016 Monument Avenue Richmond VA 23230

Important: The information contained in this product data sheet is offered for your consideration, investigation, and verification. The data is presented in good faith and is believed to be reliable. Carpenter, however, makes no representation as to the completeness or accuracy. Carpenter makes no warranty, express or implied, with respect to the data contained herein. Carpenter cannot anticipate all conditions under which this data and the product may be used. The conditions of handling, storage, use, and disposal of the product are beyond Carpenter's control. Thus we expressly disclaim responsibility or liability for any loss, damage, or expense arising out of reliance on the information contained herein. You are advised to make your own determination as to safety, suitability, and appropriate manner of handling, storage, use, and disposal. For further information please consult the appropriate Carpenter Safety Data Sheet. Warning: These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

<sup>\*</sup>Please note that these values are not specifications
Updated October 2020