

SDS: 0018405

Date Prepared: 06/02/2021

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: EBECRYL® 8301 R radiation curing resins

Synonyms: None

Product Description: Acrylate modified polyurethane resin

Molecular Formula: Mixture **Molecular Weight:** Mixture

Intended/Recommended Use: Radiation curable coating ingredient

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

For Product and all Non-Emergency Information call your local Allnex contact point or contact us at http://www.allnex.com/contact

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC) See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ®, TM or * as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive Toxicant Hazard Category 1B Acute Toxicity (Oral) Hazard Category 4 Skin Corrosion / Irritation Hazard Category 2 Serious Eye Damage / Eye Irritation Hazard Category 1 Skin Sensitizer Hazard Category 1B Aquatic Environment Acute Hazard Category 2 Aquatic Environment Chronic Hazard Category 2

LABEL ELEMENTS



Signal Word DANGER

Hazard Statements

May damage fertility or the unborn child Harmful if swallowed Causes skin irritation SDS: 0018405

Date Prepared: 06/02/2021

Causes serious eye damage

May cause an allergic skin reaction

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

Precautionary Statements

Obtain special instructions before use.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Rinse mouth.

IF ON SKIN: Wash with plenty of soap and water.

Specific treatment (see supplemental first aid instructions on this label).

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Store locked up.

Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification
Dibutyltin dilaurate	< 0.15	Muta. 2 (H341)
77-58-7		Repr. 1B (H360FD)
		STOT RE 1 (H372)
		STOT Single 1 (H370)
		Skin Corr. 1C (H314)
		Eye Dam. 1 (H318)
		Skin Sens. 1B (H317)
		Aquatic Acute 1 (H400)
		Aquatic Chronic 1 (H410)
Polyurethane resin	30 - 40	Eye Irrit. 2A (H319)
-		
Acrylated esters	60 - 70	Acute Tox. 4 (H302)
-		Skin Irrit. 2 (H315)
		Eye Dam. 1 (H318)
		Skin Sens. 1B (H317)
		Aquatic Acute 2 (H401)
		Aquatic Chronic 2 (H411)

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

First-aid Measures

Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. Apply artificial respiration if patient is not breathing. Obtain medical attention immediately.

Skin Contact:

Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

Date Prepared: 06/02/2021

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical attention immediately.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects, Acute and Delayed

None known.

Immediate Medical Attention and Special Treatment

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Notes To Physician:

No specific measures have been identified.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray or fog, carbon dioxide or dry chemical.

Unsuitable Extinguishing Media:

high pressure water jet.

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

Methods For Cleaning Up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

Environmental Precautions:

Use appropriate containment to avoid environmental contamination. Avoid release to the environment.

References to other sections:

See Sections 7, 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

Precautions: Avoid release to the environment. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and eye/face protection.

Special Handling Statements: Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Prevent unauthorised access. Storage in stainless steel, amber glass, amber polyethylene or baked phenolic lined container.

Storage Temperature: Store at 4 - 40 °C 39.2 - 104 °F

Reason: Safety.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Utilize a closed system process where feasible. Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

Eye Protection:

Prevent eye and skin contact. Provide eye wash fountain and safety shower in close proximity to points of potential exposure. Wear eye/face protection such as chemical splash proof goggles or face shield.

Skin Protection:

Prevent contamination of skin or clothing when removing protective equipment. Barrier creams may be used in conjunction with the gloves to provide additional skin protection. Wear impermeable gloves and suitable protective clothing.

Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

Gloves for repeated or prolonged exposure - non exhaustive list:

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: up to 480 min

Gloves for short term exposure/splash protection - non exhaustive list:

Nitrile rubber (NBR), thickness: 0.1 mm, break through time: up to 30 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

Not suitable gloves - non exhaustive list:

Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

Exposure Limit(s)

77-58-7 Dibutyltin dilaurate

OSHA (PEL): 0.1 mg/m³ (TWA) ACGIH (TLV): 0.2 mg/m³ Sn (STEL)

(skin)

 $0.1 \text{ mg/m}^3 \text{ Sn (TWA)}$

Other Value: Not established

Biological Exposure Limit(s)

No values have been established.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color: clear pale yellow Appearance: liquid resin acrylate Soiling Point: > 100 °C Melting Point: Not available

Vapor Pressure: 0.013 hPa @ 20 °C

Specific Gravity/Density:

Vapor Density:

Percent Volatile (% by wt.):

pH:

Saturation In Air (% By Vol.):

Evaporation Rate:

Solubility In Water:

1.16 g/cm³

Not available

Not available

Not available

Slightly soluble

Flash Point: Non Flammable (polymerized at 196 °C) Cleveland Open Cup

Not available

Flammable Limits (% By Vol):
Autoignition Temperature:
Decomposition Temperature:
Partition coefficient

Not available
Not available
Not available

(n-octanol/water):

Volatile Organic Content:

Odor Threshold: Not available Viscosity (Kinematic): Not applicable

Page 6 of 12

Viscosity (Dynamic): 150 - 550 mPa.s @ 65.5 °C

Flammability: Not available Oxidizing Properties: Not available

SDS: 0018405

10. STABILITY AND REACTIVITY

Reactivity: No information available

Stability: Stable.

Conditions To Avoid: Avoid direct exposure to sunlight. Avoid temperatures higher than 60°C. Avoid

friction with temperature increase as result. Avoid exposure to strong UV sources. Loss of dissolved air. Loss of polymerization inhibitor. Avoid direct contact with

heat sources.

Polymerization: May occur

Conditions To Avoid: Uncontrolled polymerization may cause rapid evolution of heat and increase in

pressure that could result in violent rupture of sealed storage vessels or containers Hazardous polymerization can occur when exposed to direct sunlight. Hazardous

exothermic polymerization can occur when heated.

Materials To Avoid: Avoid contact with peroxides.

Avoid free radical producing initiators. Avoid contact with reactive metals.

Contact with alkalis.

They give an exothermic reaction with the product. Unintentional contact with them should be avoided.

Hazardous Decomposition

Products:

oxides of carbon hydrocarbons

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin, Eyes, Oral.

Acute toxicity - oral: Harmful if swallowed

Acute toxicity - dermal: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Acute toxicity - inhalation: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Skin corrosion / irritation: Causes skin irritation

Serious eye damage / eye irritation: Causes serious eye damage

Respiratory sensitization: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Skin sensitization: May cause an allergic skin reaction

Carcinogenicity: Not Classified - Based on available data and/or professional judgment, the classification

criteria are not met.

Germ cell mutagenicity: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

Reproductive toxicity: May damage fertility or the unborn child

Specific target organ toxicity (STOT) - single exposure: Not Classified. - Based on available data and/or

professional judgment, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure: Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

SDS: 0018405

Aspiration hazard: Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

PRODUCT TOXICITY INFORMATION

ACUTE TOXICITY DATA

oral rat Acute LD50 ~ 800 mg/kg dermal rabbit Acute LD50 > 2000 mg/kg inhalation Acute LC50 4 hr > 5 mg/l (Dust/Mist) rat

LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation dermal rabbit Irritating

Acute Irritation rabbit Causes serious damage eye

ALLERGIC SENSITIZATION

Sensitization Sensitizing dermal guinea pig

Sensitization No data respiratory

GENOTOXICITY

Assays for Gene Mutations

Ames Salmonella Assay Negative

OTHER INFORMATION

The product toxicity information above has been estimated.

The toxicological properties of this material have not been fully determined.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

HAZARDOUS INGREDIENT TOXICITY DATA

Based on literature and actual test data, dibutyltin dilaurate (DBTL) has acute oral LD50 values ranging from less than 2000 to >2000 mg/kg. The acute dermal LD50 (rat) is >2000 mg/kg. Dibutyltin dilaurate (DBTL) may cause severe skin irritation. This substance may cause skin sensitization (allergic skin reactions). Repeated oral administration of DBTL has caused liver damage and death in animals. Neurotoxicity has also been observed in animals after oral exposure. DBTL may impair fertility, may cause harm to the unborn child and is suspected of causing genetic defects. Tumour formation was not observed in a 2-year chronic study conducted with mice and rats with a structural analogue. Organotin compounds are suspected of causing immunosuppressant effects.

The toxicological properties of acrylated resin have not been fully investigated. Direct contact with this material may cause moderate eye irritation.

Acrylated esters has acute oral (rat) and dermal (rabbit) LD50 values of 540-1350 mg/kg and 4600 mg/kg, respectively. This material may cause moderate skin irritation and severe eve irritation. Acrylated esters may cause skin sensitization. This material was not mutagenic in the Ames Salmonella Assay and not mutagenic in the mammalian forward gene mutation test (HPRT). The outcome for chromosomal damage in the mouse Micronucleus Assay was also negative. A prenatal study in rabbits has not shown any adverse effects with regard to developmental toxicity. Carcinogenicity has not been investigated.



MARNING: Reproductive Harm – www.P65Warnings.ca.gov

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, **OTHER ADVERSE EFFECTS**

Overall Environmental Toxicity: Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

The ecological assessment for this material is based on an evaluation of its components.

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Fish
Dibutyltin dilaurate (77-58-7)	LC50 = 2 mg/L - Oryzias latipes (48h)
	LC50 = 3.1 mg/L - Brachydanio rerio (zebrafish)
Polyurethane resin (-)	Not available
Acrylated esters (-)	Not available

Component / CAS No.	Toxicity to Water Flea
Dibutyltin dilaurate (77-58-7)	EC50 = 0.463 mg/L - Daphnia magna
Polyurethane resin (-)	Not available
Acrylated esters (-)	Not available

Component / CAS No.	Toxicity to Algae
Dibutyltin dilaurate (77-58-7)	EC50 = 1 mg/L - Scenedesmus subspicatus (algae)
Polyurethane resin (-)	Not available
Acrylated esters (-)	Not available

Component / CAS No.	Partition coefficient
Dibutyltin dilaurate (77-58-7)	Log Kow = 4.44
Polyurethane resin (-)	Not available
Acrylated esters (-)	Not available

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA

"listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9
Packing Group: III
UN/ID Number: UN3082

Transport Label Required: Miscellaneous

Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): MIXTURE PENTAERYTHRITOL TRI/TETRAACRYLATE

Comments: Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to

non-bulk packagings transported by motor vehicles, rail cars or aircraft.

TRANSPORT CANADA

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9 Packing Group: III UN Number: UN3082

Transport Label Required: Miscellaneous Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): MIXTURE PENTAERYTHRITOL TRI/TETRAACRYLATE

ICAO / IATA

Dangerous Goods? X

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9 Packing Group: III

UN Number: UN3082

Transport Label Required: Miscellaneous

TECHNICAL NAME (N.O.S.): MIXTURE PENTAERYTHRITOL TRI/TETRAACRYLATE

Dangerous Goods? X

IMO

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9 UN Number: UN3082 Packing Group: III

Transport Label Required: Miscellaneous Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): MIXTURE PENTAERYTHRITOL TRI/TETRAACRYLATE

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are designated as "Active" on the TSCA Inventory or are not required to be listed.

Canada: One or more components of this product are NOT included on the Canadian Domestic Substances List (DSL). These components are included on the Canadian Non-Domestic Substances List (NDSL).

European Economic Area (including EU): When purchased and shipped from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

Australia: All components of this product are included in the Australian Inventory of Industrial Chemicals (AIIC) or are not required to be listed on AIIC.

New Zealand: This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory. When purchased from Allnex Korea or Chemart distributor this product is compliant with the ARECs (the Act on the Registration and Evaluation, etc. of Chemical Substances). All its components are either excluded, exempt, pre-notified and/or registered. When purchased from another allnex entity, please contact PSRA-KREACH@allnex.com to check the possibility to be covered by our Only Representative.

Philippines: One or more components of this product are NOT included on the Philippine (PICCS) inventory.

Taiwan: All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

Physical Hazards

Not applicable

Health Hazards

Acute toxicity (any route of exposure)
Reproductive toxicity
Skin Corrosion or Irritation
Respiratory or Skin Sensitization
Serious eye damage or eye irritation

16. OTHER INFORMATION

NFPA Hazard Rating (National Fire Protection Association)

Health: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

Reasons for Issue: Revised Section 1

Date Prepared: 06/02/2021 **Date of last significant revision:** 06/02/2021

Component - Hazard Statements

Dibutyltin dilaurate

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H341 - Suspected of causing genetic defects.

H360FD - May damage fertility. May damage the unborn child.

H370 - Causes damage to organs.

H372 - Causes damage to organs through prolonged or repeated exposure.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

Polyurethane resin

H319 - Causes serious eye irritation.

Acrylated esters

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H317 - May cause an allergic skin reaction.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

Emergency phone numbers for other regions

Asia Pacific

Australia: +61 1800 022 037 (Allnex Australia) China (PRC): +86(0)532 8388 9090 (NRCC)

India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)

Indonesia: 007 803 011 0293 (Carechem 24) Japan: +81 345 789 341 (Carechem 24) Korea: +82 2 3479 8401 (Carechem 24) Malaysia: +60 3 6207 4347 (Carechem 24)

New Zealand: +64 0800 803 002 (Allnex New Zealand)

Philippines: +63 2 231 2149 (Carechem 24) Taiwan: +886 2 8793 3212 (Carechem 24) Vietnam: +84 8 4458 2388 (Carechem 24) All Others: +65 3158 1074 (Carechem 24)

Europe

+44 (0) 1235 239 670 (Carechem 24)

Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)

Chile: +56 2 2582 9336 (Carechem 24)

Mexico and all others: +52-555-004-8763 (Carechem 24)

SDS: 0018405

Prepared By: Product Stewardship & Regulatory Affairs Department, http://www.allnex.com/contact

Date Prepared: 06/02/2021

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.