TOYO ALUMINIUM K.K.

ALUMINIUM POWDER AND PASTE



TECHNICAL DATA SHEET

SAMPLE DESCRIPTION					Date	: June 1, 2024
SAMPLE NAME:	Powder Shine PS-30S					
TYPE:	Silver aluminium pigment					
PRODUCT SPECIFICATION						
Characteristics	Typical value				Unit	Test Method
Non-volatile content	99.0 100.0	Min Max			% %	by Weight
INDICATIVE VALUES Characteristics Typical value Unit Test Method						
Characteristics	Characteristics		Typical	Typical value		Test Method
Volatile content			1.0	Max	%	by Weight
Solvent composition			None			
Non-volatile composition						
Aluminium flake			81.5	App.	%	by calculation
Oleic Acid			0.5	App.	%	by calculation
Methyl acrylate-methyl methacrylate copolymer			18.0	App.	%	by calculation
Particle size D50		30		μm	Microtrac	
Specific gravity			2.1		g/cm ³	by calculation

SHELF LIFE 36 months from production date

so months from production date

ASSOCIATED SAFETY DATA SHEET Refer to safety data sheet - SDS PS-30S

The data given in this technical data sheet are in accordance with the current status of our knowledge and experience. Technical details and information on our products are given as technical quality description and do not imply guaranteed properties in the legal sense. We reserve the right to modify any product data as a result of technical progress or new developments in the manufacturing process.