

Date of Preparation: August 16, 2022

Section 1: IDENTIFICATION		
Product Name:	WANNATE® HT-300	
Synonyms:	Hexamethylene Diisocyanate Polymer.	
Product Use:	Binding agents, intermediates; other isocyanate component for polyurethanes.	
Restrictions on Use:	Not available.	
Manufacturer/Supplier:	Wanhua Chemical (America) Co., Ltd. 3803 West Chester Pike, Suite 240 Newtown Square, PA 19073	
Phone Number:	Customer service telephone: 610-566-5297 Telephone in Canada: 613-796-1606	
Emergency Phone:	North America: Chemtrec 800-424-9300 (domestic) +1-703-527-3887 (International, collect calls accepted)	
Date of Preparation of SDS:	August 16, 2022	
Section 2: HAZARD(S) IDENTIFICATION		

GHS INFORMATION

Classification:	Acute Toxicity - Inhalation, Category 4
	Sensitization - Respiratory, Category 1
	Sensitization - Skin, Category 1
	Specific Target Organ Toxicity (Single Exposure), Category 3 - Respiratory
	Irritation

LABEL ELEMENTS Hazard

Signal Word:DangerHazardHarmful if inhaled.Statements:May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary Statements

Prevention: Avoid breathing mist, vapours, or spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing and eye protection. Wear respiratory protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. If skin irritation or rash occurs: Get medical attention.



Date of Preparation: August 16, 2022

If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse.

- **Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up.
- **Disposal:** Dispose of contents and container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.
Hexane, 1,6-diisocyanato-, homopolymer	Not available.	28182-81-2	99.6 - 100
Hexane, 1,6-diisocyanato-	Hexamethylene diisocyanate; HDI	822-06-0	≤ 0.40

Section 4. EIDST AID MEASURES

	Section 4: FIRST-AID MEASURES
Inhalation:	If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor.
	Acute and delayed symptoms and effects: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergy- prone people who have been sensitized to isocyanates or even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm. Asthma sufferers or people who easily get contact dermatitis should therefore not be exposed to isocyanates. The isocyanate odour does not provide sufficient warning of overexposure due to the high odour thresholds.
Eye Contact:	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor if you feel unwell.
	Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Isocyanates may cause severe watering, formation of solid particles in the eye fluid, glaucoma, photophobia (sensitivity to light), blepharospasm (uncontrollable winking), conjunctivitis (inflammation of the mucous membranes of the eye lids with possible discharge), keratitis (inflammation of the cornea) and damage the cornea (opacity or clouding).



	WANNATE® HT-300	
SAFETY DATA SHEET	Date of Preparation: August 16, 2022	
Skin Contact:	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.	
	Acute and delayed symptoms and effects: May cause an allergic skin reaction. May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching. Prolonged skin contact may cause redness, swelling, blistering and possible skin sensitization (dermatitis).	
Ingestion:	If swallowed: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.	
	Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.	
General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).	
Note to Physicians:	Symptoms may not appear immediately.	
Section 5: FIRE-FIGHTING MEASURES		

FLAMMABILITY AND EXPLOSION INFORMATION

Not flammable or combustible by OSHA/WHMIS criteria.

Sensitivity to Mechanical Impact: Sensitivity to Static Discharge:	This material is not sensitive to mechanical impact. This material is sensitive to static discharge at temperatures at or above the flash point.	
MEANS OF EXTINCTION Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, water spray or regular foam.	
	Large Fire: Water spray, fog or alcohol-resistant foam. Move containers from fire area if you can do it without risk.	
Unsuitable Extinguishing Media:	Not available.	
Products of Combustion:	Oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Isocyanate vapours.	
Protection of Firefighters:	Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.	
Section 6: ACCIDENTAL RELEASE MEASURES		

Emergency Procedures:	Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in
	immediate area).



WANNATE® HT-300 SAFETY DATA SHEET Date of Preparation: August 16, 2022 Personal Precautions: Do not touch or walk through spilled material. Use personal protection recommended in Section 8. **Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Methods for Containment: Stop leak if without risk. Do not flush to sewer or allow to enter waterways. Methods for Clean-Up: Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Other Information: See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Handling:

Do not swallow. Avoid breathing mist, vapours, or spray. Use only outdoors or in a wellventilated area. Contaminated work clothing should not be allowed out of the workplace. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines Component

Hexane, 1,6-diisocyanato-, homopolymer [CAS No. 28182-81-2]

ACGIH: No TLV established. **OSHA:** No PEL established.

Hexamethylene diisocyanate (HDI) [CAS No. 822-06-0]

ACGIH: 0.005 ppm (TWA); (1985)

OSHA: No PEL established.

PEL: Permissible Exposure Limit **TLV:** Threshold Limit Value **TWA:** Time-Weighted Average

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection:

Wear safety glasses. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3:20 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.



Date of Preparation: August 16, 2022

Hand Protection:	Wear protective gloves. Consult manufacturer specifications for further information.
Skin and Body Protection:	Wear protective clothing.
Respiratory Protection:	Wear respiratory protection. If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-18, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

Appearance:Light yellow liquid.Colour:Light yellow.Odoures.Odourless.Odour Threshold:Not available.Physical State:Liquid.pH:Not available.pMeting Point / Freezing Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Inwability (solid, gas):Not available.Inper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:9.81	Sect	ION 9: PHYSICAL AND CHEMICAL PROPERTIES
DefensionLight yeachtOdour:Odourless.Odour Threshold:Not available.Physical State:Liquid.pH:Not available.Melting Point / Freezing Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Appearance:	Light yellow liquid.
Odour Threshold:Not available.Physical State:Liquid.pH:Not available.Melting Point / Freezing Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Colour:	Light yellow.
Physical State:Liquid.pH:Not available.Melting Point / Freezing Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:9.81	Odour:	Odourless.
pH:Not available.Melting Point / Freezing Point:Not available.Initial Boiling Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Odour Threshold:	Not available.
Melting Point / Freezing Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Physical State:	Liquid.
Point:Not available.Initial Boiling Point:Not available.Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	pH:	Not available.
Boiling Range:Not available.Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	•	Not available.
Flash Point:228 °C (442.4 °F)Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Initial Boiling Point:	Not available.
Evaporation Rate:Not available.Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Boiling Range:	Not available.
Flammability (solid, gas):Not applicable.Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Flash Point:	228 °C (442.4 °F)
Lower Flammability Limit:0.9Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Evaporation Rate:	Not available.
Upper Flammability Limit:9.5Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Flammability (solid, gas):	Not applicable.
Vapor Pressure:0.00246 Pa at 20 °C (68 °F)Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Lower Flammability Limit:	0.9
Vapor Density:Not available.Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Upper Flammability Limit:	9.5
Relative Density:1.16 (Water = 1)Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Vapor Pressure:	0.00246 Pa at 20 °C (68 °F)
Solubilities:Immiscible in water.Partition Coefficient: n-9.81	Vapor Density:	Not available.
Partition Coefficient: n- 9.81	Relative Density:	1.16 (Water = 1)
	Solubilities:	Immiscible in water.
		9.81

Section 9: PHYSICAL AND CHEMICAL PROPERTIES



WANNATE® HT-300

Date of Preparation: August 16, 2022

•	
Auto-ignition Temperature:	460°C (860 °F)
Decomposition Temperature:	250 °C (482 °F)
Viscosity:	2500 ± 700cSt at 25 °C (77 °F)
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.
Density:	Not available.
Coefficient of Water/Oil Distribution:	Not available.
Section 10: STABILITY AND REACTIVITY	
Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to

Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Chemical Stability:	Stable under normal storage conditions.
Possibility of Hazardous Reactions:	HDI-based isocyanurates may undergo uncontrolled exothermic polymerization upon contact with incompatible materials, especially strong bases, such as triethylamine and sodium hydroxide, trialkyl phosphines, potassium acetate, many metal compounds soluble in organic media or at temperatures over 204°C. The resulting pressure build-up may rupture closed containers.
Conditions to Avoid:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Incompatible Materials:	Acids. Bases. Oxidizers. Water. Amines. Alcohols.
Hazardous Decomposition Products: Not available.	

Section 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE

Product Toxicity					
Oral:	Not available.				
Dermal:	Not available.				
Inhalation:	Not available.				
Component Toxicity Component Hexane, 1,6-diisocyanato-, homopolymer Hexamethylene diisocyanate		CAS No. 28182-81-2 822-06-0	LD₅o oral Not available. 350 mg/kg (mouse)	LD₅₀ dermal Not available. 570 uL/kg (rabbit)	L C ₅₀ 18500 mg/m³ (rat); 1H 30 mg/m³ (mouse);
Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.					
Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs.			tem. Lungs.		



Date of Preparation: August 16, 2022

Symptoms (including delayed and immediate effects)

- **Inhalation:** Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergy-prone people who have been sensitized to isocyanates or even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm. Asthma sufferers or people who easily get contact dermatitis should therefore not be exposed to isocyanates. The isocyanate odour does not provide sufficient warning of overexposure due to the high odour thresholds.
- Eye: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Isocyanates may cause severe watering, formation of solid particles in the eye fluid, glaucoma, photophobia (sensitivity to light), blepharospasm (uncontrollable winking), conjunctivitis (inflammation of the mucous membranes of the eye lids with possible discharge), keratitis (inflammation of the cornea) and damage the cornea (opacity or clouding). I
- **Skin:** May cause an allergic skin reaction. May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching. Prolonged skin contact may cause redness, swelling, blistering and possible skin sensitization (dermatitis).
- **Ingestion:** May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization:	Allergy-prone people who have been sensitized to isocyanates or even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm.
Respiratory Sensitization:	Allergy-prone people who have been sensitized to isocyanates or even have not been previously exposed to isocyanates may experience symptoms at concentrations as low as 0.0014 ppm.
Medical Conditions Aggravated By Exposure:	Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

- Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs.
- **Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity: This product does not contain any carcinogens or potential carcinogens above reportable thresholds as listed by ACGIH, IARC, OSHA, or NTP.

- Mutagenicity: Not available.
- Reproductive Effects: Not available.
- Developmental Effects Teratogenicity: Not available.

Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.



WANNATE® HT-300

Date of Preparation: August 16, 2022

Section 12: ECOLOGICAL INFORMATION			
Ecotoxicity:	Not available.		
Persistence / Degradability:	Not available.		
Bioaccumulation / Accumulation:	Not available.		
Mobility in Environment:	Not available.		
Other Adverse Effects:	Not available.		
Section 13: DISPOSAL CONSIDERATIONS			
Disposal Instructions: Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.			

Section 14: TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

Proper Shipping Name:	Not regulated.		
Class:	Not applicable.		
UN Number:	Not applicable.		
Packing Group:	Not applicable.		
Placard(s):	Not applicable.		

Canada Transportation of Dangerous Goods (TDG)

Proper Shipping Name:	Not regulated.
Class:	Not applicable.
UN Number:	Not applicable.
Packing Group:	Not applicable.
Placard(s):	Not applicable.

Section 15: REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Date of Preparation: August 16, 2022

SARA Title III Component	Section 302 (EHS) TPQ (Ibs.)	Section 304 EHS RQ (Ibs.)	CERCLA RQ (lbs.)	Section 313	RCRA CODE	CAA 112(r) TQ (lbs.)
Hexamethylene diisocyanate	Not listed.	Not listed.	100	313#	Not listed.	Not listed.
State Regulations MassachusettsUS Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)ComponentCAS No.Hexamethylene diisocyanate822-06-0Listed.						
New JerseyUS New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)ComponentCAS No.Hexamethylene diisocyanate822-06-0Listed.						
PennsylvaniaUS Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)ComponentCAS No.Hexamethylene diisocyanate822-06-0Listed.						
California						

California Prop 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS:	August 16, 2022		
Version:	1.0		
GHS SDS Prepared by:	Aegis Regulatory Inc.		
	Phone: 1 (519) 488-0351		
	www.aegisreg.com		