# TOYO ALUMINIUM K.K.

ALUMINIUM POWDER AND PASTE



## **TECHNICAL DATA SHEET**

PRODUCT DESCRIPTION Date: September 16, 2022

PRODUCT NAME: EMR-D46GRA

TYPE: Waterborne Colored Aluminium Paste

## PRODUCT SPECIFICATION

Characteristics	Typical value	Unit	Test Method	
Non-volatile content	53.0 Min	%	by Weight	
	57.0 Max	%		
Screen analysis >45µ	0.1 Max	%	Wet screen	
Color	In Accordance with our standard		Drawdown	

#### **INDICATIVE VALUES**

Characteristics	Typical value	Unit	Test Method
/olatile content	47.0 Max	%	by Weight
Solvent composition			
Isopropyl alcohol	45 App.	%	
Ion-volatile composition			
Aluminium flake	26.5 App.	%	
Acrylic acid-styrene copolymer	5 App.	%	
Phthalocyanine green	15.5 App.	%	
Silicon dioxide	8 App.	%	
pecific gravity	1.1	g/cm3	by calculation

#### SHELF LIFE

12 months from production date

### ASSOCIATED SAFETY DATA SHEET

Refer to safety data sheet - SDS EMR-D46GRA

The data given in this technical data sheet are in accordance with the current status of our knowledge and experience. Technical details and information on our products are given as technical quality description and do not imply guaranteed properties in the legal sense. We reserve the right to modify any product data as a result of technical progress or new developments in the manufacturing process.