烟台优联新材料有限公司

YANTAI YOLIAN ADVANCED MATERIALS CO.,LTD

Add:#406 Juzheng Building,No. 44 Zhujiang RD,Economic and Technological Development Dist., Yantai China Tel&Fax:0086-535-6393167 Email:export@modularresins.com Website: www.modularresins.com

Material Safety Data Sheet

1. Indentification of the Substance / Preparation and Company

Product Information: Fingerprint Resistant Agent

Product Number:HR-442

Suplier: Yantai Yolian Advanced Materials Co.,Ltd

Emergency Phone: 0086-535-6964678

2、 **Composition / Information on Ingredients**

English Name: Fingerprint Resistant Agent

Relevant identified uses of the substance or mixture and uses advised against

Identified uses: As powder coating raw materials

Chemical Abstracts Number (CAS No.): --

Percentage for Chemical Ingredient (%)

Hazard class and label elements of the product according to Canadian WHMIS:

GHS Hazard class

Non-hazardous substance or mixture

GHS label elements Pictogram(s): one

Signal word: None

Hazard statements: Not applicable.

Other Hazards: None.

Composition:

chemical name	Percentage composition	CAS No		
mineral wax	60%	8002-53-7		
PP wax	30%	235-847-2		
Other	10%	Secrecy		

3. Hazard Identification

Hazard Effect

Hazard Warnings for Health: The dust may cause irritation to eye, skin and respiratory system.

Hazard Warnings for Environment:It may cause dust pollution

Physical and Chemical Dangerous: None

Special Harm: None

Major State: Feel uncomfortable for eye, skin and respiratory system.

Hazard Category: (None)

YOLIAN MODULAR RESINS

烟台优联新材料有限公司

YANTAI YOLIAN ADVANCED MATERIALS CO.,LTD

Add:#406 Juzheng Building,No. 44 Zhujiang RD,Economic and Technological Development Dist.,Yantai China Tel&Fax:0086-535-6393167
Email:export@modularresins.com Website: www.modularresins.com

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation: Move to fresh air. Please seek medical advice if one feels difficult respiration

Skin Contact:Wash with plenty of water. Change clothes and seek medical treatment if one still feels irritated.

Eye Contact: Rinse with plenty of water. Seek medical treatment if one still feels irrited.

Ingestion: Drink plenty of water. If one feels uncomfortable or convulsive, stop eating and seek medical advice.

Major Disease and Harm Effect: Skin inflammation, respiratory difficulty, unrest or convulsion.

First-Aid Personal Protection Protective gloves.

Prompt to Doctor: Harm caused by dust.

5. Fire Fighting Measures

Suitable Extinguishing Media: CO2(Form, powder and Carbon dioxide.

Special Exposure Hazards: Dust explosion.

Special Extinguishing Procedure:

- 1. Wear protective clothing, helmet and use self-contained breathing apparatus.
- 2. Water can be used for small fire

Special Protection Equipment: Protective clothing, helmet and use self-contained breathing apparatus.

6. Accidental Release Measures

Personal Protection: Do not breathe dust. Avoid direct skin contact.

Environmental Protection: Do not blow the powder)

Methods for Cleaning Up: Clean with plenty of water

7. Handing and Storage

Handling: Handle with care.

Storage: Keep in cool, well-ventilated place (under 30 * C)

YOLIAN MODULAR RESINS

烟台优联新材料有限公司

YANTAI YOLIAN ADVANCED MATERIALS CO.,LTD

Add:#406 Juzheng Building,No. 44 Zhujiang RD,Economic and Technological Development Dist.,Yantai China Tel&Fax:0086-535-6393167
Email:export@modularresins.com Website: www.modularresins.com

8. Exposure Control /Personal Protection

Engineering Control:

Control Factor:

TWA/STEL/CEILING: --

Biotic Index: None

Personal Protection Equipment:

- Respiratory Protection: Wear mask or self-contained breathing apparatus if it is necessary
- Hand Protection: Protective gloves.Eye Protection: Protective goggles.
- Skin & Body Protection: Protective clothing

Hygiene Procedures: Keep protective clothing clean. Wash with soap water if contaminated by the dust.

9. Physical Chemical Properties/Characteristics

Appearance: Powder.	Form: Solid Powder.
Color: White	Oduor: None
PH value:	Melting Point / Melting Range: 120~145℃
Decomposition Temperature:	Flash Point:°F >250°C Test Method: ☑ Open Cup ☐ Close Cup
Spontaneous Temperature:	Exposure Limits: 30~70g/m3
Vapor Pressure:	Vapor Density:
pecific Gravity: 1.4~ 1.7 Solubility in Water: insoluble	
Conditions to Avoid: Avoid fire.	'
Incompatibility: Strong oxidant.	
Hazardous Decomposition Products: None	

10 Stability and Reactivity

Stability: Safe

Special Conditions of Hazardous Reaction: Dust explosion.

YOLIAN MODULAR RESINS

烟台优联新材料有限公司

YANTAI YOLIAN ADVANCED MATERIALS CO.,LTD

Add:#406 Juzheng Building,No. 44 Zhujiang RD,Economic and Technological Development Dist.,Yantai China Tel&Fax:0086-535-6393167
Email:export@modularresins.com Website: www.modularresins.com

11 Toxicological Information

Acute Toxicity:
Sensitive: Some people might be sensitive to these powders.
Chronic:
Exceptional Effect:
Local Effects:

12 Ecological Information

Possibility of Environmental Impact/Move:	
---	--

13 Disposal Information

Disposal Information:	(Bury or controlled incineration)	

14. Transport Information

Dangerous goods number:
UN NO:
Packing:

Packing method: --

Transport notes:: Compliance with traffic regulations, far away from the source of fire and inflammable and explosive dangerous goods. Avoid sun exposure and moisture

15 Regulatory Information

Regulatory information: --

Reference to the local, national, US, EU, CA and international regulations.

CAS No.	TSCA	EINECS	DSL	IECSC	NZIoC	PICCS	KECI	AICS
7631-86-9	~	√	√	1	4	4	4	4

TSCA:	CA: United States Toxic Substances Control Act Inventory			
EINECS:	European Inventory of Existing Commercial Chemical Substances			
DSL:	Canadian Domestic Substances List			
IECSC:	China Inventory of Existing Chemical Substances			
PICCS:	Philippines Inventory of Chemicals and Chemical Substances			
NZIoC: New Zealand Inventory of Chemicals				



烟台优联新材料有限公司

YANTAI YOLIAN ADVANCED MATERIALS CO.,LTD

Add:#406 Juzheng Building,No. 44 Zhujiang RD,Economic and Technological Development Dist.,Yantai China Tel&Fax:0086-535-6393167
Email:export@modularresins.com Website: www.modularresins.com

16. Documents statements

Reference:

Department of filling: Powder technology department

Date audit unit:

Modification instruction:

Note: This file is for the safety of the products of our company, more physical and chemical indicators, please refer to the product testing inspection report.