Polycin D-290 Technical Data Sheet



Product Identification

Polycin D-290 is a 100% solids castor oil based derivative designed for use as a polyol or reactive diluent in polyurethane coating systems. Polycin D-290 with its very low viscosity, will allow for the formulation of higher system solids with improved VOC reduction. Polycin D-290, will also impart the beneficial properties of castor oil derivatives such as improved flow and levelling.

	<u>Property</u>	<u>Value</u>	
Physical	Acid Value	1	
Properties	Appearance	Pale yellow liquid	
	Color, Gardner	3 – 4, typical	
	Density, lbs./gal, 25°C	7.99	
	Equivalent Weight	193	
	Functionality	2	
	Hydroxyl Value	290	
	Moisture, %	0.02	
	Non-Volatile, %	100	
	Specific Gravity, 25°C/25°C	0.960	
	Viscosity, cP @ 25°C	280	
Applications	 Formulation of 100% solids high performance polyurethane coatings 		
		Low VOC UV resistant 2-component industrial maintenance coatings and thermosetting OEM coatings	
	resistance, and chemical	 Property improvements such as; flexibility, adhesion, moisture resistance, and chemical resistance in coatings, adhesives, sealants, and elastomeric formulations 	
	 Low VOC force dry and metal 	= on the control and some teperation and primaries for placement and	
	 Low viscosity, solvent f melamine bake systems. 	zen viesten, terrent net pigment dispersione ier distillant dita	
Reduced	VOC and viscosity reduction in coatings, adhesives and sealants		
	Urethane Intermediates, Polymers		

For toxicity or regulatory information please consult the Material Safety Data Sheet.

Information contained in this technical data sheet is believed to be accurate. Vertellus Performance Materials Inc. assumes no liability and makes no warranty or representation that the information is correct or complete and EXPRESSLY DISCLAIMS ALL REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Final determination of suitability of any material and issues of patent infringement is the sole responsibility of the user who alone knows the conditions of intended use. Our customers should ensure that any product incorporating a Vertellus ingredient is safe for its intended use pursuant to applicable law and that any necessary disclosures to consumers have been made.

Vertellus Performance Materials Inc., 2110 High Point Road, Greensboro, NC 27403 USA

USA Tel: 800-227-2436 USA Fax: 336-854-4058 USA Email: VPM-TechServices@vertellus.com

Web: www.vertellus.com