

## Oxidized Petrolatum LA 1531-20

### Oxidized Petrolatum

#### Product Description

Oxpet LA 1531-20 is a first intent oxidized petrolatum. It is recommended for use as a rust preventative. It is designed to provide excellent rust protection in formulating industrial lubricating oils, greases, hydraulic fluids, slushing oils and various other protective compounds. With its non-staining characteristics, this product is ideally suited for formulations that call for a high level of rust protection.

Nominal dosages would range from 0,1 to 5.0 wt.% of the finished lubricant. Oxpet LA 1531-20 is compatible with most mineral base oils, white oils and synthetic base stocks.

The acids present in the Oxidate can be neutralized with bivalent metaloxides, e.g. Calcium-hydroxide, giving end-products of a high molecular weight and wax-like nature with excellent water-resistant and anti-corrosion.

#### Physical Properties

Properties	Unit	Test Method	Specification
Total Acid Number	mg/KOH/g	ASTM D 664	17 - 22
Relative Density at 100°C	kg/m <sup>3</sup>		800 - 900
Saponification Number	mg/KOH/g	DIN 51559	47 (typical)
Congeeing Point	°C	ASTM D 938	40 - 50
Ash Content	wt, %	ASTM D 482	max. 0.5
Colour, dilute		ASTM D 1500	8.0 (typical)
Flash Point. COC	°C	ASTM D 92	min. 150

Revision date: August 10, 2010

The information presented herein is based on the best data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied, regarding the accuracy of the information or the use of our product or products; nor shall anything contained herein be constructed to constitute a permission or recommendation to practice any invention covered by a patent owned by Sonneborn Refined Products B.V., any of its division, or by other, without a license from the owner of the patent.