

**SDS**: 0072547

**Date Prepared:** 05/14/2019

# **SAFETY DATA SHEET**

# 1. IDENTIFICATION

Product Name: EBECRYL® 8315 radiation curing resins

Synonyms: None

**Product Description:** Acrylated resin

Molecular Formula: Mixture Molecular Weight: Mixture

Intended/Recommended Use: Surface coating

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

For Product and all Non-Emergency Information call your local Allnex contact point or contact us at http://www.allnex.com/contact

# EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC) See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ®, TM or \* as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

#### 2. HAZARDS IDENTIFICATION

#### **GHS Classification**

Skin Corrosion / Irritation Hazard Category 2 Serious Eye Damage / Eye Irritation Hazard Category 2A Skin Sensitizer Hazard Category 1B

#### LABEL ELEMENTS



# Signal Word WARNING

#### **Hazard Statements**

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction

# **Precautionary Statements**

Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

IF ON SKIN: Wash with plenty of soap and water.

Specific treatment (see supplemental first aid instructions on this label).

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Date Prepared: 05/14/2019

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local and national regulations.

# Hazards Not Otherwise Classified (HNOC), Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

# -\_\_\_\_

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **HAZARDOUS INGREDIENTS**

Component / CAS No.	%	GHS Classification	Carcinogen
Methacrylate monomer	18 - 20	Skin Irrit. 3 (H316)	-
-		Eye Irrit. 2A (H319)	
		Skin Sens. 1B (H317)	
Acrylated urethane	15 - 17	Skin Irrit. 2 (H315)	-
-		Eye Irrit. 2A (H319)	
Acrylated resin	65 - 75	Skin Irrit. 2 (H315)	-
-		Eye Irrit. 2A (H319)	

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

#### 4. FIRST AID MEASURES

# **First-aid Measures**

#### Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. Apply artificial respiration if patient is not breathing. Obtain medical attention immediately.

#### **Skin Contact:**

Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

#### **Eve Contact:**

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

# Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

# Most Important Symptoms and Effects, Acute and Delayed

None known.

SDS: 0072547

Date Prepared: 05/14/2019

#### **Immediate Medical Attention and Special Treatment**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

# **Notes To Physician:**

No specific measures have been identified.

\_\_\_\_\_

#### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media:**

Use water spray or fog, carbon dioxide or dry chemical.

# **Unsuitable Extinguishing Media:**

high pressure water jet.

#### **Protective Equipment:**

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

# **Special Hazards:**

Keep containers cool by spraying with water if exposed to fire.

# 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

#### **Methods For Cleaning Up:**

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

#### **Environmental Precautions:**

None known.

#### References to other sections:

See Sections 7, 8 and 13 for additional information.

# 7. HANDLING AND STORAGE

#### **HANDLING**

**Precautions:** Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and eye/face protection.

**Special Handling Statements:** Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization. Provide good ventilation of working area (local exhaust ventilation if necessary).

#### STORAGE

To avoid product degradation and equipment corrosion, do not use iron, copper or aluminum containers or equipment. Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

Storage Temperature: Store at 4 - 40 °C 39 - 104 °F

Reason: Quality.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Engineering Measures:**

Utilize a closed system process where feasible. Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

# **Respiratory Protection:**

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

#### Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

# **Eye Protection:**

Prevent eye and skin contact. Provide eye wash fountain and safety shower in close proximity to points of potential exposure. Wear eye/face protection such as chemical splash proof goggles or face shield.

#### Skin Protection:

Prevent contamination of skin or clothing when removing protective equipment. Barrier creams may be used in conjunction with the gloves to provide additional skin protection. Wear impermeable gloves and suitable protective clothing.

#### **Hand Protection:**

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

#### Gloves for repeated or prolonged exposure - non exhaustive list:

Butyl rubber (VB), thickness: > 0.30 mm, break through time: up to 480 min

# Gloves for short term exposure/splash protection - non exhaustive list:

Nitrile rubber (NBR), thickness: 0.38 mm, break through time: up to 30 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

#### Not suitable gloves - non exhaustive list:

Nitrile rubber (NBR), thickness: 0.12 mm

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

#### Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

# **Exposure Limit(s)**

No values have been established.

# **Biological Exposure Limit(s)**

No values have been established.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Color: clear to hazy, colorless to amber

Appearance:liquidOdor:acrylateBoiling Point:> 100 °CMelting Point:Not available

Vapor Pressure:< 0.1 kPa @ 25 °C</th>Specific Gravity/Density:1.1 - 1.15 g/cm³Vapor Density:Not available

Percent Volatile (% by wt.): < 0.5

pH: Not applicable Saturation In Air (% By Vol.): Not available

**Evaporation Rate:** Not available Non-volatile **Solubility In Water:** 0 - 1.5 g/L Minimal

Volatile Organic Content: Not available

Flash Point: 154 °C 309 °F Cleveland Open Cup

Flammable Limits (% By Vol):
Autoignition Temperature:
Decomposition Temperature:
Partition coefficient

Not available
Not available

(n-octanol/water):

Odor Threshold: Not available Viscosity (Kinematic): Not available

Viscosity (Dynamic): 5400 - 11400 cP @ 25 °C Viscous liquid

**Explosive Properties:** None. **Oxidizing Properties:** No

#### 10. STABILITY AND REACTIVITY

Reactivity: No information available

Stability: Stable.

Conditions To Avoid: Extreme heat, sparks, open flame, and oxidizers. Prevent loss of dissolved

oxygen. Avoid excessive heat to closed containers. Stable under normal temperatures and pressure. Avoid direct exposure to sunlight. Excessively high

temperatures and ignition sources.

Polymerization: May occur

**Conditions To Avoid:** Hazardous exothermic polymerization can occur when heated. Avoid contact with

oxidizing agents, free radical initiators, sunlight or ultraviolet light, bases or

amines.

Materials To Avoid: Iron or rust may trigger rapid exothermic polymerization.

Sunlight or ultraviolet light.

Excessive heat

Primary and secondary aliphatic amines.

Avoid sources of free radicals, peroxides and metal ions.

Hazardous polymerization may occur.

**Hazardous Decomposition** 

**Products:** 

oxides of nitrogen hydrocarbons soot when burned

#### Smoke, carbon monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin, Eyes, Oral.

**Acute toxicity - oral:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - dermal:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - inhalation:** Not Classified **-** Based on available data and/or professional judgment, the classification criteria are not met.

Skin corrosion / irritation: Causes skin irritation

Serious eye damage / eye irritation: Causes serious eye irritation

Respiratory sensitization: Not Classified - Based on available data and/or professional judgment, the

classification criteria are not met.

**Skin sensitization:** May cause an allergic skin reaction

**Carcinogenicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Germ cell mutagenicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Reproductive toxicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure:** Not Classified. **-** Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - repeated exposure:** Not Classified. **-** Based on available data and/or professional judgment, the classification criteria are not met.

**Aspiration hazard:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

# PRODUCT TOXICITY INFORMATION

#### **ACUTE TOXICITY DATA**

oral	rat	Acute LD50	>	2000 mg/kg
dermal	rabbit	Acute LD50	>	2000 mg/kg
inhalation	rat	Acute LC50 4 hr	>	5 mg/l (Dust/Mist)

# **LOCAL EFFECTS ON SKIN AND EYE**

Acute Irritation Skin Irritating
Acute Irritation eye Irritating

#### **ALLERGIC SENSITIZATION**

Sensitization Skin Sensitizing
Sensitization respiratory No data

#### **GENOTOXICITY**

# **Assays for Gene Mutations**

Ames Salmonella Assay No data

Date Prepared: 05/14/2019

#### OTHER INFORMATION

The product toxicity information above has been estimated.

The toxicological properties of this material have not been fully determined.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

# 11. TOXICOLOGICAL INFORMATION

#### HAZARDOUS INGREDIENT TOXICITY DATA

The toxicological properties of methacrylate monomer have not been fully determined. Moderately irritating to eyes and mildly irritating to the skin. Produced dermal sensitization (guinea pigs). Prolonged exposure may produce central nervous system depression. May cause irritation of respiratory passages following inhalation exposure.

The toxicological properties of acrylated urethane have not been fully investigated. Direct contact with this material may cause moderate irritation to eyes and skin.

Acrylated resin may cause moderate eye and skin irritation. Delayed removal from the skin, may lead to blistering of the skin, even if no immediate irritation was noted.



WARNING: Cancer – www.P65Warnings.ca.gov

#### 12. ECOLOGICAL INFORMATION

# TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

This material is not classified as dangerous for the environment.

The ecological assessment for this material is based on an evaluation of its components.

#### RESULTS OF PBT AND VPVB ASSESSMENT

Not determined

# HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Fish
Methacrylate monomer (-)	Not available
Acrylated urethane (-)	Not available
Acrylated resin (-)	Not available

Component / CAS No.	Toxicity to Water Flea
Methacrylate monomer (-)	Not available
Acrylated urethane (-)	Not available
Acrylated resin (-)	Not available

Component / CAS No.	Toxicity to Algae
Methacrylate monomer (-)	Not available
Acrylated urethane (-)	Not available
Acrylated resin (-)	Not available

Component / CAS No.	Partition coefficient
Methacrylate monomer (-)	Not available
Acrylated urethane (-)	Not available
Acrylated resin (-)	Not available

SDS: 0072547

# 13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

# 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

#### **US DOT**

Dangerous Goods? Not applicable/Not regulated

#### TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

#### ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

#### **IMO**

Dangerous Goods? Not applicable/Not regulated

#### SPECIAL PRECAUTIONS FOR USER

Date Prepared: 05/14/2019

Protect against external heat sources above +40°C/104°F.

#### 15. REGULATORY INFORMATION

# **Inventory Information**

**United States (USA):** All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

**Canada:** One or more components of this product are NOT included on the Canadian Domestic Substances List (DSL).

**European Economic Area (including EU):** When purchased from an Allnex legal entity based in the EEA (EU or Norway), this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt and/or registered.

**Australia:** One or more components of this product have NOT yet been included in the Australian Inventory of Chemical Substances (AICS) or assessed by NICNAS.

China: One or more components of this product are NOT included on the Chinese (IECSC) inventory.

**Japan:** All components of this product are included on the Japanese (ENCS and ISHL) inventories or are not required to be listed on the Japanese inventories.

**Korea:** One or more components of this product are NOT included on the Korean (ECL) inventory. The company has obtained the required notification approvals from Ministry of Environment (MOE) as per the "Act on the Registration and Evaluation of Chemical Substances of Korea (K-REACH)" for the component(s) not listed in the Korean Inventory (ECL). The product can be imported/manufactured in Korea ONLY under specific conditions.

**Philippines:** All components of this product are either listed on the Philippine (PICCS) inventory, have been assessed by Environmental Management Bureau (EMB) or are exempt from notification requirements.

**Taiwan:** All components of this product are included in the Taiwan chemical substance inventory or are not required to be listed on the Taiwan chemical substance inventory (TCSI).

#### OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

#### PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA

#### **Physical Hazards**

Not applicable

# **Health Hazards**

Skin Corrosion or Irritation Respiratory or Skin Sensitization Serious eye damage or eye irritation

# 16. OTHER INFORMATION

# NFPA Hazard Rating (National Fire Protection Association)

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Date Prepared: 05/14/2019

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

Reasons For Issue: New Format

**Date Prepared:** 05/14/2019 **Date of last significant revision:** 05/14/2019

Methacrylate monomer

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Acrylated urethane

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Acrylated resin

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

#### **Emergency phone numbers for other regions**

#### **Asia Pacific**

Australia: +61 1800 022 037 (Allnex Australia)

China (PRC): +86(0)25 8547 7110 (Jiangsu registration center) / +86(0)532 8388 9090 (NRCC)

India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)

Indonesia: 007 803 011 0293 (Carechem 24) Japan: +81 345 789 341 (Carechem 24) Korea: +82 2 3479 8401 (Carechem 24) Malaysia: +60 3 6207 4347 (Carechem 24)

New Zealand: +64 0800 803 002 (Allnex New Zealand)

Philippines: +63 2 231 2149 (Carechem 24) Taiwan: +886 2 8793 3212 (Carechem 24) Vietnam: +84 8 4458 2388 (Carechem 24) All Others: +65 3158 1074 (Carechem 24)

**Europe** 

+44 (0) 1235 239 670 (Carechem 24)

Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

**Latin America** 

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)

Chile: +56 2 2582 9336 (Carechem 24)

Mexico and all others: +52-555-004-8763 (Carechem 24)

Prepared By: Product Stewardship & Regulatory Affairs Department, http://www.allnex.com/contact

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.