

## SAFETY DATA SHEET

---

### 1. IDENTIFICATION

<b>Product Name:</b>	<b>EBECRYL® 452 radiation curing resins</b>
<b>Synonyms:</b>	None
<b>Product Description:</b>	Radiation curing resin
<b>Molecular Formula:</b>	Mixture
<b>Molecular Weight:</b>	Mixture
<b>Intended/Recommended Use:</b>	Coatings & Inks
<b>Uses advised against:</b>	This product should not be used in any application where unreacted liquid product is intended to come in direct contact with skin or nails. Reason: sensitizing properties.

Allnex USA Inc., 9005 Westside Parkway, Alpharetta, Georgia 30009, USA

**For Product and all Non-Emergency Information call** your local Allnex contact point or contact us at <http://www.allnex.com/contact>

**EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:**

+1-866-928-0789 (toll free) or +1-215-207-0061 (Carechem 24 - Allnex29003-NCEC)

See Section 16 for Emergency phone numbers for other regions.

Trademarks indicated with ®, TM or \* as well as the allnex name and logo are registered, unregistered or pending trademarks of Allnex Netherlands BV or its directly or indirectly affiliated allnex Group companies.

---

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Skin Corrosion / Irritation Hazard Category 2

Serious Eye Damage / Eye Irritation Hazard Category 2A

Skin Sensitizer Hazard Category 1B

Aquatic Environment Acute Hazard Category 2

Aquatic Environment Chronic Hazard Category 2

#### LABEL ELEMENTS



#### Signal Word

WARNING

#### Hazard Statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction  
 Toxic to aquatic life  
 Toxic to aquatic life with long lasting effects

### Precautionary Statements

Wash face, hands and any exposed skin thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Avoid release to the environment.  
 IF ON SKIN: Wash with plenty of soap and water.  
 Specific treatment (see supplemental first aid instructions on this label).  
 Take off contaminated clothing and wash it before reuse.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Dispose of contents/container in accordance with local and national regulations.

### Hazards Not Otherwise Classified (HNOC), Other Hazards

Polymerization may occur from excessive heat, contamination or exposure to direct sunlight.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification
Acrylic acid 79-10-7	< 0.3	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) STOT Single 3 (H335) Skin Corr. 1A (H314) Eye Dam. 1 (H318) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)
Polyol acrylate -	15 - 30	Eye Irrit. 2A (H319) Skin Sens. 1B (H317) Aquatic acute 2 (H401)
Alkyd resin -	50 - 70	Skin Irrit. 2 (H315) Eye Irrit. 2A (H319)
Acrylated resin -	15 - <25	Skin Irrit. 2 (H315) Eye Irrit. 2A (H319) Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

## 4. FIRST AID MEASURES

### First-aid Measures

**Inhalation:**

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

**Skin Contact:**

Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

**Eye Contact:**

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical advice if there are persistent symptoms.

**Ingestion:**

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

**Most Important Symptoms and Effects, Acute and Delayed**

None known.

**Immediate Medical Attention and Special Treatment**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Notes To Physician:**

No specific measures have been identified.

---

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:**

Use water spray or fog, carbon dioxide or dry chemical.

**Unsuitable Extinguishing Media:**

full water jet.

**Protective Equipment:**

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See SDS Section 8 (Exposure Controls/Personal Protection).

**Special Hazards:**

Keep containers cool by spraying with water if exposed to fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:**

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

**Methods For Cleaning Up:**

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

**Environmental Precautions:**

Avoid release to the environment.

**References to other sections:**

See Sections 7, 8 and 13 for additional information.

---

## 7. HANDLING AND STORAGE

### HANDLING

**Precautions:** Avoid release to the environment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and eye/face protection.

**Special Handling Statements:** Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid excessive heat, contamination or exposure to direct sunlight to prevent polymerization.

### STORAGE

Store in a cool, dry, well ventilated place and keep container tightly closed. Keep away from heat sources and direct sunlight.

**Storage Temperature:** Store at 4 - 40 °C 39 - 104 °F

**Reason:** Quality.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering Measures:

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

### Respiratory Protection:

For operations where inhalation exposure can occur use an approved respirator. Recommendations are listed below. Other protective respiratory equipment may be used based on user's own risk assessment. Recommended respirators include those certified by NIOSH.

#### Recommended:

Full Face Mask with organic vapor cartridge, Type A filter (BP >65°C)

### Eye Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield. Eyewash equipment and safety shower should be provided in areas of potential exposure.

### Skin Protection:

Avoid skin contact. Wear impermeable gloves and suitable protective clothing. Barrier creams may be used in conjunction with the gloves to provide additional skin protection.

### Hand Protection:

Wear protective gloves. Recommendations are listed below. Other protective materials may be used based on user's own risk assessment. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Replace gloves immediately when torn or any change in appearance (dimension, color, flexibility etc.) is noticed.

#### Gloves for short term exposure/splash protection - non exhaustive list:

Laminated multilayer gloves, break through time: > 60 min

Nitrile rubber (NBR), thickness: > 0.56 mm, break through time: < 60 min

The chemical resistance depends on the type of product and amount of product on the glove. Therefore gloves need to be changed when in contact with chemicals.

#### Not suitable gloves - non exhaustive list:

Latex gloves

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. Use PE gloves as under gloves for

difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

**Additional Advice:**

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

---

**Exposure Limit(s)****79-10-7 Acrylic acid**

OSHA (PEL):	Not established
ACGIH (TLV):	(skin) 2 ppm (TWA)
Other Value:	1 ppm skin (Allnex)

**Biological Exposure Limit(s)**

No values have been established.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Color:</b>	yellow to brown
<b>Appearance:</b>	liquid resin
<b>Odor:</b>	ester-like
<b>Boiling Point:</b>	> 100 °C 212 °F
<b>Melting Point:</b>	Not applicable
<b>Vapor Pressure:</b>	0.013 Pa @ 20 °C
<b>Specific Gravity/Density:</b>	1 - 1.2 g/cm <sup>3</sup>
<b>Vapor Density:</b>	Not available
<b>Percent Volatile (% by wt.):</b>	0.1 - 0.3
<b>pH:</b>	Not applicable
<b>Saturation In Air (% By Vol.):</b>	Not applicable
<b>Evaporation Rate:</b>	Not applicable
<b>Solubility In Water:</b>	negligible
<b>Volatile Organic Content:</b>	Not available
<b>Flash Point:</b>	> 100 °C 212 °F Cleveland Open Cup
<b>Flammable Limits (% By Vol):</b>	Not available
<b>Autoignition Temperature:</b>	Not available
<b>Decomposition Temperature:</b>	Not available
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>Odor Threshold:</b>	Not available
<b>Viscosity (Kinematic):</b>	Not available
<b>Viscosity (Dynamic):</b>	Low viscous liquid
<b>Flammability:</b>	Not available
<b>Oxidizing Properties:</b>	No

---

**10. STABILITY AND REACTIVITY**

**Reactivity:** No information available

**Stability:** Stable.

**Conditions To Avoid:** Avoid direct contact with heat sources. Avoid direct exposure to sunlight. Avoid exposure to strong UV sources. Avoid friction with temperature increase as result.

Loss of polymerization inhibitor. Loss of dissolved air. Avoid temperatures higher than 60°C.

**Polymerization:** May occur

**Conditions To Avoid:** Avoid contact with free radical initiators. Avoid contact with strong oxidizing agents. Avoid contact with bases or amines. Hazardous polymerization can occur when exposed to direct sunlight. Hazardous exothermic polymerization can occur when heated. Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers

**Materials To Avoid:** Avoid contact with active metals.  
Avoid free radical producing initiators. Avoid contact with peroxides. Avoid contact with reactive metals. Avoid contact with strong alkalis. They give an exothermic reaction with the product. Unintentional contact with them should be avoided.

**Hazardous Decomposition Products:** oxides of carbon  
hydrocarbons  
smoke  
soot

---

## 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Skin, Eyes, Oral.

**Acute toxicity - oral:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - dermal:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Acute toxicity - inhalation:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin corrosion / irritation:** Causes skin irritation

**Serious eye damage / eye irritation:** Causes serious eye irritation

**Respiratory sensitization:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Skin sensitization:** May cause an allergic skin reaction

**Carcinogenicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Germ cell mutagenicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Reproductive toxicity:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Specific target organ toxicity (STOT) - repeated exposure:** Not Classified. - Based on available data and/or professional judgment, the classification criteria are not met.

**Aspiration hazard:** Not Classified - Based on available data and/or professional judgment, the classification criteria are not met.

## PRODUCT TOXICITY INFORMATION

### ACUTE TOXICITY DATA

oral	rat	Acute LD50	> 2000	mg/kg
dermal	rabbit	Acute LD50	> 2000	mg/kg
inhalation	rat	Acute LC50	4 hr	No data

### LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	dermal	Irritating
Acute Irritation	eye	Irritating

### ALLERGIC SENSITIZATION

Sensitization	Skin	Sensitizing
Sensitization	respiratory	No data

### GENOTOXICITY

#### Assays for Gene Mutations

Ames Salmonella Assay	No data
-----------------------	---------

### OTHER INFORMATION

The product toxicity information above has been estimated.

The toxicological properties of this material have not been fully determined.

Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms such as redness, blistering, dermatitis, etc.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

### HAZARDOUS INGREDIENT TOXICITY DATA

Acrylic acid has acute oral (rat) LD50, acute dermal (rabbit) LD50, and acute inhalation (rat, 4-hr, vapor) LC50 values of 617-1405 mg/kg, >2000 mg/kg, and >1730 ppm (>5.1 mg/L), respectively. Direct contact may cause severe eye irritation with corneal injury which may result in permanent impairment of vision and even blindness. Chemical burns may occur. Vapors may also cause severe eye irritation. Skin contact may cause severe skin burns. Symptoms may include pain, severe local redness, swelling, blistering and tissue damage. Inhalation overexposure may cause severe irritation of the respiratory tract. Repeated overexposures may have effects on the kidney. Acrylic acid did not cause cancer when given to rats in their drinking water throughout their lifetime. No skin tumors occurred in mice receiving repeated skin applications of acrylic acid at nonirritating doses. A slight, not statistically significant increase in skin tumors reported in another study is difficult to interpret due to the low incidence and conflicting information regarding dose. This substance has been toxic to the fetus in laboratory animals at doses toxic to the mother but has not been found to cause birth defects in laboratory animals. In laboratory animal studies with acrylic acid, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. The results of in vitro genetic toxicity studies are predominantly negative. Animal genetic toxicity studies are negative (not mutagenic).

Polyol acrylate has acute oral (rat) and dermal (rabbit) LD50 values >2000 mg/kg bw, respectively. Serious corneal opacity and considerable redness and oedema were observed in an eye irritation study with rabbits. No dermal reactions were observed in a skin irritation study with rabbits. This material may cause dermal sensitization. Based on all available data, genotoxicity is not expected. No systemic toxicity was observed up to the highest dose level in a sub-chronic study via oral route with rats. Developmental toxicity is not expected and reproductive performance were not affected with a structural analogue.

The toxicological properties of acrylated resin have not been fully investigated. Moderately irritating to eyes and skin. May cause allergic skin reaction in individuals previously sensitized to acrylates.

Acrylate resin has an acute oral (rat) LD50 and acute dermal (rabbit) LD50 values of > 5000 mg/kg and > 2000 mg/kg, respectively. Direct contact with this material may cause moderate eye and skin irritation. Repeated or prolonged

skin contact may cause allergic skin reactions.



**WARNING:** Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## 12. ECOLOGICAL INFORMATION

### TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

**Overall Environmental Toxicity:** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

The ecological assessment for this material is based on an evaluation of its components.

### RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

### HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Fish
Acrylic acid (79-10-7)	LC50 = 27 mg/L - <i>Salmo gairdneri</i> (96h)
Polyol acrylate (-)	Not available
Alkyd resin (-)	Not available
Acrylated resin (-)	Not available

Component / CAS No.	Toxicity to Water Flea
Acrylic acid (79-10-7)	EC50 = 47 mg/L - <i>Daphnia magna</i> (48h) EC50 = 95 mg/L - <i>Daphnia magna</i> (48h) NOEC = 12-19 mg/L - <i>Daphnia magna</i> (21d)
Polyol acrylate (-)	Not available
Alkyd resin (-)	Not available
Acrylated resin (-)	Not available

Component / CAS No.	Toxicity to Algae
Acrylic acid (79-10-7)	EC50 = 0.13 mg/L - <i>Scenedesmus subspicatus</i> (72h) EC10 = 0.03 mg/L - <i>Scenedesmus subspicatus</i> (72h)
Polyol acrylate (-)	Not available
Alkyd resin (-)	Not available
Acrylated resin (-)	Not available

Component / CAS No.	Partition coefficient
Acrylic acid (79-10-7)	0.38 - 0.46
Polyol acrylate (-)	Not available
Alkyd resin (-)	Not available



Acrylated resin (-)	Not available
---------------------	---------------

### 13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this SDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this SDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

### 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

#### US DOT

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9

Packing Group: III

UN/ID Number: UN3082

Transport Label Required:           Miscellaneous  
  Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): ACRYLATED RESIN

Comments:                               Marine Pollutants - DOT requirements specific to Marine Pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars or aircraft.

#### TRANSPORT CANADA

Dangerous Goods? X

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9

Packing Group: III

UN Number: UN3082

Transport Label Required:           Miscellaneous  
  Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): ACRYLATED RESIN

#### ICAO / IATA

Dangerous Goods? X

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9

Packing Group: III

UN Number: UN3082

Transport Label Required: Miscellaneous

TECHNICAL NAME (N.O.S.): ACRYLATED RESIN

## IMO

Dangerous Goods? X

UN PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport Hazard Class: 9

UN Number: UN3082

Packing Group: III

Transport Label Required: Miscellaneous  
Marine Pollutant

Marine Pollutant

TECHNICAL NAME (N.O.S.): ACRYLATED RESIN

## SPECIAL PRECAUTIONS FOR USER

Protect against external heat sources above +40°C/104°F.

---

## 15. REGULATORY INFORMATION

### Inventory Information

**United States (USA):** All components of this product are designated as "Active" on the TSCA Inventory or are not required to be listed.

**Canada:** One or more components of this product are NOT included on the Canadian Domestic Substances List (DSL).

**Australia:** One or more components of this product have NOT yet been included in the Australian Inventory of Industrial Chemicals (AIIC) or assessed by AICIS.

**New Zealand:** This product is approved or exempt under the Hazardous Substances and New Organisms (HSNO) Act.

**China:** One or more components of this product are NOT included on the Chinese (IECSC) inventory. The company has obtained the required notification approvals from the Ministry of Environmental Protection (MEP) as per the "Environmental Administrative Measures for New Chemical Substance" for the component(s) not listed in the Chinese Inventory (IECSC). The product can be imported/manufactured in China ONLY under specific conditions.

**Japan:** All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

**Korea:** One or more components of this product are NOT included on the Korean (ECL) inventory.

**Philippines:** One or more components of this product are NOT included on the Philippine (PICCS) inventory.

**Taiwan:** One or more components of this product are NOT included in the Taiwan chemical substance inventory (TCSI).

**Switzerland:** All components of this product are exempt from the new substance notification requirements for

Switzerland (SR 813.11 art. 24-26).

**Turkey:** When purchased directly from Allnex by a Turkish legal entity, this product is compliant with the PRE-registration requirements of KKDIK as all its components are either pre-registered, excluded and/or exempt.

#### **OTHER ENVIRONMENTAL INFORMATION**

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

#### **PRODUCT HAZARD CATEGORY UNDER SECTIONS 311 AND 312 OF EPCRA**

##### **Physical Hazards**

Not applicable

##### **Health Hazards**

Skin Corrosion or Irritation

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

---

## **16. OTHER INFORMATION**

#### **NFPA Hazard Rating (National Fire Protection Association)**

Health: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 1 - Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures.

**Reasons for Issue:** Revised Section 1

**Date Prepared:** 06/01/2021

**Date of last significant revision:** 06/01/2021

#### **Component - Hazard Statements**

Acrylic acid

H226 - Flammable liquid and vapor.

H302 - Harmful if swallowed.

H312 - Harmful in contact with skin.

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation.

H400 - Very toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

Polyol acrylate

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H401 - Toxic to aquatic life.

Alkyd resin

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Acrylated resin

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

- H319 - Causes serious eye irritation.
- H400 - Very toxic to aquatic life.
- H410 - Very toxic to aquatic life with long lasting effects.

### Emergency phone numbers for other regions

#### Asia Pacific

Australia: +61 1800 022 037 (Allnex Australia)  
China (PRC): +86(0)532 8388 9090 (NRCC)  
India: 000 800 100 7479 (toll free) or +65 3158 1198 (Carechem 24)  
Indonesia: 007 803 011 0293 (Carechem 24)  
Japan: +81 345 789 341 (Carechem 24)  
Korea: +82 2 3479 8401 (Carechem 24)  
Malaysia: +60 3 6207 4347 (Carechem 24)  
New Zealand: +64 0800 803 002 (Allnex New Zealand)  
Philippines: +63 2 231 2149 (Carechem 24)  
Taiwan: +886 2 8793 3212 (Carechem 24)  
Vietnam: +84 8 4458 2388 (Carechem 24)  
All Others: +65 3158 1074 (Carechem 24)

#### Europe

+44 (0) 1235 239 670 (Carechem 24)

#### Middle East, Africa

+44 (0) 1235 239 671 (Carechem 24)

#### Latin America

Brazil: +55-800-707-7022 (toll free) or +55-11-98149-0850 (Suatrans 24)  
Chile: +56 2 2582 9336 (Carechem 24)  
Mexico and all others: +52-555-004-8763 (Carechem 24)

---

Prepared By: Product Stewardship & Regulatory Affairs Department, <http://www.allnex.com/contact>

---

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.

---