

### BRITOL<sup>®</sup> 35 USP White Mineral Oil

Page 1 of 6

---

Revision Date: 5/29/2015 Version: 5 Issue Date: 6/4/2015

Sonneborn, LLC urges the recipient of this Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety you should (1) notify your employees, agents and contractors of the information of this sheet, (2) furnish a copy to each of your customers for the product and (3) request your customers to inform their employees and customers as well.

---

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

---

### Identification of the substance or preparation

White Mineral Oil

### Use of substance/preparation:

Highly refined mineral oil is typically used as a blending base in a variety of applications including cosmetic, pharmaceutical, food and general industrial.

### Company identification

Sonneborn, LLC  
600 Parsippany Road, Suite 100  
Parsippany, NJ 07054 USA

### Emergency telephone number

Chemtrec (24hrs): 800-424-9300  
Sonneborn: 724-756-2210

---

## 2. HAZARDS IDENTIFICATION

---

GHS Classification :Not classified as dangerous under EC/GHS-criteria

Human Health Hazards :None

Physico-chemical and environmental hazards and effects: None

### HMIS RATING USA

Health: 0	Flammability: 1	Reactivity: 0	PPI: -
-----------	-----------------	---------------	--------

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

INGREDIENT	% BY WEIGHT	CAS #	HAZARD	DANGER SYMBOL(S)
White Mineral Oil	100	8042-47-5		

---

## 4. FIRST AID MEASURES

---

### Swallowing

Do not induce vomiting. Obtain medical attention immediately. This is not a toxic substance.

## BRITOL<sup>®</sup> 35 USP White Mineral Oil

---

### Inhalation

No emergency care anticipated. If mineral oil mist is present, see Section 8.

### Skin

No emergency care anticipated. Wash skin with soap and water.

### Eye contact

Flush eyes thoroughly with water for several minutes. Obtain medical attention if discomfort persists.

---

## 5. FIRE-FIGHTING MEASURES

---

<b>Flash Point:</b> >93.4°C (200°F) PMCC, ASTM D93
--

### NFPA CLASSIFICATION USA

Health: 0	Flammability: 1	Reactivity: 0	Special provisions: -
-----------	-----------------	---------------	-----------------------

### Extinguishing media

Suitable: Extinguish with:

- dry chemical
- carbon dioxide (in case of small fires)
- water fog
- foam
- sand or earth

Unsuitable: Do not use water jet. Oil will float on water and can spread any fire.

### Special fire fighting procedures

Do not direct a solid stream of water or foam into burning material; this may cause spattering and spread the fire. If a rail or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

### Special protective equipment for firefighters

Self-contained breathing apparatus.

### Unusual fire and explosion hazards

Following products may be produced during a fire: Oxides of carbon.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### Personal precautions

Wear suitable protective equipment.

### Environmental precautions

Avoid runoff to sewers or waterways. Dike area of spill to prevent spreading and pump liquid to salvage tank. Waste: avoid washing into watercourses. Use methods consistent with local regulations or incinerate.

## BRITOL<sup>®</sup> 35 USP White Mineral Oil

---

### Methods for cleaning up

Dike to contain spill. Absorb on inert material such as sand, earth, vermiculite. Stop the leak if it can be done without risk. Floor may be slippery; use care to avoid falling.

---

## 7. HANDLING AND STORAGE

### HANDLING

Do not handle at temperatures >+40°C, unless wearing appropriate protective equipment.

### Ventilation

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

### STORAGE

#### Storage requirements

Keep away from heat, sparks and flame. Do not store at temperatures: >+40°C without proper safety review of storage equipment. Store protected from light.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

COMPONENT	COUNTRY	TYPE/REMARK	VALUE
Mineral Oil Mist		If used in a way that generates A "mist" observe the limits for Mineral Oil Mist. TWA (mist), ACGIH STEL (mist), ACGIH	5mg/m <sup>3</sup> 10mg/m <sup>3</sup>

### OCCUPATIONAL EXPOSURE CONTROLS

#### Respiratory protection

None expected to be needed. If used in a way that generates a vapor/mist, wear an organic vapor respirator.

#### Hand protection/protective gloves

Wear oil resistant gloves.

#### Eye protection

Face shield or chemical splash goggles in case of splashing.

#### Skin protection

Wear protective clothing, such as long sleeves to minimize skin contact.

#### Environmental Exposure Controls:

Store in a second containment to catch leakages

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

## BRITOL<sup>®</sup> 35 USP White Mineral Oil

---

Physical State:	Liquid
Color:	Water-white
Odor:	None or Mild Petroleum
Odor Threshold:	N/A

### Important health, safety and environmental information

Flammability	No Data
Evaporation Rate	No Data
Decomposition Temperature	No Data
Flash Point:	>93.4°C (200°F) Method: PMCC, ASTM D93
Upper explosion limits:	Not determined
Lower explosion limits:	Not determined
Vapor Pressure:	<0.1 kPa at 20°C
Density:	0.81 – 0.89 g/cm <sup>3</sup> at 20°C
Bulk Density:	Not available
Solubility in Water:	Insoluble
Solubility in organic solvents:	Soluble
Kinematic viscosity:	> 20.5 mm <sup>2</sup> /s at 40°C, > 100 SUS @ 100°F
Boiling Point:	> 230°C
PH:	N/A
Specific gravity (H <sub>2</sub> O=1)	<1
Partitioning coefficient	log POW: >6 This product is soluble in oil.
Vapor Density:	N/A
Percent volatiles	Nil
Autoignition Temperature:	No Data
Melting Point:	N/A

---

## 10. STABILITY AND REACTIVITY

---

**Stability:** Stable

**Conditions/Materials to avoid:** Extreme temperature and direct sunlight/ultraviolet light and strong oxidizing agents.

### Hazardous combustion products

Burning can produce the following combustion products: Oxides of carbon and Soot

**Hazardous polymerization:** Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

### GENERAL

No evidence of harmful effects from available information.

## BRITOL<sup>®</sup> 35 USP White Mineral Oil

---

### 12. ECOLOGICAL INFORMATION

---

This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant.

---

### 13. DISPOSAL CONSIDERATIONS

---

Dispose of in accordance with appropriate Federal, State and local regulations or incinerate.

---

### 14. TRANSPORT INFORMATION

---

#### ADR/RID/IMDG/ICAO

This product is not regulated by ADR / RID / IMDG / ICAO.

USA – This product is not regulated by DOT, Freight Description Road: 65 Petroleum Oil, N.O.I.B.N.

#### TDG-CANADA

This product is not regulated by TDG.

---

### 15. REGULATORY INFORMATION

---

#### EC/GHS classification

According to EC/GHS regulations this product is not classified or labeled

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40CFR372 (for SARA 313). This information must be included in SDS's that are copied and distributed for this material.

Components present in this product at a level which could require reporting under the statute are:

\*\*\*\*NONE\*\*\*\*

#### New Jersey Worker and Community Right-To-Know Act (Labeling Requirements)

Chemical name	CAS#	New Jersey TS Number
White Mineral Oil	8042-47-5	

EPA Hazard Categories (SARA 311, 312): None

WHMIS Classification: This product is not a WHMIS controlled product.

#### Chemical Inventory

<u>Canada:</u>	The ingredients of this product are on the DSL.
<u>Europe:</u>	The ingredients of this product are on the EINECS inventory.
<u>United States:</u>	The ingredients of this product are on the TSCA inventory.
<u>Australia:</u>	The ingredients of this product are on the AICS inventory.
<u>China:</u>	This product is on the IECSC inventory.

### BRITOL<sup>®</sup> 35 USP White Mineral Oil

Page 6 of 6

---

<u>Japan:</u>	The ingredients of this product are on the ENCS inventory.
<u>Korea:</u>	This product is listed on the Existing Chemicals List (ECL).
<u>Philippines:</u>	This product is on the PICCS.

---

## 16. OTHER INFORMATION

---

### **Recommended uses and restrictions**

Please consult the product and/or application information bulletins for this product.

### **Further information, Europe**

Where appropriate, use CE approved personal protection equipment.

This Safety Data Sheet conforms to EC Directive 1907/2006 and amendments.

The opinions expressed herein are those of qualified experts within Sonneborn, LLC. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn, LLC it is the user's obligation to determine the conditions of safe use of the products.